

davide groppi

HANDBOOK 2024

INDEX

WIRELESS / SENZA FILO	13
35MM	15
BUGIA	19
PoPuP	23
POST PRANDIUM	27
QuiQuoQua	33
TeTaTeT	37
TeTaTeT Flûte	43
VIS À VIS	47
TABLE / TAVOLO	51
ABA 45	53
ANIMA	57
CALVINO	61
FM	65
MOON T	69
MORSETTO	75
PALPEBRA	81
PIGRECO	85
FLOOR / TERRA	89
ABA 120	91
BANNER	95
HASHI	99
MASAI	103
MISTER	109
MOON F	113
MOVIE	117
ORIGINE	121
PABLO	127
Q	131
SAMPEI	135
SHOJI	141

SUSPENSION / SOSPENSIONE	145
CARTESIO	147
CATHODE	151
FOSBURY	159
LED IS MORE	163
LOUIS XIV	167
MAGIA	173
MISS	185
MOON	191
NEURO	199
OVO	203
OVONELPIATTO	207
REFLEX S	211
SHANGHAI	215
SIMBIOSI	219
SOTTILE	223
SOTTOSOPRA	229
SPY	233
WALL / PARETE	237
DOT P	239
DUET	247
EDISON'S NIGHTMARE	251
FILM	255
FOIL	259
FOLDER	263
LINET	267
MIRA	271
MIRA MAGNETIC	275
MORSETTO P	279
PIÙ	283
RAIL	287
REFLEX	291
SHADE	295
SOL 1	299
SOL 2	303
SPOT	307
TOAST	316

CEILING / SOFFITTO	319
ASINTOTO	321
AURORA	327
DOT PL 51	331
HAKO PL	335
MINI PL 51	339
NULLA PL	343
PUNTO PL	347
PUNTO 2 PL	351
SANMARTINO	355
SPY PL	359
TRICK TRACK	363
RECESSED / INCASSO	367
BUCO 58	369
BUCO R	373
DOT R	379
MINI 51	385
MINI BIT 51	389
MIRA R	393
NULLA	397
PUNTO	407
PURA	413
QUAD	417
SYSTEMS / SISTEMI	421
ENDLESS	423
FLASH	453
INFINITO	469
OHM	481
UTOPIA	491

TRACKS - PROFILES / BINARI - PROFILI	497
BINARIO TRIFASE	499
COLIBRÌ	513
FRAMELESS	523
LIGHTLINE 0808	531
LIGHTLINE 1010	536
LIGHTLINE 1508	540
LIGHTLINE 2612	544
LIGHTLINE 7454	548
OUTDOOR / ESTERNO	553
BELLADINOTTE	555
BUBKA	559
BUBKA BOLLARD	563
BUIO - TRIMLESS	568
BUIO - TRIM	572
BUIO - SPOT	576
CHILLOUT	585
GRILLO	589
HAZARD	593
IMU	599
JULIET	603
LENTA	607
NEURO OUTDOOR	611
NUIT	615
ORIGINE OUTDOOR	619
OUT 44	623
OUT 58	629
OUT 100	633
Q²	637
SAMPEI 440 OUTDOOR	641
SHOJI OUTDOOR	645
SPOT OUTDOOR	649
BULBS / LAMPADINE	652
DG111 LED MODULES / MODULI LED DG111	653
DRIVERS / ALIMENTATORI	654
COMMON ACCESSORIES / ACCESSORI COMUNI	658
SUSPENSION KITS / KIT DI SOSPENSIONE	660
COMMERCIAL TERMS / CONDIZIONI COMMERCIALI	662

INDEX

Our codification system consists of a fifteen-digit structure defined as follows:

Il nostro sistema di codifica prevede una struttura a quindici cifre così definita:

1	A	3	0	0	0	3	0	0		2	7		0	0
PRODUCT FAMILY FAMIGLIA PRODOTTO					FINISH FINITURA		INTERNAL USE ONLY SOLO PER USO INTERNO			COLOUR TEMPERATURE TEMPERATURA COLORE		ELECTRIFICATION ELETTRIFICAZIONE		

Finish / Finitura

0	0	Standard
0	1	Polished Chrome / Cromo Lucido
0	3	Matt White / Bianco Opaco
0	4	Matt Black / Nero Opaco
0	8	Brushed Brass / Ottone Spazzolato
1	0	Stainless Steel / Inox
1	3	Black Brushed Stainless Steel / Inox Nero Spazzolato
1	4	Brushed Chrome / Cromo Spazzolato
1	5	Natural Brass / Ottone Naturale
1	8	Matt Gold / Oro Opaco
1	9	Polished Gold / Oro Lucido
2	6	Total Black / Nero Totale
2	7	Gravity Black
2	8	Polished Black Chrome/ Cromo Nero Lucido
2	9	Brushed Bronze / Bronzo Spazzolato
3	2	Copper Oxide
3	4	Matt White - Black Bicolour / Bianco - Nero Opaco Bicolore
3	6	Brushed Black / Nero Spazzolato
3	8	Blasted Inox / Inox Pallinato

Colour temperature / Temperatura di colore

0	0	Light source not included / Sorgente non inclusa
2	2	2200K
2	7	2700K
3	0	3000K
9	6	2700K / 6500K (Tunable White)
9	8	RGBW (Warm White)
9	9	RGB

Electrification / Elettrificazione

0	0	ON/OFF
0	1	DALI
0	2	TRIAC/IGBT
0	3	1-10V
0	4	PUSH
0	5	DIM (DALI - PUSH - 1-10V - TRIAC)
0	6	Dimmer on board
0	7	DALI - PUSH - 1-10V
2	0	CLASS III
4	0	ENDLESS
4	1	ENDLESS CASAMBI

The Davide Groppi handbook is a confidential document and cannot be disclosed. In this document the drawings and technical information are to be considered indicative. All product features and technical measurements are available on our website davidegropi.com

Il manuale tecnico Davide Groppi è un documento riservato e non può essere divulgato. In questo documento i disegni e le informazioni tecniche sono da ritenersi indicative. Tutte le caratteristiche di prodotto e le misure tecniche sono disponibili sul nostro sito davidegropi.com





GUIDELINE TO PROPERLY READ THE CATALOGUE / GUIDA ALLA LETTURA DEL CATALOGO

General data on the product
Informazioni generali sul prodotto

Mounting - Lighting - Use - Material - Finish - Note

Model specifications
Specifiche modello














Technical data - Certifications - Codes

NULLA		Davide Groppi / 2010	
Recessed / Direct / Indoor			
Material	Metal		
Finish	00 Standard		
Note	Recessed luminaire. Visible 18/25 mm diameter hole. NULLA 18 and NULLA 25: lamp extractable for maintenance. Apparecchio illuminante da incasso. Foro visibile con diametro di 18/25 mm. NULLA 18 e NULLA 25: apparecchio estraibile per manutenzione.		
	NULLA - 23° 14W 24V DC 2700K - 425lm / 3000K - 458lm CR1 >90 Beam: 23° UGR <19 Driver not included CE 	Standard - 2700K Standard - 3000K	14410000.27.20 14410000.30.20
	NULLA - 32° 14W 24V DC 2700K - 538lm / 3000K - 579lm CR1 >90 Beam: 32° UGR <19 Driver not included CE 	Standard - 2700K Standard - 3000K	1A2110000.27.20 1A2110000.30.20

Compulsory and optional accessories
Accessori obbligatori e accessori opzionali

Accessories finishes and specifications - Codes

Reference model
Modello di riferimento

NULLA		Davide Groppi / 2010	
Compulsory accessories / Accessori obbligatori			
Installation kits / Kit d'installazione			
	Plasterboard flange 12,5 mm / Flangia per cartongesso 12,5 mm		Not included
	Matt Black Cut-out Ø 21 mm Minimum space for mounting 100 mm IP65	NULLA	1A2200400.00.00
	Plasterboard flange 12,5 mm / Flangia per cartongesso 12,5 mm		Not included
	Matt Black Cut-out Ø 22 mm Minimum space for mounting 190 mm	NULLA 18	1A2210400.00.00
	Plasterboard flange 12,5 mm / Flangia per cartongesso 12,5 mm		Not included
	Matt Black Cut-out Ø 35 mm Minimum space for mounting 190 mm IP65	NULLA 25	1A2170400.00.00
	Plasterboard flange 12,5 mm / Flangia per cartongesso 12,5 mm		Not included
	Matt Black Cut-out Ø 35 mm Minimum space for mounting 190 mm IP65	NULLA 25	1A3980400.00.00
	Plasterboard flange (bottom) = 12,5 mm / Flangia (da sotto) per cartongesso = 12,5 mm		Not included
	Matt Black Cut-out Ø 35 mm Minimum space for mounting 190 mm IP65	NULLA 25	1A4960400.00.00
Drivers / Alimentatori			
	Driver / Alimentatore 220-240V(100-127V) 24V/16W(15W)/IP20/DALI		Not included
	Driver / Alimentatore 220-240V(100-127V) 24V/20W(15W)/IP20/PUSH		Not included
	Driver / Alimentatore 220-240V 24V/20W/IP20/TRIAC/IGBT		Not included
			12024180.24
			120240870.24
			120240850.24

PICTOGRAPHY / SIMBOLOGIA



Class II appliance: appliance whose protection against electric shock is not only relevant to the main insulation, but also includes additional safety measures, such as dual insulation or reinforced insulation. These measures do not include ground devices as protection and do not depend on the installation conditions.



Class III appliance: appliance whose safety against electric shock is based on safe extra low voltage power supply. Compliance with legislation is guaranteed only if the appliance is powered by a SELV safety transformer/driver in compliance with legislation in force. The appliance must not be connected to ground conductors.



Degree of protection against access of foreign bodies, dust and water.



Appliance with this symbol can only use low pressure bulbs or bulbs with safety glass.



Do not use cold light lamps.



To prevent the risk of fire, maintain the minimum distance indicated from the bulb with lighting objects. This distance should be measured along the optical axis of the appliance to the closest lighting object.



Color Rendering Index: the degree of colour distortion under a given light source in comparison with a reference light source. The optimum colour rendition index is Ra=100.



The luminous flux, measured in lumen, indicates the quantity of light perceived by the human eye emitted by a light source. In Davide Groppi lights with an integrated module, the delivered lumen flux is obtained from the photometric measurement. In lights with a lightbulb included, the luminous flux is indicated provided by the manufacturer of the lightbulb.

Apparecchio in classe II: apparecchio in cui la protezione contro le scariche elettriche non interessa solamente l'isolamento principale, bensì comprende misure di sicurezza supplementari, come il doppio isolamento o l'isolamento rinforzato. Tali misure non comprendono mezzi di messa a terra come protezione e non dipendono dalle condizioni di installazione.

Apparecchio in classe III: apparecchio in cui la sicurezza contro la scossa elettrica si basa sull'alimentazione a bassissima tensione di sicurezza. La conformità alla normativa è garantita solo se l'apparecchio è alimentato da un trasformatore/driver di sicurezza SELV conforme alla normativa in vigore. L'apparecchio non deve essere collegato a conduttori di messa a terra.

Livello di protezione contro l'accesso di corpi estranei, polvere e acqua.

Apparecchio che può utilizzare solamente lampadine a bassa pressione o con vetro di protezione.

Non utilizzare lampade a luce fredda.

Per prevenire il rischio di incendio, mantenere come minimo la distanza indicata dalla lampadina agli oggetti illuminati. Tale distanza va misurata lungo l'asse ottico dell'apparecchio all'oggetto illuminato più vicino.

Color Rendering Index: grado di alterazione dei colori sotto una data illuminazione in confronto ad una sorgente luminosa di riferimento. L'indice ottimale di resa cromatica Ra è pari a 100.

Il flusso luminoso, misurato in lumen, indica la quantità di luce percepita dall'occhio umano emessa da una sorgente luminosa. Nelle lampade Davide Groppi con modulo integrato è indicato il reale flusso luminoso ricavato dal rilievo fotometrico. Nelle lampade in cui è inclusa una lampadina è indicato il flusso luminoso fornito dal fabbricante della lampadina stessa.



Luminaire designed to be powered by ENDLESS conductive tape.



Luminaire integrated with Casambi, the Bluetooth Low Energy (BLE) technology for lighting control.



Luminaire with Extradark comfort system. The Extradark system associates an optical TIR PMMA lens to an element that geometrically shields the light beam viewing angle to obtain highly uniform lighting and full beam control. The polished black light shield is used to control the mirror reflection of the light, perfectly controlling the unified glare rating (UGR* <19).

Apparecchio predisposto per essere alimentato dal tape conduttivo ENDLESS.

Apparecchio in cui è integrata la tecnologia Bluetooth Low Energy (BLE), per il controllo dell'illuminazione, Casambi.

Apparecchio dotato di Extradark comfort system. Il sistema Extradark è l'unione di un'ottica TIR in PMMA ottico a un elemento che schermata geometricamente l'angolo di visione del fascio luminoso ottenendo un'elevata uniformità di illuminamento e il pieno controllo dell'emissione. L'elemento ottico schermante, con finitura nero lucido, permette di controllare la riflessione speculare della luce e quindi di controllare in maniera perfetta l'indice di abbagliamento (UGR* <19).

*Unified Glare Rating

All Davide Groppi products, except those specifically indicated,
are equipped with electronic light sources (LED).
The selection of diodes is carried out with the utmost care to guarantee
the highest levels of performance and luminous uniformity.

Tutti i prodotti Davide Groppi, salvo quelli specificamente indicati,
sono equipaggiati con fonti luminose elettroniche (LED).
La selezione dei diodi è eseguita con la massima cura per garantire
i più alti livelli di prestazione e di uniformità luminosa.

WIRELESS / SENZA FILO



Those dear old slides. Nobody pays any attention to them anymore.
It's the smallest lamp in our collection.
It's an idea, a thought, a pendant, something you can wear.
The pulsating light and the images you choose to display on it
make 35MM unique and exceptional.

La vecchia, cara diapositiva. Purtroppo ormai in disuso.
È la più piccola lampada della nostra collezione.
È un'idea, un pensiero, un ciondolo, luce da indossare.
La luce pulsante e le immagini personalizzabili
rendono 35MM un progetto unico ed eccezionale.


35MM

Alessandra Dallagiovanna - Davide Groppi / 2009

Objects / Diffuse / Wireless

Material Metal - Polycarbonate
Finish .00 Standard


Note Battery-operated wearable luminaire. Matt white front. Glossy black back. Customised image not included. Intermittent light. *Apparecchio illuminante da indossare a batteria. Fronte bianco opaco. Retro nero lucido. Immagine personalizzabile non inclusa. Luce intermittente.*



35MM
0,3W
ON/OFF
Batteries 2xCR2032 included
CE IP20

Standard - ON/OFF

|1A2640000.00.00 |



BUGIA

Daide Groppi / 2018



A lightweight and soft light.
A lamp designed to enjoy wonderful diffuse light but without an electrical cable.

Una luce morbida e leggera.
Una lampada pensata per godere di una meravigliosa luce diffusa
senza il vincolo del cavo elettrico.


BUGIA

Davide Groppi / 2018


Table / Diffuse / Wireless

Material Metal - Methacrylate
Finish .18 Matt Gold

Note Chargeable table luminaire. Matt white diffuser. Gold finish base. *Apparecchio illuminante da tavolo a batteria ricaricabile. Diffusore bianco opaco. Base verniciata dorata. Autonomia della batteria: 9 ore.*



BUGIA


2W
3000K - 120lm
CRI >90
ON/OFF
Driver with plug not included
USB cable included
CE  IP20

Matt Gold - 3000K - ON/OFF

| 1A2351800.30.00 |

Optional accessories / Accessori opzionali

Drivers / Alimentatori



Driver with plug / Alimentatore con spina		Not included
Matt Black	Input 110-240V - 50/60Hz Output 5V DC - 2A - 10W - IP20	1Z0000088

Other accessories / Altri accessori



USB to USB-C cable / Cavo da USB a USB-C		Included
Matt Black	Length 1 m	1Z0000132





Light*Music*Wireless

Created to give you both light and music any place, at any time.

PoPuP accompanies you during your unforgettable moments.

The sounds it produces are dynamic and of excellent quality.

Light and sound can also be enjoyed separately.

Listen to the light.

Light*Music*Wireless

Ideata per ottenere luce e musica in qualsiasi luogo ed in qualunque momento.

PoPuP permette di vivere un'esperienza musicale emozionante

grazie ad un suono ampio e dinamico.


Luce e suono sono utilizzabili separatamente.

Ascolta la luce.

Table / Direct / Wireless

Material Metal - Methacrylate
Finish .03 Matt White

Note Chargeable table luminaire and speaker. Magnetic fixing stem. *Apparecchio illuminante e diffusore audio da tavolo a batteria ricaricabile. Battery life: 12 hours light only and 30 hours audio only at medium volume. Stelo con fissaggio magnetico. Autonomia della batteria: 12 ore solo luce e 30 ore solo audio a medio volume.*



PoPuP


2W
 3000K - 183lm
 CRI >80
 ON/OFF
 5W Audio - 50-20000Hz
 Driver with plug included
 CE IP20

Matt White - 3000K - ON/OFF

| 1A2610300.30.00 |


Optional accessories / Accessori opzionali

Drivers / Alimentatori



Driver with plug / Alimentatore con spina		Included
Matt Black	Input 110-240V - 50/60Hz Output 10000mAh - 4,2-14V DC 18W - IP20	1Z1530030

Other accessories / Altri accessori



Rechargeable battery / Batteria ricaricabile		Included
Matt White	12V DC - NiMH 3700mAh	1A2620300.00.00



POST PRANDIUM

Davide Groppi / 2023



During a meal with friends, a ladle is reused to scoop up the light
and serve it onto the table.

A project from many years ago, today in a new wireless version.

Archiproducts Design Award 2023

Durante una cena tra amici, un mestolo è ri-utilizzato
per raccogliere la luce e servirla al tavolo.

Un progetto di molti anni fa, oggi rieditato in versione wireless.

Archiproducts Design Award 2023


POST PRANDIUM

Davide Groppi / 2023

Table / Direct / Wireless

Material Metal - Methacrylate
Finish .01 Polished Chrome

Note Chargeable table luminaire. Details with polished gold finish. Matt black *Apparecchio illuminante da tavolo a batteria ricaricabile. Dettagli con finitura oro lucido. Base nero opaco. Autonomia della batteria: 9 ore.*
 base. Battery life: 9 hours.



POST PRANDIUM

2W
 3000K - 171lm
 CRI >90
 ON/OFF
 Driver with plug not included
 USB cable included


CE IP20

Polished Chrome - 3000K - ON/OFF

| 1A4550100.30.00 |

Optional accessories / Accessori opzionali

Drivers / Alimentatori



Driver with plug / Alimentatore con spina		Not included
Matt Black	Input 110-240V - 50/60Hz Output 5V DC - 2A - 10W - IP20	1Z0000088

Other accessories / Altri accessori



USB to USB-C cable / Cavo da USB a USB-C		Included
Matt Black	Length 1 m	1Z0000132





POST PRANDIUM





QuiQuoQua

Daide Groppi / 2017

The light where you want it.

A unique suspension lamp with a rechargeable battery.
The light source is applied magnetically to a metal dish that hangs from the ceiling
using a very thin steel wire. The effect is delicately elegant.
QuiQuoQua takes light where it is needed, without the limitation of electric wires.


La luce dove vuoi.

Un'inedita lampada a sospensione a batteria ricaricabile.
La parte ottica è applicata magneticamente ad una parabola e sospesa
attraverso un sottilissimo cavo in acciaio. L'effetto è delicatamente elegante.
QuiQuoQua offre la possibilità di portare la luce dove si desidera
senza il vincolo del cavo elettrico.

Suspension / Direct / Wireless

Material Metal - Methacrylate
Finish .03 Matt White

Note Chargeable suspension luminaire. Magnetic fixing LED module. *Apparecchio illuminante a sospensione a batteria ricaricabile. Matt white rose. AISI 304 stainless steel suspension cable. Modulo LED con fissaggio magnetico. Rosone bianco opaco. Battery life: 8 hours. Cavo di sospensione in inox AISI 304. Autonomia della batteria: 8 ore.*



QuiQuoQua


5W
 3000K - 345lm
 CRI >80
 ON/OFF
 Driver with plug included
 CE IP20

Matt White - 3000K - ON/OFF

1A2630300.30.00


Optional accessories / Accessori opzionali

Drivers / Alimentatori



Driver with plug / Alimentatore con spina		Included
Matt Black	Input 110-240V - 50/60Hz Output 9V DC - 2A - 20W - IP20	1Z1120170

LED modules / Moduli LED




LED module / Modulo LED		Included
Matt Black	5W - 3000K - 345lm - CRI >80 Rechargeable lithium battery 9V DC Li-Ion 5800mAh - Battery life 8 hours	1A0570400.30.00

Suspension kits / Kit di sospensione



Sloped ceiling suspension kit / Kit di sospensione per soffitto inclinato		Not included
	Nickel plated - 1 Piece	1A0510000.00.00





A timeless icon with an eye on the future.
Portable and rechargeable, the greatest expression of freedom.
With TeTaTeT, every table becomes a meeting place, a complete dining experience.
Its light caresses those it illuminates with pure emotion.
Equipped with Touch technology and a magnetic fixing base.
Mention of Honour XXIV Compasso d'Oro ADI Award, 2016

Un'icona senza tempo, con lo sguardo rivolto al futuro.
Portatile e ricaricabile, la massima espressione della libertà.
Grazie a TeTaTeT, ogni tavola diventa un luogo d'incontro, ogni cena un'emozione.
La sua luce accarezza i volti e amplifica le sensazioni.
Dotata di accensione touch, il fissaggio alla base è magnetico.
Menzione d'Onore XXIV Compasso d'Oro ADI, 2016


Compasso d'Oro ADI
Mention of Honour
2016



Table / Direct / Wireless

Material	ABS - Metal - Methacrylate		
Finish	.03 Matt White	.04 Matt Black	.18 Matt Gold

Note Chargeable table luminaire. Magnetic fixing stem. Touch ON/OFF. Battery life: 12 hours. *Apparecchio illuminante da tavolo a batteria ricaricabile. Stelo con fissaggio magnetico. ON/OFF touch. Autonomia della batteria: 12 ore.*




TeTaTeT

2W
2700K - 165lm / 3000K - 178lm
CRI >90
ON/OFF
Driver with plug included
CE IP20

Matt White - 2700K - ON/OFF	1A0310300.27.00
Matt White - 3000K - ON/OFF	1A0310300.30.00
Matt Black - 2700K - ON/OFF	1A0310400.27.00
Matt Black - 3000K - ON/OFF	1A0310400.30.00
Matt Gold - 2700K - ON/OFF	1A0311800.27.00
Matt Gold - 3000K - ON/OFF	1A0311800.30.00


Optional accessories / Accessori opzionali

Drivers / Alimentatori



Driver with plug / Alimentatore con spina		Included
Matt Black	Input 110-240V - 50/60Hz Output 6V DC - 1A - 6W - IP20	1Z0000073

Other accessories / Altri accessori



Rechargeable battery / Batteria ricaricabile		Included
Matt White	4,8V DC - NiMH 4300mAh	1A0430300.00.00
Matt Black	4,8V DC - NiMH 4300mAh	1A0430400.00.00
Matt Gold	4,8V DC - NiMH 4300mAh	1A0431800.00.00

Optional accessories / Accessori opzionali

Other accessories / Altri accessori



Table / Tavolino	Not included
Matt White	1A4020300.00.00
Matt Black	1A4020400.00.00



TeTaTeT Flûte

Davide Groppi / 2017



This is an evolution of our TeTaTeT lamp.
The lamp head is lightweight and appears to be floating in air.
The transparent stem brings to mind the glasses used in the classic "mise en place".
Magnetic fixing base.


L'evoluzione del nostro modello TeTaTeT.
La testa appare leggera e sospesa nel vuoto.
Lo stelo trasparente evoca i bicchieri utilizzati nelle classiche "mise en place".
Il fissaggio alla base è magnetico.

Table / Direct / Wireless

Material Metal - Methacrylate
Finish .03 Matt White

Note Chargeable table luminaire. Magnetic fixing transparent stem. Magnetic LED module. Battery life: 9 hours.

Apparecchio illuminante da tavolo a batteria ricaricabile. Stelo trasparente con fissaggio magnetico. Modulo LED con fissaggio magnetico. Autonomia della batteria: 9 ore.



TeTaTeT Flûte

2W
 2700K - 167lm / 3000K - 180lm
 CRI >90
 ON/OFF
 Driver with plug not included
 USB cable included


CE IP20

Matt White - 2700K - ON/OFF
 Matt White - 3000K - ON/OFF

1A2360300.27.00
 1A2360300.30.00

Optional accessories / Accessori opzionali

Drivers / Alimentatori




Driver with plug / Alimentatore con spina

Not included

Matt Black Input 110-240V - 50/60Hz
 Output 5V DC - 2A - 10W - IP20
 1Z0000088

LED modules / Moduli LED



LED module / Modulo LED

Included

Matt White 2W - 2700K - 167lm - CRI >90
 Rechargeable lithium battery 5V DC Li-Ion
 4800mAh - Battery life 9 hours
 1A5360300.27.00
 2W - 3000K - 180lm - CRI >90
 Rechargeable lithium battery 5V DC Li-Ion
 4800mAh - Battery life 9 hours
 1A5360300.30.00

Optional accessories / Accessori opzionali

Other accessories / Altri accessori



USB to USB-C cable / Cavo da USB a USB-C

Included

Matt Black Length 1 m
 1Z0000132




Table / Tavolino

Not included

Matt White 1A4020300.00.00
 Matt Black 1A4020400.00.00



Vis à Vis is a magic trick, between technique and illusion.
Once again, we decided to take away, seeking only the light.
Transparency is the main feature of this battery-powered lamp.

Archiproducts Design Award 2023

Vis à Vis è un gioco di prestigio, tra la tecnica e l'illusione.
Abbiamo pensato, ancora una volta, di togliere, cercando solo la luce.
La trasparenza è la caratteristica principale di questa lampada a batteria.

Archiproducts Design Award 2023


VIS À VIS

Michele Groppi / 2023

Table / Direct / Wireless

Material Metal - Methacrylate
Finish .00 Standard

Note Chargeable table luminaire. Transparent disc with refractive effect. *Apparecchio illuminante da tavolo a batteria ricaricabile. Disco trasparente con effetto rifrattivo. Stelo trasparente e modulo LED con fissaggio magnetico. Autonomia della batteria: 9 ore.*
 Magnetic fixing LED module and transparent stem. Battery life: 9 hours.



VIS À VIS


2W
 2700K - 110lm / 3000K - 113lm
 CRI >90
 ON/OFF
 Driver with plug not included
 USB cable included
 CE IP20

Standard - 2700K - ON/OFF
 Standard - 3000K - ON/OFF

1A4530000.27.00
 1A4530000.30.00

Optional accessories / Accessori opzionali

Drivers / Alimentatori



Driver with plug / Alimentatore con spina		Not included
Matt Black	Input 110-240V - 50/60Hz Output 5V DC - 2A - 10W - IP20	1Z0000088

LED modules / Moduli LED



LED module / Modulo LED		Included
Standard	5W - 2700K - 110lm - CRI >90 Rechargeable lithium battery 5V DC Li-Ion 4800mAh - Battery life 9 hours	1A5370000.27.00
	2W - 3000K - 113lm - CRI >90 Rechargeable lithium battery 5V DC Li-Ion 4800mAh - Battery life 9 hours	1A5370000.30.00

Other accessories / Altri accessori



USB to USB-C cable / Cavo da USB a USB-C		Included
Matt Black	Length 1 m	1Z0000132



TABLE / TAVOLO

ABA 45

Omar Carraglia / 2007



Inspired by the shape of a traditional lampshade.
The bulb is not shielded but displayed, and it peeks out from the shade.
Floor version available.

Ispirata alla forma di un'abat-jour tradizionale.
La lampadina non è schermata, ma esibita, e fa capolino dal paralume.
Disponibile anche nella versione da terra.

ABA 45


Omar Carraglia / 2007

Table / Diffuse / Indoor

Material Metal - Methacrylate
Finish .03 Matt White

Note Table luminaire. Dimmer on the cable. White cable.

Apparecchio illuminante da tavolo. Dimmer lungo il cavo. Cavo bianco.



ABA 45

Max 10W - E27
100-240V - 50/60Hz
Dimmer on board
Bulb not included


CE IP20 0,5 m

Matt White - Dimmer on board

| 1A2700300.00.06 |

Optional accessories / Accessori opzionali

Bulbs / Lampadine



LED - E27 - G125

220-240V - 7W - 360°
2700K - 806lm - CRI >80
Energy Efficiency E - Dimmable

1Y2080010

Not included





ANIMA

Davide Groppi - Giorgio Rava / 2021

A slender, light, ephemeral and abstract sculpture, it is a weightless ideogram. It's the emotion of an indirect light with an aesthetic poised between Scandinavian and Japanese design, two apparently distant cultures but, actually, very close.

At the top, an open circle, almost a hook for fishermen of the soul.

Selection for ADI Design Index 2022

AZ Award 2022

Archiproducts Design Award 2021

Scultura filiforme, leggera, effimera, astratta, è un ideogramma senza peso. È l'emozione di una luce indiretta con un'estetica in bilico tra la Scandinavia e il Giappone, due culture apparentemente lontane, ma in realtà molto vicine tra loro.

In cima, un cerchio non chiuso, quasi un amo per pescatori d'anime.

Selezione per ADI Design Index 2022


Premio AZ Award 2022

Premio Archiproducts Design Award 2021

Table-Floor / Indirect / Indoor

Material ABS - Carbon fiber - Metal
Finish .04 Matt Black

Note Table luminaire. Touch ON/OFF and adjustment. Black cable. *Apparecchio illuminante da tavolo. ON/OFF e regolazione touch. Cavo nero.*



ANIMA


4W
 5V DC
 2700K - 575lm / 3000K - 589lm
 CRI >80
 Dimmer on board
 Driver with plug not included
 USB cable included
 CE IP20

Matt Black - 2700K - Dimmer on board
 Matt Black - 3000K - Dimmer on board

1A1090400.27.06
 1A1090400.30.06

Optional accessories / Accessori opzionali

Drivers / Alimentatori




Driver with plug / Alimentatore con spina		Not included
Matt Black	Input 110-240V - 50/60Hz Output 5V DC - 2A - 10W - IP20	1Z0000088

Other accessories / Altri accessori



USB to USB-C cable / Cavo da USB a USB-C		Included
Matt Black	Length 1 m	1Z0000132



Power bank		Not included
	10000mAh/36Wh Output 5V DC Battery life 10 hours	1A1990000.00.00





CALVINO

Davide Groppi / 2018

Full and empty, shadow and light.
A circular mirror to be positioned as you please,
to both light and capture the surrounding space.
Born Series Award 2019

Pieni e vuoti, ombra e luce.
Uno specchio circolare può essere orientato a piacimento
per illuminare e nello stesso tempo cogliere lo spazio circostante.
Premio Born Series Award 2019


CALVINO

Davide Groppi / 2018

Table / Indirect / Indoor

Material Brass - Metal - Methacrylate - Mirror
Finish .00 Standard

Note Table luminaire. Disc with mirror finish adjustable in all directions. *Apparecchio illuminante da tavolo. Disco con finitura a specchio orientabile in tutte le direzioni. Retro del disco blu opaco. Base nero opaco. Stelo in ottone. Dimmer lungo il cavo. Cavo nero.*
 Matt blue rear disc. Matt black base. Brass stem. Dimmer on the cable. Black cable.



CALVINO

18W
 24V DC
 2700K - 1275lm / 3000K - 1372lm
 CRI >90
 Dimmer on board
 Driver with plug included


CE IP20

Standard - 2700K - Dimmer on board
 Standard - 3000K - Dimmer on board

1A2710000.27.06
 1A2710000.30.06

Optional accessories / Accessori opzionali

Drivers / Alimentatori




Driver with plug / Alimentatore con spina

Included

Matt Black	Input 110-240V - 50/60Hz Output 24V DC - 18W - IP20	1Z0431020
------------	--	-----------





An antenna of light.

Antennas are mysterious, absolute and intrinsically beautiful,
because their essentialness expresses nothing more than their function.

A performing, adjustable and extremely comfortable light.

Selection for ADI Design Index 2023
Archiproducts Design Award 2022

Un'antenna di luce.

Le antenne sono misteriose, assolute e intrinsecamente belle perché esprimono,
con la loro essenzialità, null'altro che la loro funzione.


Una luce prestante, orientabile ed estremamente confortevole.

Selection for ADI Design Index 2023
Archiproducts Design Award 2022

Table / Direct / Indoor

Material Carbon fiber - Metal
Finish .04 Matt Black

Note Table luminaire. Adjustable along the vertical axis. ON/OFF and push control. Black cable. *Apparecchio illuminante da tavolo. Orientabile lungo l'asse verticale. ON/OFF e regolazione push. Cavo nero.*



FM

1,5W
 5V DC
 2700K - 154lm / 3000K - 179lm
 CRI >90
 UGR <19
 Dimmer on board
 Driver with plug not included
 USB cable included




Matt Black - 2700K - Dimmer on board
 Matt Black - 3000K - Dimmer on board

1A2440400.27.06
 1A2440400.30.06

Optional accessories / Accessori opzionali

Drivers / Alimentatori




Driver with plug / Alimentatore con spina		Not included
Matt Black	Input 110-240V - 50/60Hz Output 5V DC - 2A - 10W - IP20	1Z0000088

Other accessories / Altri accessori



USB to USB-C cable / Cavo da USB a USB-C		Included
Matt Black	Length 1 m	1Z0000132



Power bank		Not included
	10000mAh/36Wh Output 5V DC Battery life 10 hours	1A1990000.00.00



MOON T

Daide Groppi / 2019



Moon was created from the dream of bringing the moon inside your own home.
The hand-made Japanese paper surface makes every lamp unique.
Suspension and floor versions also available.

Moon nasce da un sogno, quello di portare la luna dentro casa.
La superficie di carta giapponese, fatta a mano, rende unico ogni pezzo.
Disponibile anche nelle versioni a sospensione e da terra.


MOON T

Davide Groppi / 2019

Table / Diffuse / Indoor

Material Japanese paper - Metal - PE
Finish .00 Standard

Note Table luminaire. PE and Japanese paper shade. Gold finish base. Dimmer on the cable. White cable. Compulsory moisture barrier bag packaging for air and sea shipping. *Apparecchio illuminante da tavolo. Paralume in PE e carta giapponese. Base verniciata dorata. Dimmer lungo il cavo. Cavo bianco. Sacco barriera obbligatorio per spedizioni aerea e via nave.*



MOON T

Max 15W - E27
100-240V - 50/60Hz
Dimmer on board
Bulb not included
CE IP20

Standard - Dimmer on board

| 1A2690000.00.06 |

Optional accessories / Accessori opzionali

Bulbs / Lampadine



LED - E27 - A60 /	Not included
220-240V - 11,2W - 360° 2700K - 1521lm - CRI >90 Energy Efficiency D - Dimmable	1Y0330790

Other accessories / Altri accessori

Moisture barrier bag / Sacco barriera	Not included
Packaging for air and sea shipping	4A2690010







A lamp that can be positioned, balanced and turned,
but overall it produces a beautiful light on the table.
The oversized workshop-style clamp allows the light source to be positioned far from
where the lamp is attached to the table, using three adjustable arms.
A table lamp, but at the same time a suspended light.
Wall version also available.

Una lampada che si inclina, si bilancia, si gira,
ma soprattutto che produce una bellissima luce sul tavolo.
L'utilizzo di un grande e sproporzionato morsetto da officina, ci ha permesso
di portare la fonte luminosa lontana dal punto di fissaggio attraverso tre bracci regolabili.
Una lampada da tavolo, ma nello stesso tempo a sospensione.
Disponibile anche nella versione da parete.


MORSETTO

Davide Groppi / 2017

Table / Direct / Indoor

Material Metal
Finish .04 Matt Black

Note Table luminaire. Adjustable in all directions. Shiny red clamp. *Apparecchio illuminante da tavolo. Orientabile in tutte le direzioni. Morsetto rosso lucido. Dimmer lungo il cavo. Cavo nero.*
 Dimmer on the cable. Black cable.



MORSETTO

13W
 24V DC
 2700K - 765lm / 3000K - 823lm
 CRI >90
 UGR <19
 Dimmer on board
 Driver with plug included




Matt Black - 2700K - Dimmer on board
 Matt Black - 3000K - Dimmer on board

1A2520400.27.06
 1A2520400.30.06

Optional accessories / Accessori opzionali

Drivers / Alimentatori



Driver with plug / Alimentatore con spina

Material	Input	Output	Code	Included
Matt Black	110-240V - 50/60Hz	24V DC - 18W - IP20	1Z0431020	







Reminiscent of waking up, that magical instant just before you open your eyes completely, when the light barely filters, making everything indistinct as you pass from sleeping to being awake.

A metal cone positioned diagonally on its base creates an asymmetrical light.

Ricorda il risveglio, quel breve magico attimo, prima di aprire totalmente gli occhi, in cui la luce filtra appena, rendendo tutto indistinto nel passaggio fra il sonno e la veglia. Un cono in metallo, posizionato in obliquo sulla base, genera una luce asimmetrica.

PALPEBRA


Federico Delrosso / 2009

Table / Diffuse / Indoor

Material Metal
Finish .03 Matt White

Note Table luminaire. Dimmer on the cable. White cable.

Apparecchio illuminante da tavolo. Dimmer lungo il cavo. Cavo bianco.



PALPEBRA

Max 5W - E14
100-240V - 50/60Hz
Dimmer on board
Bulb not included
CE IP20

Matt White - Dimmer on board

| 1A2680300.00.06 |

Optional accessories / Accessori opzionali

Bulbs / Lampadine



LED - E14 - P40

220-240V - 4,5W
2700K - 470lm - CRI >80
Energy Efficiency F - Dimmable

1Y0041410

Not included






A rigorous project in its design.
A dialogue between two essential, concrete and tangible materials: wood and glass.
Part frosted and part transparent, it moves feely on the base,
functioning both as diffuser and convex lens.

Un progetto dalle linee rigorose.
Un dialogo tra due materiali primari, concreti e tangibili: il legno e il vetro.
Satinata e in parte trasparente, si muove liberamente sulla base,
diventando a volte diffusore, a volte lente convessa.

Table / Diffuse / Indoor

Material Glass - Oak wood
Finish .00 Standard

Note Table luminaire. Sanded glass ball. Oak wood base. Dimmer on the cable. *Apparecchio illuminante da tavolo. Sfera in vetro sabbiato. Base in legno di rovere. Dimmer lungo il cavo. Cavo nero.*



PIGRECO


6,5W
 24V DC
 3000K - 450lm
 CRI >90
 Dimmer on board
 Driver with plug included
 CE IP20

Standard - 3000K - Dimmer on board

| 1A2600000.30.06 |

Optional accessories / Accessori opzionali


Drivers / Alimentatori



Driver with plug / Alimentatore con spina

Included

Matt Black	Input 110-240V - 50/60Hz Output 24V DC - 18W - IP20	1Z0431020
------------	--	-----------



FLOOR / TERRA



ABA 120

Omar Carraglia / 2007

Inspired by the shape of a traditional lampshade.
The bulb is not shielded but displayed, and it peeks out from the shade.
Table version available.

Ispirata alla forma di un'abat-jour tradizionale.
La lampadina non è schermata, ma esibita, e fa capolino dal paralume.
Disponibile anche nella versione da tavolo.

ABA 120


Omar Carraglia / 2007

Floor / Diffuse / Indoor

Material Metal - Methacrylate
Finish .03 Matt White

Note Floor luminaire. Dimmer on the cable. White cable.

Apparecchio illuminante da terra. Dimmer lungo il cavo. Cavo bianco.



ABA 120

Max 10W - E27
100-240V - 50/60Hz
Dimmer on board
Bulb not included
CE IP20 0.5 m

Matt White - Dimmer on board

1A2770300.00.06

Optional accessories / Accessori opzionali

Bulbs / Lampadine



LED - E27 - G125

Not included

220-240V - 7W - 360°
2700K - 806lm - CRI >80
Energy Efficiency E - Dimmable

1Y2080010



BANNER

Mauro Ferrari / 2004



A solution that is part fixed and part mobile.
The lamp is fixed to the wall, but is powered by a cable and normal electrical plug.
Banner is one of our many solutions for bringing light
where you need it, with the greatest freedom.

Una soluzione fissa ma anche mobile.
La lampada è fissata a parete, ma viene alimentata attraverso una cavo e una normale
spina elettrica. Banner è una delle nostre tante soluzioni
per portare la luce dove si desidera con la massima libertà.

BANNER

Mauro Ferrari / 2004

Floor / Indirect / Indoor

Material Metal - Polycarbonate
Finish .03 Matt White

Note Floor lamp with wall fixing. Connection cable not included.

Apparecchio illuminante da terra con fissaggio a parete. Cavo di connessione non incluso.



BANNER

90W

110-240V - 50/60Hz

2700K - 11083lm / 3000K - 11918lm

CRI >80

Driver integrated

DALI


CE IP20

Matt White - 2700K - DALI

1A1840300.27.01

Matt White - 3000K - DALI

1A1840300.30.01



BANNER

90W

110-240V - 50/60Hz

2700K - 11083lm / 3000K - 11918lm

CRI >80

Driver integrated

Dimmer on board

CE IP20

Matt White - 2700K - Dimmer on board

1A1840300.27.06

Matt White - 3000K - Dimmer on board

1A1840300.30.06



HASHI

Federico Delrosso / 2017



A floor lamp conceived to provide direct light in a simple and flexible manner.
Its principle component is the pivot point between two "chopsticks" (Hashi)
that serve as light sources which, positioned in different ways,
create a strong, graphic effect in space.
Particular care has been given to the proportions.
The sticks always appear lightweight and balanced.

Lampada da terra pensata per fare luce d'accento con purezza e flessibilità.
La componente fondamentale di progetto è lo snodo che, grazie alla sua energica tenacia,
permette di posizionare le "bacchette" (Hashi) nello spazio in modo grafico e deciso.
La particolare attenzione per le proporzioni rende il gesto molto libero,
ma sempre equilibrato.

HASHI


Federico Delrosso / 2017

Floor / Direct / Indoor

Material Metal - Methacrylate

Finish .04 Matt Black .18 Matt Gold

Note Floor luminaire. Adjustable along the vertical axis. Dimmer on the cable. *Apparecchio illuminante da terra. Orientabile lungo l'asse verticale. Dimmer lungo il cavo. Cavo nero.*



HASHI

15,5W

110-240V - 50/60Hz

2700K - 765lm / 3000K - 823lm

CRI >90

UGR <19

Driver integrated

Dimmer on board

CE IP20

Matt Black - 2700K - Dimmer on board

Matt Black - 3000K - Dimmer on board

Matt Gold - 2700K - Dimmer on board

Matt Gold - 3000K - Dimmer on board

1A2510400.27.06

1A2510400.30.06

1A2511800.27.06

1A2511800.30.06






A tribute to Alberto Giacometti and to his thin fellows...
A lamp for lighting pictures, powered by an ordinary electrical socket.
The lamp has an adjustable light and it can be oriented.
The lamp section is reduced to a minimum.

Un omaggio ad Alberto Giacometti e alle sue figure sottili...
Una lampada per illuminare i quadri prendendo corrente da una normale presa elettrica.
La lampada è regolabile in altezza ed il flusso luminoso orientabile.
La sezione del corpo illuminante è ridotta ai minimi termini.

Floor-Suspension / Indirect / Indoor

Material Brass - Methacrylate
Finish **.03** Matt White **.04** Matt Black **.08** Brushed Brass

Note Floor luminaire with ceiling fixing. Adjustable along the vertical axis. Matt white rose. AISI 304 stainless steel suspension cable. Dimmer on the cable. Transparent cable. MASAI 2: version with power cable only and without driver. *Apparecchio da terra con fissaggio a soffitto. Orientabile lungo l'asse verticale. Rosone bianco opaco. Cavo di sospensione in inox AISI 304. Dimmer lungo il cavo. Cavo trasparente. MASAI 2: versione con solo il cavo di alimentazione e senza driver.*




MASAI 1

Driver with plug version
 15,5W
 110-240V - 50/60Hz
 2700K - 600lm / 3000K - 619lm
 CRI >90
 Driver integrated
 Dimmer on board

CE IP20

Matt White - 2700K - Dimmer on board
 Matt White - 3000K - Dimmer on board
 Matt Black - 2700K - Dimmer on board
 Matt Black - 3000K - Dimmer on board
 Brushed Brass - 2700K - Dimmer on board
 Brushed Brass - 3000K - Dimmer on board

1A2720300.27.06
 1A2720300.30.06
 1A2720400.27.06
 1A2720400.30.06
 1A2720800.27.06
 1A2720800.30.06



MASAI 2

Remote driver version
 13W
 24V DC - 50/60Hz
 2700K - 600lm / 3000K - 619lm
 CRI >90
 Driver not included


CE IP20

Matt White - 2700K
 Matt White - 3000K
 Matt Black - 2700K
 Matt Black - 3000K
 Brushed Brass - 2700K
 Brushed Brass - 3000K


1A2720300.27.20
 1A2720300.30.20
 1A2720400.27.20
 1A2720400.30.20
 1A2720800.27.20
 1A2720800.30.20

Compulsory accessories / Accessori obbligatori


Drivers / Alimentatori



Driver / Alimentatore				Not included
220-240V(100-127V)	24V/16W(15W)/IP20/DALI	MASAI 2	1Z0241180.24	



Driver / Alimentatore				Not included
220-240V(100-127V)	24V/20W(15W)/IP20/PUSH	MASAI 2	1Z0240870.24	



Driver / Alimentatore				Not included
220-240V	24V/20W/IP20/TRIAC/IGBT	MASAI 2	1Z0240850.24	

Optional accessories / Accessori opzionali

Suspension kits / Kit di sospensione




Sloped ceiling suspension kit / Kit di sospensione per soffitto inclinato		Not included
	Nickel plated - 1 Piece	1A0510000.00.00



Recessed suspension kit for 12,5 mm plasterboard / Kit di sospensione da incasso per cartongesso 12,5 mm			Not included
Matt White	For suspension cables - 1 Piece Plasterboard cut-out Ø 44 mm Minimum space for mounting 70 mm	1X0000300.03.00	
Matt Black	For suspension cables - 1 Piece Plasterboard cut-out Ø 44 mm Minimum space for mounting 70 mm	1X0000400.03.00	



Ceiling suspension kit / Kit di sospensione da soffitto		Not included
Matt White	For suspension cables - 1 Piece	1X0010300.03.00
Matt Black	For suspension cables - 1 Piece	1X0010400.03.00



Wall adapter plate / Piastra di adattamento da parete		Not included
Matt White	For mounting on brick masonry walls	1X0050300.01.00



304 Stainless steel suspension cable / Cavo di sospensione in acciaio inox AISI 304		Not included
	Lenght 10 m	1A1680000.00.00



MISTER

Omar Carraglia / 2013



Portable light.

A floor tool to grant a wonderful indirect light in the purest possible way.

Luce mobile.

Un elemento da terra per garantire nel modo più puro possibile una meravigliosa luce indiretta.

MISTER


Omar Carraglia / 2013

Floor / Indirect / Indoor

Material Metal - Methacrylate

Finish .03 Matt White .04 Matt Black

Note Floor luminaire. Dimmer on the cable. White cable for the matt white finish, black cable for the matt black finish. *Apparecchio illuminante da terra. Dimmer lungo il cavo. Cavo bianco per la finitura bianco opaco e cavo nero per la finitura nero opaco.*



MISTER

33W

110-240V - 50/60Hz

2700K - 2771lm / 3000K - 2884lm

CRI >90

Driver integrated

Dimmer on board

CE IP20

Matt White - 2700K - Dimmer on board

1A2750300.27.06

Matt White - 3000K - Dimmer on board

1A2750300.30.06

Matt Black - 2700K - Dimmer on board

1A2750400.27.06

Matt Black - 3000K - Dimmer on board

1A2750400.30.06





MOON F

Daide Groppi / 2023

Moon was created from the dream of bringing the moon inside your own home.
The hand-made Japanese paper surface makes every lamp unique.
Suspension and floor versions also available.

Moon nasce da un sogno, quello di portare la luna dentro casa.
La superficie di carta giapponese, fatta a mano, rende unico ogni pezzo.
Disponibile anche nelle versioni a sospensione e da tavolo.

MOON F

Davide Groppi / 2023


Floor / Diffuse / Indoor

Material Japanese paper - PE

Finish .00 Standard

Note Floor luminaire. PE and Japanese paper shade. Matt white base. Dimmer on the cable. White cable. For air and sea shipping: moisture barrier bag compulsory for all models and wooden crate compulsory for MOON 120 F model.

Apparecchio illuminante da terra. Paralume in PE e carta giapponese. Base bianco opaco. Dimmer lungo il cavo. Cavo bianco.
Per spedizioni aerea e via nave: sacco barriera obbligatorio per tutti i modelli e cassa in legno obbligatoria per il modello MOON 120 F.




MOON 80 F

Max 15W - E27
 100-240V - 50/60Hz
 Dimmer on board
 Bulb not included

CE IP20

Standard - Dimmer on board

|1A4880000.00.06 |



MOON 120 F

Max 2x25W - E27
 100-240V - 50/60Hz
 Dimmer on board
 Bulb not included

CE IP20

Standard - Dimmer on board

|1A4890000.00.06 |

MOON F

Davide Groppi / 2023

Optional accessories / Accessori opzionali

Bulbs / Lampadine



LED - E27 - A60

220-240V - 11,2W - 360°
 2700K - 1521lm - CRI >90
 Energy Efficiency D - Dimmable

MOON 80 F

1Y0330790

Not included



LED - E27 - A150

220-240V - 20W - 200°
 2700K - 2452lm - CRI >80
 Energy Efficiency E - Dimmable

MOON 120 F

1Y2160020

Not included

Other accessories / Altri accessori

Moisture barrier bag / Sacco barriera

Packaging for air and sea shipping

MOON 80 F

4A2840010

Not included

Moisture barrier bag / Sacco barriera

Packaging for air and sea shipping

MOON 120 F

49860020

Not included

Wooden crate / Cassa in legno

Packaging for air and sea shipping


MOON 120 F

49860010

Not included

MOVIE

Omar Carraglia / 2005



To "play" with the light.
A RGBW system lets you create all the light of the world.
To feel the light and to live it in all its spectrum.

Per giocare con i colori della luce.
Un sistema RGBW permette di creare tutta la luce del mondo.
Per sentire la luce e viverla in tutto il suo spettro.

MOVIE

Omar Carraglia / 2005


Floor / Indirect / Indoor

Material Metal - Polycarbonate

Finish .03 Matt White .13 Black Brushed Stainless Steel

Note Floor luminaire. RGBW wireless control. Black cable.

Apparecchio illuminante da terra. RGBW wireless control. Cavo nero.



MOVIE

80W

100-240V - 50/60Hz

2832lm

CRI >90

Driver integrated

Dimmer on board

RGBW wireless control

CE IP20

Matt White - RGBW - Dimmer on board

1A2740300.98.06

Black Brushed Stainless Steel - RGBW - Dimmer on board

1A2741300.98.06



ORIGINE

Davide Groppi - Giorgio Rava / 2020



From the Latin "origo", start, birth, source.
It appears like a bud emerging from the ground and soaring upwards towards the sky,
a stem that becomes increasingly thinner.

Mysterious and enigmatic, it combines the fascination of the unknown
with the pleasure of a sophisticated and elegant ambient light.

Origine sculpts and enhances every environment with its indirect light,
which is intentionally non-invasive, graphic and fascinating.

Available in 3 different heights and in an outdoor version.

**AZ Award 2021 and People's Choice
Archiproducts Design Award 2020**

Dal latino "origo", inizio, nascita, fonte.

Evoca un germoglio che emerge dalla terra e si slancia verso il cielo,
lo stelo che diventa sempre più sottile.

Misteriosa ed enigmatica, unisce il fascino dell'incognito
al piacere di una luce d'ambiente sofisticata ed elegante.

Origine scolpisce e valorizza ogni ambiente con la sua luce indiretta,
volutamente non invasiva, grafica e affascinante.

Disponibile in 3 altezze differenti e nella versione outdoor.


**Premio AZ Award 2021 e People's Choice
Premio Archiproducts Design Award 2020**

Floor / Indirect / Indoor

Material Glass fiber - Metal
Finish .04 Matt Black

Note Floor luminaire. Dimmer on the cable. Black cable.


Apparecchio illuminante da terra. Dimmer lungo il cavo. Cavo nero.



ORIGINE 490
 35W
 24V DC
 2700K - 3760lm / 3000K - 4051lm
 CRI >80
 Driver included
 Dimmer on board
 CE IP20

Matt Black - 2700K - Dimmer on board
 Matt Black - 3000K - Dimmer on board


1A2320400.27.06
 1A2320400.30.06



ORIGINE 290
 25W
 24V DC
 2700K - 1926lm / 3000K - 2075lm
 CRI >80
 Driver included
 Dimmer on board
 CE IP20

Matt Black - 2700K - Dimmer on board
 Matt Black - 3000K - Dimmer on board

1A2300400.27.06
 1A2300400.30.06



ORIGINE 390
 30W
 24V DC
 2700K - 2843lm / 3000K - 3063lm
 CRI >80
 Driver included
 Dimmer on board
 CE IP20

Matt Black - 2700K - Dimmer on board
 Matt Black - 3000K - Dimmer on board

1A2310400.27.06
 1A2310400.30.06





The light is elevated to a work of art and contemplation.
A luminous panel without a frame leans against the wall as if waiting to be hung.
The colour and brightness can be controlled from the remote control.

La luce è elevata a oggetto d'arte e di contemplazione.
Un pannello luminoso senza cornice è appoggiato alla parete
come se aspettasse di essere appeso.
È possibile scegliere il colore e l'intensità della luce agendo sul telecomando.


PABLO

Davide Groppi / 2015

Floor / Diffuse / Indoor

Material Metal - Methacrylate
Finish .00 Standard

Note Floor luminaire. Matt white diffuser. RGB wireless control. *Apparecchio illuminante da terra. Diffusore bianco opaco. RGB wireless control. Cavo trasparente.*




PABLO

66W
220-240V - 50/60Hz
Driver integrated
Dimmer on board
RGB wireless control
CE IP20

Standard - RGB - Dimmer on board

| 1A2730000.99.06 |





A piece of architecture to be used in space.
A concrete cube that allows you to understand volumes
and architecture in an unusual and unprecedented way.
Outdoor version also available.

Un pezzo di architettura da utilizzare nello spazio.
Un cubo realizzato in cemento che permette di interpretare i volumi
e le architetture in modo inconsueto e inedito.
Disponibile anche nella versione outdoor.

Q


Alberto Zattin / 2000

Floor / Direct / Indoor

Material Cement - Metal
Finish .00 Standard

Note Floor luminaire. Concrete body. Orange cable.

Apparecchio illuminante da terra. Corpo in cemento. Cavo arancione.



Q

Max 10W - GU10
100-240V - 50/60Hz
ON/OFF
Bulb not included
CE IP20

Standard - ON/OFF

| 1A2760000.00.00 |

Optional accessories / Accessori opzionali

Bulbs / Lampadine



LED - GU10 - PAR16

Not included

220-240V - 4,9W - 120°
3000K - 550lm - CRI >80
Energy Efficiency E

1Y0330740





A special project, an authentic ready-made.
Obtained from a flexible fishing rod, it is a delicate and elegant sign,
which brings to mind the subtle branches of a willow tree
or bamboo canes floating on a light breeze.
Sampei is an unexpected gift, it is the magic of looking up, using light as a hook,
and being amazed by so much weightlessness.

The light is the fisherman's line, catching faces, gazes, people.
Available in 4 different heights and also in an outdoor version.

XXIII Compasso d'Oro ADI Award 2014

Elle Deco International Design Award 2011

Un progetto speciale, un autentico ready-made.
Ricavata da una canna da pesca flessibile, è un segno delicato ed elegante,
che fa pensare a effimeri rami di salice, a canne di bambù mosse da un debole vento.
Sampei è un regalo inaspettato, è la magia di guardare in alto,
usando la luce come amo, e stupirsi di tanta leggerezza.
La luce è la lenza del pescatore, pronta per catturare volti, sguardi, persone.
Disponibile in 4 altezze differenti e anche nella versione outdoor.


XXIII Premio Compasso d'Oro ADI 2014

Premio Elle Deco International Design Award 2011

Floor / Direct / Indoor

Material Glass fiber - Metal
Finish **.03** Matt White **.04** Matt Black


Note Floor luminaire. Adjustable in all directions. Dimmer on the cable. White cable for the matt white finish, black cable for the matt black finish. *Apparecchio illuminante da terra. Orientabile in tutte le direzioni. Dimmer lungo il cavo. Cavo bianco per la finitura bianco opaco e cavo nero per la finitura nero opaco.*



SAMPEI 230
 Max 21W
 220-240V - 50/60Hz
 2700K - 1808lm / 3000K - 1890lm
 CRI >90
 Driver integrated
 Dimmer on board
CE IP20

Matt White - 2700K - Dimmer on board
 Matt White - 3000K - Dimmer on board
 Matt Black - 2700K - Dimmer on board
 Matt Black - 3000K - Dimmer on board


1A3730300.27.06
 1A3730300.30.06
 1A3730400.27.06
 1A3730400.30.06



SAMPEI 260
 Max 21W
 220-240V - 50/60Hz
 2700K - 1808lm / 3000K - 1890lm
 CRI >90
 Driver integrated
 Dimmer on board
CE IP20

Matt White - 2700K - Dimmer on board
 Matt White - 3000K - Dimmer on board
 Matt Black - 2700K - Dimmer on board
 Matt Black - 3000K - Dimmer on board


1A3740300.27.06
 1A3740300.30.06
 1A3740400.27.06
 1A3740400.30.06



SAMPEI 290
 Max 21W
 220-240V - 50/60Hz
 2700K - 1808lm / 3000K - 1890lm
 CRI >90
 Driver integrated
 Dimmer on board
CE IP20

Matt White - 2700K - Dimmer on board
 Matt White - 3000K - Dimmer on board
 Matt Black - 2700K - Dimmer on board
 Matt Black - 3000K - Dimmer on board

1A3750300.27.06
 1A3750300.30.06
 1A3750400.27.06
 1A3750400.30.06



SAMPEI 440
 Max 21W
 220-240V - 50/60Hz
 2700K - 1832lm / 3000K - 1915lm
 CRI >90
 Driver integrated
 Dimmer on board
CE IP20

Matt White - 2700K - Dimmer on board
 Matt White - 3000K - Dimmer on board
 Matt Black - 2700K - Dimmer on board
 Matt Black - 3000K - Dimmer on board


1A3760300.27.06
 1A3760300.30.06
 1A3760400.27.06
 1A3760400.30.06

Optional accessories / Accessori opzionali


Other accessories / Altri accessori




Accessory holder + Soft filter + Honeycomb louvre / Porta accessori + Filtro soft + Frangiluce nido d'ape
Matt Black 1X0070400.04.00 Not included




Accessory holder + Elliptical filter / Porta accessori + Filtro ellittico
Matt Black 1X0070400.05.00 Not included



Blue filter / Filtro blu
Standard Compulsory with 1X0070000.06.00 Not included
1X0070400.04.00 / 1X0070400.05.00



Red filter / Filtro rosso
Standard Compulsory with 1X0070000.07.00 Not included
1X0070400.04.00 / 1X0070400.05.00



Yellow filter / Filtro giallo
Standard Compulsory with 1X0070000.08.00 Not included
1X0070400.04.00 / 1X0070400.05.00



SHOJI

Davide Groppi - Paola Lenti / 2013



A nylon lampshade, strictly hand-stitched and hand-made.
Outdoor version also available.

Un paralume in nylon rigorosamente cucito e confezionato a mano.
Disponibile anche nella versione outdoor.

SHOJI


Davide Groppi - Paola Lenti / 2013

Floor / Diffuse / Indoor

Material Metal - PBT - Polycarbonate

Finish .00 Standard

Note Floor luminaire. Hand-stitched shade. Matt black stems. Dimmer on the cable. Black cable. *Apparecchio illuminante da terra. Paralume cucito a mano. Steli nero opaco. Dimmer lungo il cavo. Cavo nero.*



SHOJI

Max 18W - E27

100-240V - 50/60Hz

Dimmer on board

Bulb not included

CE IP20

Standard - Dimmer on board

| 1A2780000.00.06 |

Optional accessories / Accessori opzionali

Bulbs / Lampadine



LED - E27 - A60

220-240V - 11,2W - 360°

2700K - 1521lm - CRI >90

Energy Efficiency D - Dimmable

1Y0330790

Not included



SUSPENSION / SOSPENSIONE

CARTESIO

Davide Groppi / 2018



A thin, circular mirror is suspended to provide light,
combining both direct and indirect lighting.
A sophisticated clamping system is used to position the disc wherever you want,
without the need for wall or ceiling wires.

Uno specchio circolare sospeso e sottile per illuminare,
coniugando la luce diretta e quella indiretta.
Il sofisticato sistema di fissaggio permette di posizionare il disco dove si desidera
senza il vincolo della posizione dei cavi di alimentazione a soffitto o a parete.

CARTESIO


Davide Groppi / 2018

Suspension / Direct-Indirect / Indoor

Material Metal - Methacrylate

Finish .00 Standard

Note Suspension luminaire. Disc with mirror finish. Matt red rear disc. Matt white rose. AISI 304 stainless steel suspension cables. Dual emission. White cable. *Apparecchio illuminante a sospensione. Disco con finitura a specchio. Retro del disco rosso opaco. Rosone bianco opaco. Cavi di sospensione in inox AISI 304. Doppia emissione. Cavo bianco.*



CARTESIO 60

18W

110-240V - 50/60Hz

3000K - Down 350lm - Up 1050lm

Down CRI >80 - Up CRI >90


Driver integrated

PUSH

CE IP20

Standard - 3000K - PUSH

| 1A3190000.30.04 |



CARTESIO 90

18W

110-240V - 50/60Hz

3000K - Down 350lm - Up 1050lm

Down CRI >80 - Up CRI >90

Driver integrated

PUSH

CE IP20

Standard - 3000K - PUSH

| 1A0070000.30.04 |





CATHODE

Omar Carraglia / 2015

A scientific looking bulb made from mouth blown glass.
The shape brings to mind a light bulb that was never born.
Think steampunk: situations in which instruments were inspired by
the rudiments of electricity. The classic light bulb that has no future
becomes a wonderful device made of luminous diodes.
What would the past have looked like if the future had arrived first?
Luminaire available also in ENDLESS version.


Un'ampolla di vetro soffiato a bocca dall'aspetto scientifico.
La forma evoca quella di una lampadina mai nata, atmosfere steampunk,
situazioni in cui le strumentazioni erano attivate dalle prime forme di elettricità.
La classica lampadina senza più futuro diventa un apparecchio a diodi luminosi.
Come sarebbe stato il passato se il futuro fosse arrivato prima?
Apparecchio illuminante disponibile anche nella versione ENDLESS.

Suspension / Diffuse / Indoor

Material Blown glass - Metal
Finish .03 Matt White .08 Brushed Brass

Note Suspension luminaire. Blown glass diffuser. Matt white rose and white cable for the matt white finish. Matt black rose and black cable for the brushed brass finish. Single rose for more than one lamp on request. CATHODE 2: plasterboard version with magnetic fixing flat rose. CATHODE ENDLESS: luminaire dedicated to ENDLESS system (Max 48V DC - Max 150W - Max 4A). It can be used, on the same circuit, with the ENDLESS models. See page: ENDLESS.

Apparecchio illuminante a sospensione. Diffusore in vetro soffiato. Rosone bianco opaco e cavo bianco per la finitura bianco opaco. Rosone nero opaco e cavo nero per la finitura ottone spazzolato. Rosone unico per più apparecchi su richiesta. CATHODE 2: versione per cartongesso con rosone piano a fissaggio magnetico. CATHODE ENDLESS: apparecchio illuminante dedicato al sistema ENDLESS (Max 48V DC - Max 150W - Max 4A) ed utilizzabile, sullo stesso circuito, con i modelli ENDLESS. Vedi pagina ENDLESS.



CATHODE 1
 Ceiling driver version
 5,6W
 100-240V - 50/60Hz
 2700K - 264lm / 3000K - 284lm
 CRI >90
 Driver integrated
 ON/OFF
CE IP20

Matt White - 2700K - ON/OFF	1A2980300.27.00
Matt White - 3000K - ON/OFF	1A2980300.30.00
Brushed Brass - 2700K - ON/OFF	1A2980800.27.00
Brushed Brass - 3000K - ON/OFF	1A2980800.30.00



CATHODE 1
 Ceiling driver version
 6W
 110-240V - 50/60Hz
 2700K - 264lm / 3000K - 284lm
 CRI >90
 Driver integrated
 DALI
CE IP20

Matt White - 2700K - DALI	1A2980300.27.01
Matt White - 3000K - DALI	1A2980300.30.01
Brushed Brass - 2700K - DALI	1A2980800.27.01
Brushed Brass - 3000K - DALI	1A2980800.30.01



CATHODE 1
 Ceiling driver version
 6W
 110-240V - 50/60Hz
 2700K - 264lm / 3000K - 284lm
 CRI >90
 Driver integrated
 PUSH
CE IP20

Brushed Brass - 2700K - PUSH	1A2980800.27.04
Brushed Brass - 3000K - PUSH	1A2980800.30.04
Matt White - 2700K - PUSH	1A2980300.27.04
Matt White - 3000K - PUSH	1A2980300.30.04




CATHODE 1
 Ceiling driver version
 6W
 110-240V - 50/60Hz
 2700K - 264lm / 3000K - 284lm
 CRI >90
 Driver integrated
 1-10V
CE IP20

Matt White - 2700K - 1-10V	1A2980300.27.03
Matt White - 3000K - 1-10V	1A2980300.30.03
Brushed Brass - 2700K - 1-10V	1A2980800.27.03
Brushed Brass - 3000K - 1-10V	1A2980800.30.03



CATHODE 1
 Ceiling driver version
 6W
 110-240V - 50/60Hz
 2700K - 264lm / 3000K - 284lm
 CRI >90
 Driver integrated
 TRIAC/IGBT
CE IP20

Brushed Brass - 3000K - TRIAC/IGBT	1A2980800.30.02
Matt White - 2700K - TRIAC/IGBT	1A2980300.27.02
Matt White - 3000K - TRIAC/IGBT	1A2980300.30.02
Brushed Brass - 2700K - TRIAC/IGBT	1A2980800.27.02




CATHODE 2

Remote driver version
 4W
 Max 350mA DC
 2700K - 264lm / 3000K - 284lm
 CRI >90
 Driver not included
 CE IP20

Matt White - 2700K
 Matt White - 3000K
 Brushed Brass - 2700K
 Brushed Brass - 3000K

1A2990300.27.20
 1A2990300.30.20
 1A2990800.27.20
 1A2990800.30.20



CATHODE ENDLESS


ENDLESS version only
 5,5W - 0,14A
 48V DC
 2700K - 264lm / 3000K - 284lm
 CRI >90
 Driver not included
 See page ENDLESS
 CE IP20 TE

Matt White - 2700K
 Matt White - 3000K
 Brushed Brass - 2700K
 Brushed Brass - 3000K


1A2980300.27.40
 1A2980300.30.40
 1A2980800.27.40
 1A2980800.30.40

Compulsory accessories / Accessori obbligatori


Drivers / Alimentatori



Driver / Alimentatore				Not included
220-240V(100-127V)	350mA/17W(15W)/IP20/DALI	CATHODE 2	1Z0241180.350	




Driver / Alimentatore				Not included
220-240V(100-127V)	350mA/18W(15W)/IP20/PUSH - 1-10V	CATHODE 2	1Z0240870.350	




Driver / Alimentatore				Not included
220-240V	350mA/17W/IP20/TRIAC/IGBT	CATHODE 2	1Z0240850.350	

Optional accessories / Accessori opzionali

Suspension kits / Kit di sospensione



Decentralization kit / Kit decentratore			Not included
	CATHODE 1	1A0360000.00.00	



Kit ceiling rose and decentralizer / Kit rosone e decentratore				Not included
Matt White	White cable 3 m included	CATHODE 1	1A0770300.00.00	
Matt Black	Black cable 3 m included	CATHODE 1	1A0770400.00.00	



FOSBURY

Davide Groppi / 2014



A lamp that interprets the classic theme of decentralization.
An acrobatic and apparently precarious presence, bringing light where you prefer it,
starting from a simple wall socket.

AZ Award 2016

Una lampada che interpreta il classico tema del decentramento.
Una presenza funambolica e apparentemente instabile per portare la luce
dove si desidera partendo da una semplice presa elettrica.

Premio AZ Award 2016


FOSBURY

Davide Groppi / 2014

Suspension / Direct-Indirect / Indoor

Material Metal
Finish .04 Matt Black

Note Suspension luminaire with floor support. Matt white rose. AISI 304 stainless steel suspension cable. Dual emission. Indirect blue light. Transparent cable. *Apparecchio illuminante a sospensione con appoggio a terra. Rosone bianco opaco. Cavo di sospensione in inox AISI 304. Doppia emissione. Luce indiretta blu. Cavo trasparente.*



FOSBURY

23W
220-240V - 50/60Hz
2700K - Down 765lm - Up 59lm /
3000K - Down 823lm - Up 59lm

CRI >90

UGR <19

Driver integrated

ON/OFF

CE IP20

Matt Black - 2700K - ON/OFF

1A2590400.27.00

Matt Black - 3000K - ON/OFF

1A2590400.30.00

Optional accessories / Accessori opzionali

Suspension kits / Kit di sospensione



Sloped ceiling suspension kit / Kit di sospensione per soffitto inclinato

Not included


Nickel plated - 1 Piece

1A0510000.00.00



LED IS MORE

Davide Groppi / 2011



A tribute to Mies van der Rohe and his Less is More.
The project represents a light icon in a LED key,
with a peculiar attention to energy savings and the quality of light.

Un omaggio a Mies van der Rohe e al suo Less is More.
Il progetto rappresenta un'icona della luce, rivisitata in chiave LED,
con una particolare attenzione al risparmio energetico e alla qualità della luce stessa.


LED IS MORE

Davide Groppi / 2011

Suspension / Diffuse / Indoor

Material Metal - Methacrylate
Finish .03 Matt White

Note Suspension luminaire. Sanded methacrylate diffuser. Matt white rose. *Apparecchio illuminante a sospensione. Diffusore in metacrilato sabbato. Rosone bianco opaco. Cavo bianco. Rosone unico per più apparecchi su richiesta.*
 White cable. Single rose for more than one lamp on request.



LED IS MORE


5,6W
 100-240V - 50/60Hz
 3000K - 354lm
 CRI >90
 Driver integrated
 ON/OFF
 CE IP20

Matt White - 3000K - ON/OFF

1A2790300.30.00

Optional accessories / Accessori opzionali


Suspension kits / Kit di sospensione



Decentralization kit / Kit decentratore

Not included

1A0360000.00.00



Kit ceiling rose and decentralizer / Kit rosone e decentratore

Not included

Matt White White cable 3 m included

1A0770300.00.00

Matt Black Black cable 3 m included

1A0770400.00.00





LOUIS XIV

Daide Groppi / 2023


Louis XIV is the freakiest letter of our light alphabet.
It's a disobedient design that translates a certain rebellion
to common lamp models into light.
I wanted to investigate the idea of the chandelier: in line with our poetics,
Louis XIV is the only possible solution for lightness and irony.
Dimmable suspension lamp with double emission.

Louis XIV è la lettera più "freak" del nostro alfabeto luminoso.
È un progetto disobbediente, che traduce in luce una certa ribellione
ai modelli comuni di fare lampade.
Volevo affrontare il tema del lampadario a gocce:
Louis XIV è l'unica soluzione possibile, secondo le nostre poetiche, tra leggerezza e ironia.
Lampada a sospensione dimmerabile a doppia emissione.

Suspension / Direct-Indirect / Indoor


Material Glass - Metal
Finish .19 Polished Gold

Note Suspension luminaire. Eighty crystal drops and a bird. Natural brass branches. Structure with polished gold finish. Matt white rose. Dual emission and on/off. White cable. LOUIS XIV 2: version with power cable only and without rose. *Apparecchio illuminante a sospensione. Ottanta gocce in cristallo e un uccellino. Rami in ottone naturale. Struttura con finitura oro lucido. Rosone bianco opaco. Doppia emissione ed accensione. Cavo bianco. LOUIS XIV 2: versione con solo il cavo di alimentazione e senza rosone.*




LOUIS XIV 1
 Ceiling driver version
 16,5W
 110-240V - 50/60Hz
 2700K - Up 890lm - Down 210lm /
 3000K - Up 936lm - Down 235lm
 CRI >90
 Down UGR <19
 Driver integrated
 TRIAC/IGBT
 CE IP20

Polished Gold - 2700K - TRIAC/IGBT | 1A4361900.27.02
 Polished Gold - 3000K - TRIAC/IGBT | 1A4361900.30.02



LOUIS XIV 1
 Ceiling driver version
 16,5W
 110-240V - 50/60Hz
 2700K - Up 890lm - Down 210lm /
 3000K - Up 936lm - Down 235lm
 CRI >90
 Down UGR <19
 Driver integrated
 DALI - PUSH - 1-10V
 CE IP20

Polished Gold - 2700K - DALI - PUSH - 1-10V | 1A4361900.27.07
 Polished Gold - 3000K - DALI - PUSH - 1-10V | 1A4361900.30.07




LOUIS XIV 2
 Remote driver version
 15W
 Max 250mA DC
 2700K - Up 890lm - Down 210lm /
 3000K - Up 936lm - Down 235lm
 CRI >90
 Down UGR <19
 Driver not included
 2 Drivers required
 CE IP20


Polished Gold - 2700K | 1A4361900.27.20
 Polished Gold - 3000K | 1A4361900.30.20

Compulsory accessories / Accessori obbligatori


Drivers / Alimentatori



Driver / Alimentatore		Not included
220-240V(110-127V)	250mA/13,5W(13,5W)/IP20/DALI - PUSH LOUIS XIV 2 - 1-10V	1Z0241270.250




Driver / Alimentatore		Not included
220-240V	250mA/12,5W/IP20/TRIAC/IGBT LOUIS XIV 2	1Z0241280



Driver / Alimentatore		Not included
220-240V	250mA/4,2W/IP20/TRIAC/IGBT LOUIS XIV 2	1Z2320010

Optional accessories / Accessori opzionali

Suspension kits / Kit di sospensione



Recessed suspension kit for 12,5 mm plasterboard / Kit di sospensione da incasso per cartongesso 12,5 mm		Not included
Matt White	For electrical cables - 1 Piece Plasterboard cut-out Ø 44 mm Minimum space for mounting 70 mm	LOUIS XIV 2 1X0000300.05.00
Matt Black	For electrical cables - 1 Piece Plasterboard cut-out Ø 44 mm Minimum space for mounting 70 mm	LOUIS XIV 2 1X0000400.05.00





Light and transparency are the true stars of this project. We have always liked to think heretically, evoking mystery, magic and seduction. Magia is the new modular suspension lighting system that can be adapted to suit the different heights of the rooms and can generate direct and indirect light with the 360° adjustable module.

In this case, the lens is not used to focus, but to modify the vision and perception of the object.

The effect of the convex lens conceals the part of the light beam and produces the lightest effect of suspension and inconsistency. Luminaire designed also to be powered by ENDLESS conductive tape.

Archiproducts Design Award 2023


La luce e la trasparenza sono le vere protagoniste di questo progetto. Da sempre ci piace pensare in modo eretico, evocando mistero, magia e seduzione.

Magia è il nuovo sistema d'illuminazione a sospensione componibile e adattabile a seconda delle diverse altezze degli ambienti che può generare luce diretta e indiretta con il modulo orientabile a 360°.


In questo caso, la lente non è usata per focalizzare, ma per modificare la visione e la percezione dell'oggetto. L'effetto della lente convessa permette di celare la parte di emissione della luce e produrre un leggerissimo effetto di sospensione e inconsistenza. Apparecchio illuminante alimentabile anche con il tape conduttivo ENDLESS.

Archiproducts Design Award 2023


Single installation with ceiling driver




Multiple installation with ceiling driver



Single installation with recessed or ceiling suspension kit



Multiple installation with recessed or ceiling suspension kit




Suspension / Direct-Indirect / Indoor

Material	Metal - PMMA
Finish	.19 Polished Gold .28 Polished Black Chrome

Note Modular suspension luminaire. Adjustable along the horizontal axis. Transparent bar with refractive effect. LED module profile with matt black finish. Details with polished gold or black chrome finish. Matt white rose. Possibility for the luminaire to be powered by ENDLESS conductive tape and by dedicated voltage/current (Max 48V DC - Max 150W - Max 4A). See page: ENDLESS.

Apparecchio illuminante a sospensione componibile. Orientabile lungo l'asse orizzontale. Barra trasparente con effetto rifrattivo. Profilo del modulo LED con finitura nero opaco. Dettagli con finitura oro lucido o cromo nero. Rosone bianco opaco. Alimentabile anche con il tape conduttivo ENDLESS e tensione/corrente dedicata (Max 48V DC - Max 150W - Max 4A). Vedi pagina ENDLESS.

**MAGIA - MODULE**

19W
24V DC
2700K - 1272lm / 3000K - 1312lm
CRI >90
Driver not included



Polished Gold - 2700K	1A4721900.27.20
Polished Gold - 3000K	1A4721900.30.20
Polished Black Chrome - 2700K	1A4722800.27.20
Polished Black Chrome - 3000K	1A4722800.30.20

Compulsory accessories / Accessori obbligatori

Installation kits / Kit d'installazione

**Wire guide / Guidacavo**

Matt Black	1 Piece	1A3040400.00.00	Not included
------------	---------	-----------------	--------------

**Unipolar wire - 6 m / Cavo unipolare - 6 m**

1 Piece - Max 60V DC	Max 3 modules	1A4730000.00.00	Not included
----------------------	---------------	-----------------	--------------

Suspension kits / Kit di sospensione

**Recessed suspension kit for 12,5 mm plasterboard / Kit di sospensione da incasso per cartongesso 12,5 mm**


Matt White	For electrical cables - 1 Piece Plasterboard cut-out Ø 44 mm Minimum space for mounting 70 mm	1X0000300.02.00	Not included
Matt Black	For electrical cables - 1 Piece Plasterboard cut-out Ø 44 mm Minimum space for mounting 70 mm	1X0000400.02.00	

**Ceiling suspension kit / Kit di sospensione da soffitto**


Matt White	For electrical cables - 1 Piece	1X0010300.02.00	Not included
Matt Black	For electrical cables - 1 Piece	1X0010400.02.00	

Compulsory accessories / Accessori obbligatori


Drivers / Alimentatori

**Ceiling driver / Driver da soffitto**


Matt White	Input 220-240V - 50/60Hz Output 24V - 21W - IP20 DALI - PUSH - 1-10V - TRIAC	Max 1 module	1A4780300.00.05	Not included
------------	--	--------------	-----------------	--------------

**Ceiling driver / Driver da soffitto**


Matt White	Input 120-240V - 50/60Hz Output 24V - 60W - IP20 DALI - PUSH - 1-10V - TRIAC	Max 3 modules	1A4740300.00.05	Not included
------------	--	---------------	-----------------	--------------

**Driver / Alimentatore**


100-240V	24V/50W/IP20/ON/OFF	Max 1 module	1Z1120490	Not included
----------	---------------------	--------------	-----------	--------------

**Driver / Alimentatore**

100-240V	24V/80W/IP20/ON/OFF	Max 3 modules	1Z1120440	Not included
----------	---------------------	---------------	-----------	--------------

**Driver / Alimentatore**


100-240V	24V/150W/IP67/1-10V	Max 6 modules	1Z1120500	Not included
----------	---------------------	---------------	-----------	--------------

**Controller**

DALI - PUSH - 0/1-10V - TRIAC - IP20	1Z2170010	Not included
--------------------------------------	-----------	--------------


Optional accessories / Accessori opzionali

Suspension kits / Kit di sospensione


**Wall adapter plate / Piastra di adattamento da parete**

Matt White	For mounting on brick masonry walls	1X0050300.01.00	Not included
------------	-------------------------------------	-----------------	--------------







Example of single installation with ceiling driver




Example of multiple installation with ceiling driver




Example of single installation with recessed suspension kit




Example of multiple installation with recessed suspension kit



Example of single installation with ceiling suspension kit



Example of multiple installation with ceiling suspension kit



Example of multiple installation | Max 3 modules for cable



So slim and essential...

The fundamental concept of this project is minimalism.

A small tube that lights the table with wonder.

A real dual project: sign and light.

Luminaire available also in ENDLESS version.

Così esile ed essenziale...

L'essenzialità è la componente fondamentale di progetto.

Un piccolo tubo in metallo per fare una meravigliosa luce sul tavolo.


Un vero progetto duale: segno e luce.

Apparecchio illuminante disponibile anche nella versione ENDLESS.

Suspension / Direct / Indoor

Material	Metal			
Finish	.03 Matt White	.04 Matt Black	.08 Brushed Brass	.26 Total Black
Note	Suspension luminaire. Matt white rose and white cable for the matt white and matt black finish. Matt black rose and black cable for the total black and brushed brass finish. Single rose for more than one lamp on request. MISS 2: plasterboard version with magnetic fixing flat rose. MISS ENDLESS: luminaire dedicated to ENDLESS system (Max 48V DC - Max 150W - Max 4A). It can be used, on the same circuit, with the ENDLESS models. See page: ENDLESS.			

Apparecchio illuminante a sospensione. Rosone bianco opaco e cavo bianco per la finitura bianco opaco e nero opaco. Rosone nero opaco e cavo nero per la finitura total black e ottone spazzolato. Rosone unico per più apparecchi su richiesta. MISS 2: versione per cartongesso con rosone piano a fissaggio magnetico. MISS ENDLESS: apparecchio illuminante dedicato al sistema ENDLESS (Max 48V DC - Max 150W - Max 4A) ed utilizzabile, sullo stesso circuito, con i modelli ENDLESS. Vedi pagina ENDLESS.




MISS 1
 Ceiling driver version
 5,6W
 100-240V - 50/60Hz
 2700K - 290lm / 3000K - 310lm
 CRI >90
 Driver integrated
 ON/OFF
CE IP20

Matt White - 2700K - ON/OFF	1A2960300.27.00
Matt White - 3000K - ON/OFF	1A2960300.30.00
Matt Black - 2700K - ON/OFF	1A2960400.27.00
Matt Black - 3000K - ON/OFF	1A2960400.30.00
Brushed Brass - 2700K - ON/OFF	1A2960800.27.00
Brushed Brass - 3000K - ON/OFF	1A2960800.30.00
Total Black - 2700K - ON/OFF	1A2962600.27.00
Total Black - 3000K - ON/OFF	1A2962600.30.00




MISS 1
 Ceiling driver version
 6W
 110-240V - 50/60Hz
 2700K - 290lm / 3000K - 310lm
 CRI >90
 Driver integrated
 DALI
CE IP20

Matt White - 2700K - DALI	1A2960300.27.01
Matt White - 3000K - DALI	1A2960300.30.01
Matt Black - 2700K - DALI	1A2960400.27.01
Matt Black - 3000K - DALI	1A2960400.30.01
Brushed Brass - 2700K - DALI	1A2960800.27.01
Brushed Brass - 3000K - DALI	1A2960800.30.01
Total Black - 2700K - DALI	1A2962600.27.01
Total Black - 3000K - DALI	1A2962600.30.01




MISS 1
 Ceiling driver version
 6W
 110-240V - 50/60Hz
 2700K - 290lm / 3000K - 310lm
 CRI >90
 Driver integrated
 PUSH
CE IP20

Matt White - 2700K - PUSH	1A2960300.27.04
Matt White - 3000K - PUSH	1A2960300.30.04
Matt Black - 2700K - PUSH	1A2960400.27.04
Matt Black - 3000K - PUSH	1A2960400.30.04
Brushed Brass - 2700K - PUSH	1A2960800.27.04
Brushed Brass - 3000K - PUSH	1A2960800.30.04
Total Black - 2700K - PUSH	1A2962600.27.04
Total Black - 3000K - PUSH	1A2962600.30.04




MISS 1
 Ceiling driver version
 6W
 110-240V - 50/60Hz
 2700K - 290lm / 3000K - 310lm
 CRI >90
 Driver integrated
 1-10V
CE IP20

Matt White - 2700K - 1-10V	1A2960300.27.03
Matt White - 3000K - 1-10V	1A2960300.30.03
Matt Black - 2700K - 1-10V	1A2960400.27.03
Matt Black - 3000K - 1-10V	1A2960400.30.03
Brushed Brass - 2700K - 1-10V	1A2960800.27.03
Brushed Brass - 3000K - 1-10V	1A2960800.30.03
Total Black - 2700K - 1-10V	1A2962600.27.03
Total Black - 3000K - 1-10V	1A2962600.30.03



MISS 1
 Ceiling driver version
 6W
 110-240V - 50/60Hz
 2700K - 290lm / 3000K - 310lm
 CRI >90
 Driver integrated
 TRIAC/IGBT
CE IP20

Matt White - 2700K - TRIAC/IGBT	1A2960300.27.02
Matt White - 3000K - TRIAC/IGBT	1A2960300.30.02
Matt Black - 2700K - TRIAC/IGBT	1A2960400.27.02
Matt Black - 3000K - TRIAC/IGBT	1A2960400.30.02
Brushed Brass - 2700K - TRIAC/IGBT	1A2960800.27.02
Brushed Brass - 3000K - TRIAC/IGBT	1A2960800.30.02
Total Black - 2700K - TRIAC/IGBT	1A2962600.27.02
Total Black - 3000K - TRIAC/IGBT	1A2962600.30.02




MISS 2

Remote driver version
4W
Max 350mA DC
2700K - 290lm / 3000K - 310lm
CRI >90
Driver not included
CE IP20

Matt White - 2700K
Matt White - 3000K
Matt Black - 2700K
Matt Black - 3000K
Brushed Brass - 2700K
Brushed Brass - 3000K
Total Black - 2700K
Total Black - 3000K

1A2970300.27.20
1A2970300.30.20
1A2970400.27.20
1A2970400.30.20
1A2970800.27.20
1A2970800.30.20
1A2972600.27.20
1A2972600.30.20



MISS ENDLESS


Endless version only
5,5W - 0,14A
48V DC - 50/60Hz
2700K - 290lm / 3000K - 310lm
CRI >90
Driver not included
See page ENDLESS
CE IP20 TE

Matt White - 2700K
Matt White - 3000K
Matt Black - 2700K
Matt Black - 3000K
Brushed Brass - 2700K
Brushed Brass - 3000K
Total Black - 2700K
Total Black - 3000K


1A2960300.27.40
1A2960300.30.40
1A2960400.27.40
1A2960400.30.40
1A2960800.27.40
1A2960800.30.40
1A2962600.27.40
1A2962600.30.40

Compulsory accessories / Accessori obbligatori


Drivers / Alimentatori



Driver / Alimentatore				Not included
220-240V(100-127V)	350mA/17W(15W)/IP20/DALI	MISS 2	1Z0241180.350	




Driver / Alimentatore				Not included
220-240V(100-127V)	350mA/18W(15W)/IP20/PUSH - 1-10V	MISS 2	1Z0240870.350	




Driver / Alimentatore				Not included
220-240V	350mA/17W/IP20/TRIAC/IGBT	MISS 2	1Z0240850.350	

Optional accessories / Accessori opzionali

Suspension kits / Kit di sospensione



Decentralization kit / Kit decentratore			Not included
	MISS 1	1A0360000.00.00	



Kit ceiling rose and decentralizer / Kit rosone e decentratore				Not included
Matt White	White cable 3 m included	MISS 1	1A0770300.00.00	
Matt Black	Black cable 3 m included	MISS 1	1A0770400.00.00	

MOON

Daide Groppi / 2005



Moon was created from the dream of bringing the moon inside your own home.
The hand-made Japanese paper surface makes every lamp unique.
Table and floor versions available.

Moon nasce da un sogno, quello di portare la luna dentro casa.
La superficie di carta giapponese, fatta a mano, rende unico ogni pezzo.
Disponibile anche nelle versioni da tavolo e terra.


Suspension / Diffuse / Indoor

Material Japanese paper - PE
Finish .00 Standard

Note Suspension luminaire. PE and Japanese paper shade. Matt white rose. AISI 304 stainless steel suspension cable. White cable. Compulsory moisture barrier bag packaging for air and sea shipping. MOON 60 DE: version with dual emission and on/off. Transparent cable. For air and sea shipping: moisture barrier bag packaging compulsory for all models and wooden crate specifically compulsory for MOON 120 and MOON 200 models.

Apparecchio illuminante a sospensione. Paralume in PE e carta giapponese. Rosone bianco opaco. Cavo di sospensione in inox AISI 304. Cavo bianco. MOON 60 DE: versione a doppia emissione ed accensione. Cavo trasparente.


Per spedizioni aerea e via nave: sacco barriera obbligatorio per tutti i modelli e cassa in legno obbligatoria per modelli MOON 120 e MOON 200.



MOON 60
 Max 15W - E27
 100-240V - 50/60Hz
 ON/OFF
 Bulb not included
 CE IP20

Standard - ON/OFF


|1A2820000.00.00 |



MOON 60 DE
 Dual emission
 Max 15W - E27 + Max 10W - GU10
 100-240V - 50/60Hz
 ON/OFF
 Bulb not included
 CE IP20

Standard - ON/OFF


|1A2830000.00.00 |



MOON 80
 Max 15W - E27
 100-240V - 50/60Hz
 ON/OFF
 Bulb not included
 CE IP20

Standard - ON/OFF


|1A2840000.00.00 |



MOON 120
 Max 2x25W - E27
 100-240V - 50/60Hz
 ON/OFF
 Bulb not included
 CE IP20

Standard - ON/OFF

|1A2850000.00.00 |



MOON 200
 Max 4x25W - E27
 100-240V - 50/60Hz
 ON/OFF
 Bulb not included
 Transport excluded
 CE IP20

Standard - ON/OFF

|1A2860000.00.00 |

Optional accessories / Accessori opzionali

Bulbs / Lampadine



LED - GU10 - PAR16			Not included
220-240V - 5,5W - 25° 3000K - 375lm - CRI >97 Energy Efficiency G - Dimmable	MOON 60 DE	1Y0330500	



LED - E27 - A60			Not included
220-240V - 11,2W - 360° 2700K - 1521lm - CRI >90 Energy Efficiency D - Dimmable	MOON 60 / MOON 60 DE / MOON 80 / MOON 200	1Y0330790	



LED - E27 - A150			Not included
220-240V - 20W - 200° 2700K - 2452lm - CRI >80 Energy Efficiency E - Dimmable	MOON 120	1Y2160020	

Suspension kits / Kit di sospensione




Sloped rose suspension kit / Kit di sospensione per rosone inclinato			Not included
Nickel plated - 1 Piece	MOON 60 / MOON 60 DE / MOON 80	1A0520000.00.00	



Sloped ceiling suspension kit / Kit di sospensione per soffitto inclinato			Not included
Nickel plated - 1 Piece	MOON 120	1A0510000.00.00	



Decentralization kit / Kit decentratore			Not included
		1A0360000.00.00	



Kit ceiling rose and decentralizer / Kit rosone e decentratore			Not included
Matt White	White cable 3 m included	1A0770300.00.00	
Matt Black	Black cable 3 m included	1A0770400.00.00	

Optional accessories / Accessori opzionali

Other accessories / Altri accessori

Moisture barrier bag / Sacco barriera			Not included
Packaging for air and sea shipping	MOON 60 / MOON 60 DE	4A2820010	

Moisture barrier bag / Sacco barriera			Not included
Packaging for air and sea shipping	MOON 80	4A2840010	

Moisture barrier bag / Sacco barriera			Not included
Packaging for air and sea shipping	MOON 120	49860020	

Moisture barrier bag / Sacco barriera			Not included
Packaging for air and sea shipping	MOON 200	48780030	

Wooden crate / Cassa in legno			Not included
Packaging for air and sea shipping	MOON 120	49860010	

Wooden crate / Cassa in legno			Not included
Packaging for air and sea shipping	MOON 200	48780020	



NEURO

Daide Groppi - Beppe Merlano / 2013



The idea is to bring light wherever you like, starting from a socket.

A simple project, almost a revival of the old electrical wiring.

A plug, a cable, some isolators, a socket and a LED.

Outdoor version also available.

Design Plus Award 2014

È l'idea di portare la luce dove si desidera, partendo da una presa elettrica.

Un progetto semplice, quasi la rivisitazione dei vecchi impianti elettrici.

Una spina, un cavo, degli isolatori, un portalamпада e una lampadina a LED.

Disponibile anche nella versione outdoor.

Premio Design Plus 2014


NEURO

Davide Groppi - Beppe Merlano / 2013

Suspension / Direct / Indoor

Material Metal
Finish .03 Matt White .04 Matt Black

Note Suspension luminaire. Five cable clips included. Matt white cable clips and white cable for the matt white finish. Matt black cable clips and black cable for the matt black finish. *Apparecchio illuminante a sospensione. Cinque bloccacavo inclusi. Bloccacavo bianco opaco e cavo bianco per la finitura bianco opaco. Bloccacavo nero opaco e cavo nero per la finitura nero opaco.*



NEURO

Max 15W - E27
 100-240V - 50/60Hz
 ON/OFF
 Bulb not included
 CE IP20

Matt White - ON/OFF
 Matt Black - ON/OFF

1A0160300.00.00
 1A0160400.00.00

Optional accessories / Accessori opzionali

Installation kits / Kit d'installazione



Clamp / Bloccacavo		Included
Matt White	1 Piece	1A3270300.00.00
Matt Black	1 Piece	1A3270400.00.00




Wall and ceiling rose / Rosone da parete e soffitto		Not included
Matt White		1A3440300.00.00
Matt Black		1A3440400.00.00

Bulbs / Lampadine



LED - E27 - PAR30s		Not included
	220-240V - 9,5W - 25° 3000K - 760lm - CRI >80 Energy Efficiency F - Dimmable	1Y0330730






The light in the plate is the most beautiful light.
Light as an ingredient, used courteously but at the same time decisively.

La luce nel piatto è la luce più bella.
Una luce intesa come ingrediente della cucina, usata con garbo,
ma nello stesso tempo con decisione.

Suspension / Direct / Indoor

Material Metal
 Finish .03 Matt White

Note Suspension luminaire. Matt white rose. White cable. *Apparecchio illuminante a sospensione. Rosone bianco opaco. Cavo bianco.*



OVO

Max 20W - GU4 - 12V
 230-240V - 50/60Hz
 ON/OFF
 Bulb not included
 CE IP20 0,5 m

Matt White - ON/OFF

| 1A2890300.00.00 |

Optional accessories / Accessori opzionali

Bulbs / Lampadine



LED - GU4 - MR11

Not included

12V - 4W - 24°
 2700K - 200lm - CRI >80
 Energy Efficiency G

1Y0330450





OVONELPIATTO

Massimiliano Alajmo - Raffaele Alajmo / 2010

The light in the plate is the most beautiful light.
Light as an ingredient, used courteously but at the same time decisively.

La luce nel piatto è la luce più bella.
Una luce intesa come ingrediente della cucina, usata con garbo,
ma nello stesso tempo con decisione.


OVONELPIATTO

Massimiliano Alajmo - Raffaele Alajmo / 2010

Suspension / Direct / Indoor

Material Metal
Finish .03 Matt White

Note Suspension luminaire. Matt white rose. White cable. *Apparecchio illuminante a sospensione. Rosone bianco opaco. Cavo bianco.*



OVONELPIATTO

Max 20W - GU4 - 12V
230-240V - 50/60Hz
ON/OFF
Bulb not included
CE IP20 0,5 m

Matt White - ON/OFF

1A2880300.00.00

Optional accessories / Accessori opzionali

Bulbs / Lampadine



LED - GU4 - MR11

Not included

12V - 4W - 24°
2700K - 200lm - CRI >80
Energy Efficiency G

1Y0330450





REFLEX S

Michele Groppi / 2023

A powerful LED and a subtle mirror.
A magic and almost invisible lighting solution,
which provides an indirect light that multiplies spaces
and gives the eye unprecedented perspectives, unexpected depths, illusions of light.

Wall version also available.

Luminaire designed also to be powered by ENDLESS conductive tape.

Un LED potente, uno specchio sottile.

Un apparecchio magico e quasi invisibile per una luce che moltiplica gli spazi
e regala allo sguardo prospettive inedite, profondità impreviste, illusioni di luce.

Disponibile anche nella versione da parete.


Apparecchio illuminante alimentabile anche con il tape conduttivo ENDLESS.

Suspension / Indirect / Indoor

Material Metal - Mirror
Finish .04 Matt Black

Note Suspension luminaire. Plane with mirror finish. Matt black rear plane. Matt white rose. AISI 304 stainless steel suspension cables. Black cable. Possibility for the luminaire to be powered by ENDLESS conductive tape and by dedicated voltage/current (Max 48V DC - Max 150W - Max 4A). See page: ENDLESS. REFLEX S 2: version with power cable only and without rose.

Apparecchio illuminante a sospensione. Piano con finitura a specchio. Retro del piano nero opaco. Rosone bianco opaco. Cavi di sospensione in inox AISI 304. Cavo nero. Alimentabile anche con il tape conduttivo ENDLESS e tensione/corrente dedicata (Max 48V DC - Max 150W - Max 4A). Vedi pagina ENDLESS. REFLEX S 2: versione con solo il cavo di alimentazione e senza rosone.

**REFLEX S 1**

Ceiling driver version

54W

110-240V - 50/60Hz

2700K - 5787lm / 3000K - 6156lm

CRI >90

Driver integrated

DALI - PUSH - 1-10V


CE IP20

Matt Black - 2700K - DALI - PUSH - 1-10V

1A4790400.27.07

Matt Black - 3000K - DALI - PUSH - 1-10V

1A4790400.30.07

**REFLEX S 2**

Remote driver version

49W

Max 500mA DC

2700K - 5787lm / 3000K - 6156lm

CRI >90

Driver not included

CE IP20 TE

Matt Black - 2700K


1A4790400.27.20

Matt Black - 3000K

1A4790400.30.20

Compulsory accessories / Accessori obbligatori

Drivers / Alimentatori



Driver / Alimentatore		Not included	
220-240V(100-127V)	1000mA/60W(40W)/IP20/DALI	REFLEX S 2	1Z0241140.1000

Optional accessories / Accessori opzionali


Suspension kits / Kit di sospensione

**Recessed suspension kit for 12,5 mm plasterboard / Kit di sospensione da incasso per cartongesso 12,5 mm** Not included

Matt White	For suspension cables - 1 Piece Plasterboard cut-out Ø 44 mm Minimum space for mounting 70 mm		1X0000300.01.00
Matt Black	For suspension cables - 1 Piece Plasterboard cut-out Ø 44 mm Minimum space for mounting 70 mm		1X0000400.01.00
Matt White	For electrical cables - 1 Piece Plasterboard cut-out Ø 44 mm Minimum space for mounting 70 mm	REFLEX S 2	1X0000300.04.00
Matt Black	For electrical cables - 1 Piece Plasterboard cut-out Ø 44 mm Minimum space for mounting 70 mm	REFLEX S 2	1X0000400.04.00

**Ceiling suspension kit / Kit di sospensione da soffitto** Not included

Matt White	For suspension cables - 1 Piece		1X0010300.01.00
Matt Black	For suspension cables - 1 Piece		1X0010400.01.00
Matt White	For electrical cables - 1 Piece	REFLEX S 2	1X0010300.04.00
Matt Black	For electrical cables - 1 Piece	REFLEX S 2	1X0010400.04.00

**Wall adapter plate / Piastra di adattamento da parete** Not included

Matt White	For mounting on brick masonry walls		1X0050300.01.00
------------	-------------------------------------	--	-----------------

SHANGHAI

Davide Groppi / 2013




The smallest possible shape.
A suspended luminous segment.
Beautiful by itself or in composition.
Suitable for working area or kitchen.
Luminaire designed also to be powered by ENDLESS conductive tape.

La forma minima possibile.
Un segmento luminoso sospeso.
Bellissima da sola o in composizione.
Per i luoghi di lavoro o per la cucina.
Apparecchio illuminante alimentabile anche con il tape conduttivo ENDLESS.

Suspension / Direct / Indoor

Material Metal - Methacrylate
Finish .03 Matt White .08 Brushed Brass

Note Suspension luminaire. Matt white rose. AISI 304 stainless steel suspension cables. Transparent cable. Possibility for the luminaire to be powered by ENDLESS conductive tape and by dedicated voltage/current (Max 48V DC - Max 150W - Max 4A). See page: ENDLESS. SHANGHAI 2: version with power cable only and without rose. *Apparecchio illuminante a sospensione. Rosone bianco opaco. Cavi di sospensione in inox AISI 304. Cavo trasparente. Alimentabile anche con il tape conduttivo ENDLESS e tensione/corrente dedicata (Max 48V DC - Max 150W - Max 4A). Vedi pagina ENDLESS. SHANGHAI 2: versione con solo il cavo di alimentazione e senza rosone.*




SHANGHAI 1

Ceiling driver version
 15,5W
 110-240V - 50/60Hz
 2700K - 592lm / 3000K - 619lm
 CRI >90
 Driver integrated
 PUSH
 CE IP20

Matt White - 2700K - PUSH
 Matt White - 3000K - PUSH
 Brushed Brass - 2700K - PUSH
 Brushed Brass - 3000K - PUSH

1A3260300.27.04
 1A3260300.30.04
 1A3260800.27.04
 1A3260800.30.04



SHANGHAI 2


Remote driver version
 13W
 24V DC
 2700K - 592lm / 3000K - 619lm
 CRI >90
 Driver not included
 CE IP20 I E

Matt White - 2700K
 Matt White - 3000K
 Brushed Brass - 2700K
 Brushed Brass - 3000K


1A3260300.27.20
 1A3260300.30.20
 1A3260800.27.20
 1A3260800.30.20

Compulsory accessories / Accessori obbligatori


Drivers / Alimentatori



Driver / Alimentatore				Not included
220-240V(100-127V)	24V/16W(15W)/IP20/DALI	SHANGHAI 2	1Z0241180.24	




Driver / Alimentatore				Not included
220-240V(100-127V)	24V/20W(15W)/IP20/PUSH	SHANGHAI 2	1Z0240870.24	



Driver / Alimentatore				Not included
220-240V	24V/20W/IP20/TRIAC/IGBT	SHANGHAI 2	1Z0240850.24	

Optional accessories / Accessori opzionali

Suspension kits / Kit di sospensione



Sloped ceiling suspension hook / Gancio di sospensione per soffitto inclinato			Not included
	Chrome plated - 1 Piece		1A0530000.00.00



Recessed suspension kit for 12,5 mm plasterboard / Kit di sospensione da incasso per cartongesso 12,5 mm				Not included
Matt White	For suspension cables - 1 Piece Plasterboard cut-out Ø 44 mm Minimum space for mounting 70 mm		1X0000300.01.00	
Matt Black	For suspension cables - 1 Piece Plasterboard cut-out Ø 44 mm Minimum space for mounting 70 mm		1X0000400.01.00	
Matt White	For electrical cables - 1 Piece Plasterboard cut-out Ø 44 mm Minimum space for mounting 70 mm	SHANGHAI 2	1X0000300.04.00	
Matt Black	For electrical cables - 1 Piece Plasterboard cut-out Ø 44 mm Minimum space for mounting 70 mm	SHANGHAI 2	1X0000400.04.00	



Ceiling suspension kit / Kit di sospensione da soffitto				Not included
Matt White	For suspension cables - 1 Piece		1X0010300.01.00	
Matt Black	For suspension cables - 1 Piece		1X0010400.01.00	
Matt White	For electrical cables - 1 Piece	SHANGHAI 2	1X0010300.04.00	
Matt Black	For electrical cables - 1 Piece	SHANGHAI 2	1X0010400.04.00	



Wall adapter plate / Piastra di adattamento da parete			Not included
Matt White	For mounting on brick masonry walls		1X0050300.01.00




A de-structured chandelier that can be re-assembled as you like.
A conjuring trick that gives you the possibility of connecting the diodes in series using
very weak electric currents with wires that are practically invisible.
The very thin wire that connects the light sources and brings them alive, one in relation
to the other, is the principal component of this project.

Un lampadario destrutturato e componibile a piacere.
Un piccolo gioco di prestigio sfruttando la possibilità di collegare i diodi in serie utilizzando
correnti elettriche molto basse e quindi cavi quasi invisibili.
Il filo, sottilissimo, che unisce i corpi e li fa vivere l'uno in funzione dell'altro, è la
caratteristica principale di questo progetto.

Suspension / Direct / Indoor

Material Metal
Finish .03 Matt White .26 Total Black

Note Suspension luminaire. Matt white rose and red cables for the matt white finish. Matt black rose and anthracite grey cables for the matt black finish. AISI 304 stainless steel suspension cables. *Apparecchio illuminante a sospensione. Rosone bianco opaco e cavi rossi per la finitura bianco opaco. Rosone nero opaco e cavi grigio antracite per la finitura nero opaco. Cavi di sospensione in inox AISI 304.*




SIMBIOSI

15W
 110-240V - 50/60Hz
 2700K - 931lm / 3000K - 960lm
 CRI >90
 Driver integrated
 DALI
 CE IP20

Matt White - 2700K - DALI
 Matt White - 3000K - DALI
 Total Black - 2700K - DALI
 Total Black - 3000K - DALI

1A2870300.27.01
 1A2870300.30.01
 1A2872600.27.01
 1A2872600.30.01



SIMBIOSI

15W
 110-240V - 50/60Hz
 2700K - 931lm / 3000K - 960lm
 CRI >90
 Driver integrated
 PUSH
 CE IP20

Matt White - 2700K - PUSH
 Matt White - 3000K - PUSH
 Total Black - 2700K - PUSH
 Total Black - 3000K - PUSH


1A2870300.27.04
 1A2870300.30.04
 1A2872600.27.04
 1A2872600.30.04

Optional accessories / Accessori opzionali

Suspension kits / Kit di sospensione



Sloped ceiling suspension hook / Gancio di sospensione per soffitto inclinato Not included
 Chrome plated - 1 Piece 1A0530000.00.00



SOTTILE

Davide Groppi / 2023

A blade of light just 7 millimetres thick,
the expression of that purest and most essential part of our thought.
The surprise of an extremely thin, yet at the same time very bright, lamp.
Luminaire designed also to be powered by ENDLESS conductive tape.


Una lama di luce spessa solo 7 millimetri,
espressione di una parte del nostro pensiero, quello più puro ed essenziale.
La sorpresa di una lampada estremamente sottile, ma al contempo molto luminosa.
Apparecchio illuminante alimentabile anche con il tape conduttivo ENDLESS.

Suspension / Direct / Indoor

Material Metal
Finish .29 Brushed Bronze .36 Brushed Black

Note Suspension luminaire. Matt white rose. AISI 304 stainless steel suspension cable. Black cable. Luminaire designed to be powered by our ENDLESS conductive tape and dedicated voltage/current (Max 48V DC - Max 150W - Max 4A). See page: ENDLESS. SOTTILE 1 DE and SOTTILE 2 DE: dual emission version. SOTTILE 2 and SOTTILE 2 DE: version with power cable only and without rose.

Apparecchio illuminante a sospensione. Rosone bianco opaco. Cavo di sospensione in inox AISI 304. Cavo nero. Alimentabile anche con il tape conduttivo ENDLESS e tensione/corrente dedicata (Max 48V DC - Max 150W - Max 4A). Vedi pagina ENDLESS. SOTTILE 1 DE e SOTTILE 2 DE: versione a doppia emissione. SOTTILE 2 e SOTTILE 2 DE: versione con solo il cavo di alimentazione e senza rosone.




SOTTILE 1

Ceiling driver version
 22W
 220-240V - 50/60Hz
 2700K - 1692lm / 3000K - 1855lm
 CRI >90
 Driver integrated
 DALI - PUSH - 1-10V - TRIAC

CE IP20

Brushed Bronze - 2700K - DALI - PUSH - 1-10V - TRIAC	1A4232900.27.05
Brushed Bronze - 3000K - DALI - PUSH - 1-10V - TRIAC	1A4232900.30.05
Brushed Black - 2700K - DALI - PUSH - 1-10V - TRIAC	1A4233600.27.05
Brushed Black - 3000K - DALI - PUSH - 1-10V - TRIAC	1A4233600.30.05




SOTTILE 1 DE

Ceiling driver version - Dual emission
 2x22W
 120-240V - 50/60Hz
 2700K - Up 1692lm - Down 1692lm /
 3000K - Up 1855lm - Down 1855lm
 CRI >90
 Driver integrated
 DALI - PUSH - 1-10V - TRIAC

CE IP20

Brushed Bronze - 2700K - DALI - PUSH - 1-10V - TRIAC	1A4642900.27.05
Brushed Bronze - 3000K - DALI - PUSH - 1-10V - TRIAC	1A4642900.30.05
Brushed Black - 2700K - DALI - PUSH - 1-10V - TRIAC	1A4643600.27.05
Brushed Black - 3000K - DALI - PUSH - 1-10V - TRIAC	1A4643600.30.05




SOTTILE 2

Remote driver version
 19W
 24V DC
 2700K - 1692lm / 3000K - 1855lm
 CRI >90
 Driver not included

CE IP20 E

Brushed Bronze - 2700K	1A4232900.27.20
Brushed Bronze - 3000K	1A4232900.30.20
Brushed Black - 2700K	1A4233600.27.20
Brushed Black - 3000K	1A4233600.30.20



SOTTILE 2 DE



Remote driver version - Dual emission
 2x19W
 24V DC
 2700K - Up 1692lm - Down 1692lm /
 3000K - Up 1855lm - Down 1855lm
 CRI >90
 Driver not included

CE IP20 E

Brushed Bronze - 2700K	1A4642900.27.20
Brushed Bronze - 3000K	1A4642900.30.20
Brushed Black - 2700K	1A4643600.27.20
Brushed Black - 3000K	1A4643600.30.20

Compulsory accessories / Accessori obbligatori

Drivers / Alimentatori



Driver / Alimentatore	Not included	
100-240V	24V/50W/IP20/ON/OFF	SOTTILE 2 / SOTTILE 2 DE 1Z1120490

Controller	Not included	
	DALI - PUSH - 0/1-10V - TRIAC - IP20	SOTTILE 2 / SOTTILE 2 DE 1Z2170010

Optional accessories / Accessori opzionali


Suspension kits / Kit di sospensione




Recessed suspension kit for 12,5 mm plasterboard / Kit di sospensione da incasso per cartongesso 12,5 mm				Not included
Matt White	For suspension cables - 1 Piece Plasterboard cut-out Ø 44 mm Minimum space for mounting 70 mm		1X0000300.01.00	
Matt Black	For suspension cables - 1 Piece Plasterboard cut-out Ø 44 mm Minimum space for mounting 70 mm		1X0000400.01.00	
Matt White	For electrical cables - 1 Piece Plasterboard cut-out Ø 44 mm Minimum space for mounting 70 mm	SOTTILE 2 / SOTTILE 2 DE	1X0000300.04.00	
Matt Black	For electrical cables - 1 Piece Plasterboard cut-out Ø 44 mm Minimum space for mounting 70 mm	SOTTILE 2 / SOTTILE 2 DE	1X0000400.04.00	



Ceiling suspension kit / Kit di sospensione da soffitto				Not included
Matt White	For suspension cables - 1 Piece		1X0010300.01.00	
Matt Black	For suspension cables - 1 Piece		1X0010400.01.00	
Matt White	For electrical cables - 1 Piece	SOTTILE 2 / SOTTILE 2 DE	1X0010300.04.00	
Matt Black	For electrical cables - 1 Piece	SOTTILE 2 / SOTTILE 2 DE	1X0010400.04.00	



Wall adapter plate / Piastra di adattamento da parete				Not included
Matt White	For mounting on brick masonry walls		1X0050300.01.00	



SOTTOSOPRA

Daide Groppi / 2023




The purity of the suspended cone encases a small light machine that produces direct, indirect and diffused light at the same time.
Sottosopra: pure, elegant, wonderfully efficient.

La purezza del cono sospeso racchiude una piccola macchina di luce che produce contemporaneamente luce diretta, indiretta e diffusa.
Sottosopra: pura, elegante, meravigliosamente efficiente.

Suspension / Direct-Indirect / Indoor

Material Metal
Finish .03 Matt White


Note Suspension luminaire. Matt white rose. Dual emission and on/off. *Apparecchio illuminante a sospensione. Rosone bianco opaco. Doppia emissione ed accensione. Cavo bianco. SOTTOSOPRA 2: versione con solo il cavo di alimentazione e senza rosone.*



SOTTOSOPRA 1

Ceiling driver version
 24W
 240V - 50/60Hz
 2700K - Down 228lm - Up 1827lm /
 3000K - Down 245lm - Up 1876lm
 CRI >90
 UGR <19
 Driver integrated
 TRIAC/IGBT
 CE IP20


Matt White - 2700K - TRIAC/IGBT | 1A4540300.27.02
 Matt White - 3000K - TRIAC/IGBT | 1A4540300.30.02



SOTTOSOPRA 1

Ceiling driver version
 24W
 100-240V - 50/60Hz
 2700K - Down 228lm - Up 1827lm /
 3000K - Down 245lm - Up 1876lm
 CRI >90
 UGR <19
 Driver integrated
 DALI - PUSH - 1-10V
 CE IP20

Matt White - 2700K - DALI - PUSH - 1-10V | 1A4540300.27.07
 Matt White - 3000K - DALI - PUSH - 1-10V | 1A4540300.30.07




SOTTOSOPRA 2

Remote driver version
 30W
 Max 500mA DC
 2700K - Down 228lm - Up 1827lm /
 3000K - Down 245lm - Up 1876lm
 CRI >90
 UGR <19
 Driver not included
 2 Drivers required
 CE IP20


Matt White - 2700K | 1A4540300.27.20
 Matt White - 3000K | 1A4540300.30.20

Compulsory accessories / Accessori obbligatori

Drivers / Alimentatori




Driver / Alimentatore		Not included
220-240V(110-127V)	500mA/25W(13,5W)/IP20/DALI - PUSH - 1-10V	SOTTOSOPRA 2 1Z0241270.500




Driver / Alimentatore		Not included
220-240V	500mA/20W/IP20/TRIAC/IGBT	SOTTOSOPRA 2 1Z0240850.500

Optional accessories / Accessori opzionali

Suspension kits / Kit di sospensione



Recessed suspension kit for 12,5 mm plasterboard / Kit di sospensione da incasso per cartongesso 12,5 mm		Not included
Matt White	For electrical cables - 1 Piece Plasterboard cut-out Ø 44 mm Minimum space for mounting 70 mm	SOTTOSOPRA 2 1X0000300.05.00
Matt Black	For electrical cables - 1 Piece Plasterboard cut-out Ø 44 mm Minimum space for mounting 70 mm	SOTTOSOPRA 2 1X0000400.05.00



A tool to light.

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.


Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

Suspension / Direct / Indoor

Material Metal - Polycarbonate
Finish .03 Matt White


Note Suspension luminaire. Matt white rose. AISI 304 stainless steel suspension cables. White cable. SPY DE: version with dual emission and on/off. Transparent cable. *Apparecchio illuminante a sospensione. Rosone bianco opaco. Cavi di sospensione in inox AISI 304. Cavo bianco. SPY DE: versione a doppia emissione ed accensione. Cavo trasparente.*



SPY
 39W
 110-240V - 50/60Hz
 3000K - 4292lm
 CRI >80
 UGR <19
 Driver integrated
 DALI
 CE IP20

Matt White - 3000K - DALI

| 1A2910300.30.01 |



SPY DE
 Dual emission
 77W
 110-240V - 50/60Hz
 3000K - Down 4292lm - Up 4360lm
 CRI >80
 UGR <19
 Driver integrated
 DALI
 CE IP20

Matt White - 3000K - DALI

| 1A2940300.30.01 |

Optional accessories / Accessori opzionali

Suspension kits / Kit di sospensione




Sloped ceiling suspension kit / Kit di sospensione per soffitto inclinato		Not included
	Nickel plated - 1 Piece	1A0510000.00.00



Recessed suspension kit for 12,5 mm plasterboard / Kit di sospensione da incasso per cartongesso 12,5 mm		Not included
Matt White	For suspension cables - 1 Piece Plasterboard cut-out Ø 44 mm Minimum space for mounting 70 mm	1X0000300.03.00
Matt Black	For suspension cables - 1 Piece Plasterboard cut-out Ø 44 mm Minimum space for mounting 70 mm	1X0000400.03.00



Ceiling suspension kit / Kit di sospensione da soffitto		Not included
Matt White	For suspension cables - 1 Piece	1X0010300.03.00
Matt Black	For suspension cables - 1 Piece	1X0010400.03.00



Wall adapter plate / Piastra di adattamento da parete		Not included
Matt White	For mounting on brick masonry walls	1X0050300.01.00

WALL / PARETE



A tool to light.

A luminaire designed for use with state-of-the-art LED modules to offer superior performance and a wide range of light beams.

Luminaire available also in ENDLESS version.


Elemento di luce.

Un apparecchio progettato per utilizzare moduli a LED in grado di fornire prestazioni superiori ed un'ampia gamma di fasci luminosi. Apparecchio illuminante disponibile anche nella versione ENDLESS.

Wall-Ceiling / Direct / Indoor

Material Metal
Finish .03 Matt White .04 Matt Black


Note Wall luminaire. Adjustable in all directions. DOT P DE and DOT P DE 51: *Apparecchio illuminante da parete. Orientabile in tutte le direzioni.* dual emission versions. DOT P ENDLESS and DOT P ENDLESS CASAMBI: *DOT P DE e DOT P DE 51: versioni a doppia emissione. DOT P ENDLESS e DOT P ENDLESS CASAMBI: apparecchi illuminanti dedicati al sistema ENDLESS* (Max 48V DC - Max 150W - Max 4A). They can be used, on the same circuit, with the ENDLESS models. *(Max 48V DC - Max 150W - Max 4A) ed utilizzabili, sullo stesso circuito, con i modelli ENDLESS. Vedi pagina ENDLESS.*
 See page: ENDLESS.



DOT P
 13W
 100-240V - 50/60Hz
 2700K / 3000K
 CRI >97
 Driver integrated
 DALI
 CE IP20

Matt White - 2700K - DALI
 Matt White - 3000K - DALI
 Matt Black - 2700K - DALI
 Matt Black - 3000K - DALI


1A2340300.27.01
 1A2340300.30.01
 1A2340400.27.01
 1A2340400.30.01



DOT P
 13W
 100-240V - 50/60Hz
 2700K / 3000K
 CRI >97
 Driver integrated
 PUSH
 CE IP20

Matt White - 2700K - PUSH
 Matt White - 3000K - PUSH
 Matt Black - 2700K - PUSH
 Matt Black - 3000K - PUSH


1A2340300.27.04
 1A2340300.30.04
 1A2340400.27.04
 1A2340400.30.04



DOT P 51
 Max 10W - GU10
 100-240V - 50/60Hz
 ON/OFF
 Bulb not included
 CE IP20

Matt White - ON/OFF
 Matt Black - ON/OFF


1A2490300.00.00
 1A2490400.00.00



DOT P ENDLESS
 ENDLESS version only
 13W - 0,34A
 48V DC
 2700K / 3000K
 CRI >97
 Driver not included
 See page ENDLESS
 CE IP20 TE

Matt White - 2700K
 Matt White - 3000K
 Matt Black - 2700K
 Matt Black - 3000K


1A2340300.27.40
 1A2340300.30.40
 1A2340400.27.40
 1A2340400.30.40



DOT P ENDLESS CASAMBI
 ENDLESS version only
 15,5W - 0,4A
 48V DC
 2700K / 3000K
 CRI >97
 Driver not included
 See page ENDLESS
 CE IP20 TE A

Matt White - 2700K
 Matt White - 3000K
 Matt Black - 2700K
 Matt Black - 3000K

1A2340300.27.41
 1A2340300.30.41
 1A2340400.27.41
 1A2340400.30.41




DOT P DE

Dual emission
 29W
 220-240V - 50/60Hz
 2700K / 3000K
 CRI >97
 Driver integrated
 DALI
 CE IP20

Matt White - 2700K - DALI
 Matt White - 3000K - DALI
 Matt Black - 2700K - DALI
 Matt Black - 3000K - DALI

1A4900300.27.01
 1A4900300.30.01
 1A4900400.27.01
 1A4900400.30.01



DOT P DE 51

Dual emission
 Max 2x10W - GU10
 100-240V - 50/60Hz
 ON/OFF
 Bulb not included
 CE IP20

Matt White - ON/OFF
 Matt Black - ON/OFF

1A3810300.00.00
 1A3810400.00.00

Compulsory accessories / Accessori obbligatori


Other accessories / Altri accessori



Lens / Lente			Not included
Beam - 14°	2700K - CRI >97 - 983lm	DOT P	1A3090000.00.00
	3000K - CRI >97 - 1038lm		
	2700K - CRI >97 - 983lm	DOT P ENDLESS	
	3000K - CRI >97 - 1038lm		
	2700K - CRI >97 - 983lm	DOT P ENDLESS CASAMBI	
	3000K - CRI >97 - 1038lm		
Beam - 24°	2700K - CRI >97 - 1966lm	DOT P DE	1A3100000.00.00
	3000K - CRI >97 - 2076lm		
	2700K - CRI >97 - 943lm	DOT P	
	3000K - CRI >97 - 996lm		
	2700K - CRI >97 - 943lm	DOT P ENDLESS	
	3000K - CRI >97 - 996lm		
Beam - 36°	2700K - CRI >97 - 943lm	DOT P ENDLESS CASAMBI	1A3110000.00.00
	3000K - CRI >97 - 996lm		
	2700K - CRI >97 - 1886lm	DOT P DE	
	3000K - CRI >97 - 1992lm		
	2700K - CRI >97 - 955lm	DOT P	
	3000K - CRI >97 - 1005lm		
Beam - 50°	2700K - CRI >97 - 955lm	DOT P ENDLESS	1A3120000.00.00
	3000K - CRI >97 - 1005lm		
	2700K - CRI >97 - 955lm	DOT P ENDLESS CASAMBI	
	3000K - CRI >97 - 1005lm		
	2700K - CRI >97 - 1910lm	DOT P DE	
	3000K - CRI >97 - 2010lm		
Beam - 50°	2700K - CRI >97 - 965lm	DOT P	1A3120000.00.00
	3000K - CRI >97 - 1016lm		
	2700K - CRI >97 - 965lm	DOT P ENDLESS	
	3000K - CRI >97 - 1016lm		
	2700K - CRI >97 - 965lm	DOT P ENDLESS CASAMBI	
	3000K - CRI >97 - 1016lm		
Beam - 50°	2700K - CRI >97 - 1930lm	DOT P DE	
	3000K - CRI >97 - 2032lm		

Optional accessories / Accessori opzionali


Other accessories / Altri accessori




Accessory holder + Honeycomb louvre / Porta accessori + Frangiluce nido d'ape				Not included
		DOT P / DOT P ENDLESS / DOT P ENDLESS CASAMBI / DOT P DE	1X0080400.01.00	



Elliptical filter / Filtro ellittico				Not included
Standard	Compulsory with 1X0080400.01.00	DOT P / DOT P ENDLESS / DOT P ENDLESS CASAMBI / DOT P DE	1X0080000.02.00	



Blue filter / Filtro blu				Not included
Standard	Compulsory with 1X0080400.01.00	DOT P / DOT P ENDLESS / DOT P ENDLESS CASAMBI / DOT P DE	1X0080000.03.00	



Red filter / Filtro rosso				Not included
Standard	Compulsory with 1X0080400.01.00	DOT P / DOT P ENDLESS / DOT P ENDLESS CASAMBI / DOT P DE	1X0080000.04.00	



Yellow filter / Filtro giallo				Not included
Standard	Compulsory with 1X0080400.01.00	DOT P / DOT P ENDLESS / DOT P ENDLESS CASAMBI / DOT P DE	1X0080000.05.00	

Optional accessories / Accessori opzionali

Bulbs / Lampadine



LED - GU10 - PAR16			Not included
	220-240V - 5,5W - 25° 3000K - 375lm - CRI >97 Energy Efficiency G - Dimmable	DOT P 51 / DOT P DE 51	1Y0330500




LED SORAA - GU10 - MR16			Not included
	230V - 7,5W - 10° 2700K - 390lm - CRI >95 Energy Efficiency G - Dimmable	DOT P 51 / DOT P DE 51	1Y1580210




LED SORAA - GU10 - MR16			Not included
	230V - 7,5W - 10° 3000K - 410lm - CRI >95 Energy Efficiency G - Dimmable	DOT P 51 / DOT P DE 51	1Y1580010


Other accessories / Altri accessori



Darklight			Not included
	LED SORAA - GU10 - MR16	DOT P 51 / DOT P DE 51	1Y1580040



25° beam filter / Filtro fascio 25°			Not included
	LED SORAA - GU10 - MR16	DOT P 51 / DOT P DE 51	1Y1580020



36° beam filter / Filtro fascio 36°			Not included
	LED SORAA - GU10 - MR16	DOT P 51 / DOT P DE 51	1Y1580030



1

It is pure form.
A tool to light, simple container for the light source.
Light is incorporated into the space, becoming an architectural element.

È forma pura.
Elemento di luce semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

DUET

/ 2014


Wall / Diffuse / Indoor

Material Glass - Metal

Finish **.03** Matt White **.04** Matt Black

Note Wall luminaire. Dual emission.

Apparecchio illuminante da parete. Doppia emissione.



DUET

23W

220-240V - 50/60Hz

2700K - 1293lm / 3000K - 1352lm

CRI >90

TRIAC/IGBT

CE IP20

Matt White - 2700K - TRIAC/IGBT

Matt White - 3000K - TRIAC/IGBT

Matt Black - 2700K - TRIAC/IGBT

Matt Black - 3000K - TRIAC/IGBT

1A3300300.27.02

1A3300300.30.02

1A3300400.27.02

1A3300400.30.02

EDISON'S NIGHTMARE

Harry Thaler / 2014



A gestural project, full of irony and nostalgia.
Therefore, among a thousand stories, prohibitions, absurd technical rules,
we have reached the end. The end of the incandescent bulb.

Edison's Nightmare is a salute to Edison's light bulb*,
a dream that changed the way we live forever, stealing time to read and write from sleep.

It is a classic light bulb, nailed to the wall. Like a work of art.

** From 01 September 2012, incandescent bulbs cannot be sold in the EU.*

Un progetto gestuale, carico di ironia e nostalgia.
E così, tra mille vicende, divieti, assurde norme tecniche, siamo arrivati alla fine.

Alla fine della lampadina a incandescenza.

Edison's Nightmare è un saluto alla lampadina di Edison*,
ad un sogno che ha cambiato per sempre il modo di vivere,
sottraendo al sonno ore da dedicare a lettura e scrittura.

Si tratta di una classica lampadina inchiodata al muro.

Come un'opera d'arte.

** Dal 1 Settembre 2012 non è più possibile, nella Comunità Europea,
vendere lampadine ad incandescenza.*


EDISON'S NIGHTMARE

Harry Thaler / 2014

Wall / Diffuse / Indoor

Material Blown glass - Metal
Finish .00 Standard

Note Wall luminaire. Blown glass diffuser. Dimmer on the cable. Transparent cable. *Apparecchio illuminante da parete. Diffusore in vetro soffiato. Dimmer lungo il cavo. Cavo trasparente.*



EDISON'S NIGHTMARE

Max 10W - G4 - 12V
100-240V - 50/60Hz
Driver integrated
Dimmer on board
Bulb included
CE IP20

Standard - Dimmer on board

| 1A3380000.00.06 |





A luminous short film.

Telling a story in light, a series of old 35MM slides are lit from behind, pulsating and shown at random.

The photographs can be assembled and replaced as you like.

The choice of the message to be communicated is completely personal: it can be an image, a logo, a sentence, anything you want to represent, at any time.

The light message is punctuated by a blinking LED, offering reading in movement.

Un cortometraggio luminoso.

Per raccontare una storia con la luce, retroilluminando in modo pulsante e casuale le vecchie diapositive da 35MM.

Le fotografie possono essere montate e sostituite a piacimento.

La scelta del messaggio da comunicare è del tutto personale: può essere un'immagine, un logo, una frase, tutto ciò che al momento si vuole rappresentare.

Il messaggio luminoso, ritmato attraverso la diversa intermittenza dei LED, permette una lettura in movimento.


FILM

Alessandra Dallagiovanna - Davide Groppi / 2010

Objects-Wall / Diffuse / Indoor

Material Metal - Polycarbonate
Finish .00 Standard

Note Modular wall luminaire. Matt black support. Customised images not included. Module connector included. Black cable. *Apparecchio illuminante da parete componibile. Supporto nero opaco. Immagini personalizzabili non incluse. Connettore moduli incluso. Cavo nero.*




FILM
 3W
 5V DC
 Driver not included
 ON/OFF
 CE IP20

Standard - ON/OFF


| 1A3410000.00.00 |

Compulsory accessories / Accessori obbligatori

Drivers / Alimentatori



Driver with plug / Alimentatore con spina		Not included
Matt Black	Input 110-240V - 50/60Hz Output 5V DC - 15W - IP40	1Z1470180



Driver / Alimentatore		Not included
100-240V	5V/17,5W/IP20/ON/OFF	1Z1120180





FOIL

967 DESIGN / 2011

An architectural lamp for wall and ceiling installation.
Although it's there, you can't see the thickness.
A luminaire that amazes with skill, so you only notice its two-dimensional effect.

Lampada architettuale, da installare sia a parete che a soffitto.
Lo spessore c'è, ma non si vede.
Apparecchio efficace e stupendo nel momento
in cui si coglie solo l'aspetto bidimensionale.


FOIL

967 DESIGN / 2011

Wall / Indirect / Indoor

Material Metal
Finish .03 Matt White .04 Matt Black

Note Wall luminaire. *Apparecchio illuminante da parete.*




FOIL

24,5W
220-230V - 50/60Hz
2700K - 1681lm / 3000K - 1808lm
CRI >90
TRIAC/IGBT
CE IP20

Matt White - 2700K - TRIAC/IGBT
Matt White - 3000K - TRIAC/IGBT
Matt Black - 2700K - TRIAC/IGBT
Matt Black - 3000K - TRIAC/IGBT

1A3150300.27.02
1A3150300.30.02
1A3150400.27.02
1A3150400.30.02



An indirect wall light project.
The light source remains invisible while the light comes out soft from the metal diffuser,
creating a delicate atmosphere.

Un lavoro sulla luce indiretta da parete.
La sorgente rimane invisibile mentre la luce esce morbida dal diffusore metallico,
creando un'atmosfera delicata.

FOLDER


967 DESIGN / 2013

Wall / Indirect / Indoor

Material Metal
Finish .03 Matt White

Note Wall luminaire.

Apparecchio illuminante da parete.



FOLDER

20W

110-240V - 50/60Hz

2700K - 397lm / 3000K - 415lm

CRI >80

Driver integrated

DALI

CE IP20

Matt White - 2700K - DALI

1A3350300.27.01

Matt White - 3000K - DALI

1A3350300.30.01





A tool to light.

The luminaire is pure form, a simple container for the light source.
Single-emission lamp with light directed downwards.
Light is incorporated into the space, becoming an architectural element.

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
Lampada monoemissione con luce direzionata verso il basso.
La luce si integra con lo spazio diventando elemento architettonico.


LINET

Omar Carraglia / 2014

Wall / Diffuse / Indoor

Material Metal - Methacrylate
Finish .03 Matt White .04 Matt Black

Note Wall luminaire. *Apparecchio illuminante da parete.*



LINET

11,5W
220-240V - 50/60Hz
2700K - 626lm / 3000K - 655lm
CRI >90
TRIAC/IGBT
CE IP20

Matt White - 2700K - TRIAC/IGBT
Matt White - 3000K - TRIAC/IGBT
Matt Black - 2700K - TRIAC/IGBT
Matt Black - 3000K - TRIAC/IGBT

1A3310300.27.02
1A3310300.30.02
1A3310400.27.02
1A3310400.30.02

MIRA

Omar Carraglia / 2012



Lamp with a simple and essential shape.
For interiors and adjustable.
Luminaire available also in ENDLESS version.


Lampada dalla forma semplice ed essenziale.
Per interni e orientabile.
Apparecchio illuminante disponibile anche nella versione ENDLESS.

Wall-Ceiling / Direct / Indoor

Material Metal
Finish .03 Matt White .04 Matt Black

Note Wall luminaire. Adjustable in all directions. MIRA ENDLESS and MIRA ENDLESS CASAMBI: luminaires dedicated to ENDLESS system (Max 48V DC - Max 150W - Max 4A). They can be used, on the same circuit, with the ENDLESS models. See page: ENDLESS.


Apparecchio illuminante da parete. Orientabile in tutte le direzioni. MIRA ENDLESS e MIRA ENDLESS CASAMBI: apparecchi illuminanti dedicati al sistema ENDLESS (Max 48V DC - Max 150W - Max 4A) ed utilizzabili, sullo stesso circuito, con i modelli ENDLESS. Vedi pagina ENDLESS.



MIRA
 8W
 110-240V - 50/60Hz
 2700K - 327lm / 3000K - 352lm
 CRI >90
 Driver integrated
 PUSH
 CE IP20

Matt White - 2700K - PUSH
 Matt White - 3000K - PUSH
 Matt Black - 2700K - PUSH
 Matt Black - 3000K - PUSH


1A2280300.27.04
 1A2280300.30.04
 1A2280400.27.04
 1A2280400.30.04



MIRA SWITCH
 8W
 110-240V - 50/60Hz
 2700K - 327lm / 3000K - 352lm
 CRI >90
 Driver integrated
 ON/OFF
 CE IP20

Matt White - 2700K - ON/OFF
 Matt White - 3000K - ON/OFF
 Matt Black - 2700K - ON/OFF
 Matt Black - 3000K - ON/OFF


1A2280300.27.00
 1A2280300.30.00
 1A2280400.27.00
 1A2280400.30.00



MIRA
 8W
 110-240V - 50/60Hz
 2700K - 327lm / 3000K - 352lm
 CRI >90
 Driver integrated
 DALI
 CE IP20

Matt White - 2700K - DALI
 Matt White - 3000K - DALI
 Matt Black - 2700K - DALI
 Matt Black - 3000K - DALI


1A2280300.27.01
 1A2280300.30.01
 1A2280400.27.01
 1A2280400.30.01



MIRA ENDLESS
 ENDLESS version only
 6W - 0,16A
 48V DC
 2700K - 327lm / 3000K - 352lm
 CRI >90
 Driver not included
 See page ENDLESS
 CE IP20 E

Matt White - 2700K
 Matt White - 3000K
 Matt Black - 2700K
 Matt Black - 3000K

1A2280300.27.40
 1A2280300.30.40
 1A2280400.27.40
 1A2280400.30.40



MIRA ENDLESS CASAMBI
 ENDLESS version only
 8,5W - 0,22A
 48V DC
 2700K - 327lm / 3000K - 352lm
 CRI >90
 Driver not included
 See page ENDLESS
 CE IP20 E A

Matt White - 2700K
 Matt White - 3000K
 Matt Black - 2700K
 Matt Black - 3000K

1A2280300.27.41
 1A2280300.30.41
 1A2280400.27.41
 1A2280400.30.41



MIRA MAGNETIC

Omar Carraglia / 2015

Lamp with a simple and essential shape.
For interiors and adjustable, it is designed with a magnetic application system
to be even more versatile and functional.

Lampada dalla forma semplice ed essenziale.
Per interni e orientabile, è concepita con un sistema di applicazione magnetico
per essere ancora più versatile e funzionale.


MIRA MAGNETIC

Omar Carraglia / 2015

Wall-Ceiling / Direct / Indoor

Material Metal
Finish .03 Matt White .04 Matt Black

Note Wall luminaire. Adjustable in all directions. Magnetic fixing. Dimmer on the cable. White cable. *Apparecchio illuminante da parete. Orientabile in tutte le direzioni. Fissaggio magnetico. Dimmer lungo il cavo. Cavo bianco.*



MIRA MAGNETIC

5,6W
 Max 500mA DC
 2700K - 327lm / 3000K - 352lm
 CRI >90
 Driver not included


CE IP20

Matt White - 2700K
 Matt White - 3000K
 Matt Black - 2700K
 Matt Black - 3000K


1A3680300.27.20
 1A3680300.30.20
 1A3680400.27.20
 1A3680400.30.20

Compulsory accessories / Accessori obbligatori

Drivers / Alimentatori



Driver with plug / Alimentatore con spina		Not included
Matt White	Input 110-240V - 50/60Hz Output 350mA - 15W - IP20 Dimmer on board	1A3180300.00.06
Matt Black	Input 110-240V - 50/60Hz Output 350mA - 15W - IP20 Dimmer on board	1A3180400.00.06



Driver / Alimentatore		Not included
220-240V(100-127V)	500mA/20W(15W)/IP20/PUSH - 1-10V	1Z0240870.500



MORSETTO P

Daide Groppi / 2019



A lamp that can be positioned, balanced and turned,
but overall it produces a beautiful light on the table.
It's the wall version of the Morsetto lamp.
Three adjustable arms allow the light source to be positioned
far from where the lamp is attached.
Table version also available.

Una lampada che si inclina, si bilancia, si gira,
ma soprattutto che produce una bellissima luce sul tavolo.
È la versione da parete della lampada Morsetto.
Tre bracci regolabili permettono di portare la fonte luminosa
lontana dal punto di fissaggio.
Disponibile anche nella versione da tavolo.


MORSETTO P

Davide Groppi / 2019

Wall / Direct / Indoor

Material Metal
Finish .04 Matt Black

Note Wall luminaire. Adjustable in all directions. Dimmer on the cable. Black *Apparecchio illuminante da parete. Orientabile in tutte le direzioni. Dimmer lungo il cavo. Cavo nero.*



MORSETTO P

13W
24V DC
2700K - 765lm / 3000K - 823lm
CRI >90
UGR <19
Dimmer on board
Driver with plug included




Matt Black - 2700K - Dimmer on board
Matt Black - 3000K - Dimmer on board

1A2570400.27.06
1A2570400.30.06

Optional accessories / Accessori opzionali

Drivers / Alimentatori




Driver with plug / Alimentatore con spina

Matt Black Input 110-240V - 50/60Hz
 Output 24V DC - 18W - IP20

1Z0431020

Included





PIÙ

Davide Groppi / 2007

A tool to light.

Pure form, a simple container for the light source.

Light is incorporated into the space, becoming an architectural element.

Elemento di luce.

Forma pura, semplice contenitore della fonte luminosa.

La luce si integra con lo spazio diventando elemento architettonico.

PIÙ


Davide Groppi / 2007

Wall / Indirect / Indoor

Material Metal
Finish .03 Matt White

Note Wall luminaire. Dual emission.

Apparecchio illuminante da parete. Doppia emissione.



PIÙ

Max 120W - R7s
100-240V - 50/60Hz
ON/OFF
Bulb not included
CE IP20

Matt White - ON/OFF

| 1A3370300.00.00 |

Optional accessories / Accessori opzionali

Bulbs / Lampadine





LED - R7s COB - 118 mm

Not included

220-240V - 8W - 330°
3000K - 1000lm - CRI >80
Energy Efficiency E

1Y0000139





A ready-made project to design the space with a sense of irony and weightlessness.
The tracks of an electric train can be used to draw a heart, but also to conduct electricity.
Rail is the boundary between usefulness and show, between art and design.

Un ready-made per firmare lo spazio con ironia e leggerezza.
I binari di un trenino elettrico sono lo strumento per disegnare un cuore,
ma anche per condurre la corrente elettrica.
Rail è sul confine tra utilità e rappresentazione, design e arte.


RAIL

Davide Groppi / 2019

Wall / Direct / Indoor

Material ABS - Metal
Finish .00 Standard

Note Wall luminaire. Matt black modular tracks. Dimmer on the cable. Black cable. *Apparecchio illuminante da parete. Binari componibili nero opaco. Dimmer lungo il cavo. Cavo nero.*




RAIL

22W
24V DC
3000K - 2000lm
CRI >90
Driver included
Dimmer on board
CE IP20

Standard - 3000K - Dimmer on board

1A3400000.30.06





REFLEX

Michele Groppi / 2022

A powerful LED and a subtle mirror.
A magic and almost invisible lighting solution,
which provides an indirect light that multiplies spaces
and gives the eye unprecedented perspectives,
unexpected depths, illusions of light.

Suspension version also available.

Luminaire designed also to be powered by ENDLESS system.

Un LED potente, uno specchio sottile.

Un apparecchio magico e quasi invisibile per una luce
che moltiplica gli spazi e regala allo sguardo prospettive inedite,
profondità impreviste, illusioni di luce.

Disponibile anche nella versione a sospensione.

Apparecchio illuminante alimentabile anche con il sistema ENDLESS.


REFLEX

Michele Groppi / 2022

Wall / Indirect / Indoor

Material Metal - Mirror
Finish .04 Matt Black

Note Wall luminaire. Plane with mirror finish. Matt black rear plane. *Apparecchio illuminante da parete. Piano con finitura a specchio. Retro del piano nero opaco. Alimentabile anche con il sistema ENDLESS (Max 48V DC - Max 150W - Max 4A) ed utilizzabile, sullo stesso circuito, con i modelli ENDLESS. Vedi pagina ENDLESS.*
 Possibility for the luminaire to be powered by ENDLESS system (Max 48V DC - Max 150W - Max 4A) and to be used, on the same circuit, with the ENDLESS models. See page: ENDLESS.



REFLEX

23W - 0,57A
 48V DC
 2700K - 2158lm / 3000K - 2320lm
 CRI >90
 Driver not included




Matt Black - 2700K
 Matt Black - 3000K


1A0850400.27.20
 1A0850400.30.20

Compulsory accessories / Accessori obbligatori

Drivers / Alimentatori



Driver / Alimentatore		Not included
100-240V	48V/60W/IP67/ON/OFF	1Z1120640



Driver / Alimentatore		Not included
220-240V	48V/60W/IP20/DALI	1Z0830820



SHADE

Federico Delrosso / 2013



Reflections of light.

The pure and essential form of a thin mirror wich provides indirect light.

Riflessioni di luce.

La forma pura ed essenziale di uno specchio sottile a luce indiretta.

SHADE


Federico Delrosso / 2013

Wall / Indirect / Indoor

Material Metal - Mirror
Finish .00 Standard

Note Wall luminaire. Plane with mirror finish. Dual emission.

*Apparecchio illuminante da parete. Piano con finitura a specchio.
Doppia emissione.*



SHADE

23W

220-240V - 50/60Hz

2700K - 1293lm / 3000K - 1352lm

CRI >90

Driver integrated


TRIAC/IGBT

CE IP20

Standard - 2700K - TRIAC/IGBT
Standard - 3000K - TRIAC/IGBT

1A3360000.27.02
1A3360000.30.02





SOL 1

Omar Carraglia - Davide Groppi / 2003

A tool to light.

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.


SOL 1

Omar Carraglia - Davide Groppi / 2003

Wall / Indirect / Indoor

Material Metal
Finish .03 Matt White .04 Matt Black

Note Wall luminaire. *Apparecchio illuminante da parete.*



SOL 1

12,5W
220-230V - 50/60Hz
2700K - 836lm / 3000K - 899lm
CRI >90
TRIAC/IGBT
CE IP20

Matt White - 2700K - TRIAC/IGBT
Matt White - 3000K - TRIAC/IGBT
Matt Black - 2700K - TRIAC/IGBT
Matt Black - 3000K - TRIAC/IGBT

1A3130300.27.02
1A3130300.30.02
1A3130400.27.02
1A3130400.30.02





A tool to light.

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.


SOL 2

/ 2008

Wall / Indirect / Indoor

Material Metal
Finish .03 Matt White .04 Matt Black

Note Wall luminaire. *Apparecchio illuminante da parete.*



SOL 2

24,5W
220-230V - 50/60Hz
2700K - 1681lm / 3000K - 1808lm
CRI >90
TRIAC/IGBT
CE IP20

Matt White - 2700K - TRIAC/IGBT
Matt White - 3000K - TRIAC/IGBT
Matt Black - 2700K - TRIAC/IGBT
Matt Black - 3000K - TRIAC/IGBT

1A3140300.27.02
1A3140300.30.02
1A3140400.27.02
1A3140400.30.02





A luminaire designed for use with state-of-the-art LED modules to offer superior performance and a wide range of light beams.
Luminaire available also in ENDLESS version.


Un apparecchio illuminante progettato per utilizzare moduli a LED in grado di fornire prestazioni superiori ed un'ampia gamma di fasci luminosi.
Apparecchio illuminante disponibile anche nella versione ENDLESS.

Wall-Ceiling / Direct / Indoor

Material Metal
Finish .03 Matt White .04 Matt Black

Note Wall luminaire. Adjustable in all directions. SPOT ENDLESS and SPOT ENDLESS CASAMBI: luminaires dedicated to ENDLESS system (Max 48VDC - Max 150W - Max 4A). They can be used, on the same circuit, with the ENDLESS models. See page: ENDLESS.

Apparecchio illuminante da parete. Orientabile in tutte le direzioni. SPOT ENDLESS e SPOT ENDLESS CASAMBI: apparecchi illuminanti dedicati al sistema ENDLESS (Max 48V DC - Max 150W - Max 4A) ed utilizzabili, sullo stesso circuito, con i modelli ENDLESS. Vedi pagina ENDLESS.




SPOT

Max 21W
 220-240V - 50/60Hz
 CRI >90
 Driver integrated
 DALI
 LED module not included
 CE IP20

Matt White - DALI
 Matt Black - DALI

1A1080300.00.01
 1A1080400.00.01




SPOT

Max 21W
 220-240V - 50/60Hz
 CRI >90
 Driver integrated
 PUSH
 LED module not included
 CE IP20

Matt White - PUSH
 Matt Black - PUSH

1A1080300.00.04
 1A1080400.00.04




SPOT ENDLESS

ENDLESS version only
 Max 13W - 0,34A
 48V DC
 CRI >90
 Driver not included
 See page ENDLESS
 LED module not included
 CE IP20 E

Matt White
 Matt Black

1A1080300.00.40
 1A1080400.00.40



SPOT ENDLESS CASAMBI


ENDLESS version only
 Max 15,5W - 0,4A
 48V DC
 CRI >90
 Driver not included
 See page ENDLESS
 LED module not included
 CE IP20 E A

Matt White
 Matt Black


1A1080300.00.41
 1A1080400.00.41

Compulsory accessories / Accessori obbligatori


LED modules / Moduli LED




DG111 LED module / Modulo LED DG111 Not included			
16,7W - 15° - 500mA DC	SPOT	1A4700000.27.20	
2700K - 1648lm - CRI >90			
Energy Efficiency F - Dimmable			
16,7W - 15° - 500mA DC		1A4700000.30.20	
3000K - 1682lm - CRI >90			
Energy Efficiency F - Dimmable			




DG111 LED module / Modulo LED DG111 Not included			
16,7W - 22° - 500mA DC	SPOT	1A3890000.27.20	
2700K - 1859lm - CRI >90			
Energy Efficiency F - Dimmable			
16,7W - 22° - 500mA DC		1A3890000.30.20	
3000K - 1945lm - CRI >90			
Energy Efficiency F - Dimmable			




DG111 LED module / Modulo LED DG111 Not included			
16,7W - 36° - 500mA DC	SPOT	1A3900000.27.20	
2700K - 1808lm - CRI >90			
Energy Efficiency F - Dimmable			
16,7W - 36° - 500mA DC		1A3900000.30.20	
3000K - 1890lm - CRI >90			
Energy Efficiency F - Dimmable			



DG111 LED module / Modulo LED DG111 Not included			
11,7W - 15° - 350mA DC	SPOT ENDLESS /	1A4700000.27.20	
2700K - 1336lm - CRI >90	SPOT ENDLESS CASAMBI		
Energy Efficiency F - Dimmable			
11,7W - 15° - 350mA DC		1A4700000.30.20	
3000K - 1364lm - CRI >90			
Energy Efficiency F - Dimmable			



DG111 LED module / Modulo LED DG111 Not included			
11,7W - 22° - 350mA DC	SPOT ENDLESS /	1A3890000.27.20	
2700K - 1266lm - CRI >90	SPOT ENDLESS CASAMBI		
Energy Efficiency F - Dimmable			
11,7W - 22° - 350mA DC		1A3890000.30.20	
3000K - 1323lm - CRI >90			
Energy Efficiency F - Dimmable			




DG111 LED module / Modulo LED DG111 Not included			
11,7W - 36° - 350mA DC	SPOT ENDLESS /	1A3900000.27.20	
2700K - 1508lm - CRI >90	SPOT ENDLESS CASAMBI		
Energy Efficiency F - Dimmable			
11,7W - 36° - 350mA DC		1A3900000.30.20	
3000K - 1578lm - CRI >90			
Energy Efficiency F - Dimmable			

Optional accessories / Accessori opzionali


Other accessories / Altri accessori




Accessory holder + Soft filter + Honeycomb louvre / Porta accessori + Filtro soft + Frangiluce nido d'ape Not included		
Matt Black		1X0070400.04.00




Accessory holder + Elliptical filter / Porta accessori + Filtro ellittico Not included		
Matt Black		1X0070400.05.00




Blue filter / Filtro blu Not included		
Standard	Compulsory with	1X0070000.06.00
	1X0070400.04.00 / 1X0070400.05.00	




Red filter / Filtro rosso Not included		
Standard	Compulsory with	1X0070000.07.00
	1X0070400.04.00 / 1X0070400.05.00	




Yellow filter / Filtro giallo Not included		
Standard	Compulsory with	1X0070000.08.00
	1X0070400.04.00 / 1X0070400.05.00	



Horizontal directional fins / Alette direzionali Not included		
Matt Black		1X0070400.01.00



Cylindrical screen / Schermo cilindrico Not included		
Matt Black		1X0070400.02.00



Cone 45° / Cono 45° Not included		
Matt Black		1X0070400.03.00





TOAST

Daide Groppi - Alberto Zattin / 2001

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.


Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

TOAST

Davide Groppi - Alberto Zattin / 2001

Wall / Diffuse / Indoor

Material	Glass - Metal			
Finish	.01 Polished Chrome	.03 Matt White	.04 Matt Black	.08 Brushed Brass
	.14 Brushed Chrome			
Note	Wall luminaire. Dual emission.		<i>Apparecchio illuminante da parete. Doppia emissione.</i>	




TOAST

Max 100W - R7s
100-240V - 50/60Hz
ON/OFF
Bulb not included
CE IP20 \varnothing 0,5 m

Polished Chrome - ON/OFF
Matt White - ON/OFF
Matt Black - ON/OFF
Brushed Brass - ON/OFF
Brushed Chrome - ON/OFF

1A3290100.00.00
1A3290300.00.00
1A3290400.00.00
1A3290800.00.00
1A3291400.00.00



TOAST LED

12W
100-240V - 50/60Hz
2700K - 743lm / 3000K - 743lm
CRI >90
Driver integrated
ON/OFF
CE IP20

Polished Chrome - 2700K - ON/OFF
Polished Chrome - 3000K - ON/OFF
Matt White - 2700K - ON/OFF
Matt White - 3000K - ON/OFF
Matt Black - 2700K - ON/OFF
Matt Black - 3000K - ON/OFF
Brushed Brass - 2700K - ON/OFF
Brushed Brass - 3000K - ON/OFF
Brushed Chrome - 2700K - ON/OFF
Brushed Chrome - 3000K - ON/OFF

1A3280100.27.00
1A3280100.30.00
1A3280300.27.00
1A3280300.30.00
1A3280400.27.00
1A3280400.30.00
1A3280800.27.00
1A3280800.30.00
1A3281400.27.00
1A3281400.30.00

Optional accessories / Accessori opzionali

Bulbs / Lampadine



LED - R7s COB - 78 mm

220-240V - 4W - 330°
3000K - 450lm - CRI >80
Energy Efficiency E

1Y0000138

Not included



CEILING / SOFFITTO




Abstraction, purity, graphic sign.
The projected reduction of Infinito.
The disc appears enigmatic, the symbolic presence of the absence of light.

Astrazione, purezza, segno grafico.
La riduzione puntuale di Infinito.
Il disco appare enigmatico, presenza simbolica dell'assenza della luce.

Ceiling / Indirect / Indoor

Material Metal - Methacrylate
Finish .27 Gravity Black

Note Ceiling luminaire. Disc with gravity black finish. Magnetic weight available for disc tilting. Black cable. *Apparecchio illuminante da soffitto. Disco con finitura gravity black. Disponibile un peso magnetico per l'orientamento inclinato del disco. Cavo nero.*



ASINTOTO


18W
 Max 500mA DC
 2700K - 1435lm / 3000K - 1478lm
 CRI >90
 Driver not included
 CE IP20

Gravity Black - 2700K
 Gravity Black - 3000K


1A4072700.27.20
 1A4072700.30.20

Compulsory accessories / Accessori obbligatori


Drivers / Alimentatori



Driver / Alimentatore			Not included
220-240V(100-127V)	500mA/20W(15W)/IP20/DALI	1Z0241180.500	




Driver / Alimentatore			Not included
220-240V(100-127V)	500mA/20W(15W)/IP20/PUSH - 1-10V	1Z0240870.500	



Driver / Alimentatore			Not included
220-240V	500mA/20W/IP20/TRIAC/IGBT	1Z0240850.500	

Optional accessories / Accessori opzionali

Installation kits / Kit d'installazione



Circular plasterboard panel 12,5 mm / Botola circolare per cartongesso 12,5 mm			Not included
Standard	Cut-out 400x400 mm Minimum space for mounting Ø 115 mm	1A4520000.00.00	

Suspension kits / Kit di sospensione



Recessed suspension kit for 12,5 mm plasterboard / Kit di sospensione da incasso per cartongesso 12,5 mm			Not included
Matt White	For electrical cables - 1 Piece Plasterboard cut-out Ø 44 mm Minimum space for mounting 70 mm	1X0000300.04.00	
Matt Black	For electrical cables - 1 Piece Plasterboard cut-out Ø 44 mm Minimum space for mounting 70 mm	1X0000400.04.00	



Ceiling suspension kit / Kit di sospensione da soffitto			Not included
Matt White	For electrical cables - 1 Piece	1X0010300.04.00	
Matt Black	For electrical cables - 1 Piece	1X0010400.04.00	






Wall adapter plate / Piastra di adattamento da parete			Not included
Matt White	For mounting on brick masonry walls	1X0050300.01.00	

Other accessories / Altri accessori



Magnetic weight / Peso magnetico			Not included
Matt Black	For sloped installation	1A4710400.00.00	





A white disc, the perfect representation of diffused light.
It can be mounted on the wall or ceiling, with modular brightness.

Un disco bianco, rappresentazione perfetta della luce diffusa.
È applicabile a soffitto o a parete ed è modulabile in tutte le intensità.

AURORA

Davide Groppi / 2023

Ceiling-Wall / Diffuse / Indoor

Material Metal - PMMA


Finish .03 Matt White

.04 Matt Black

.32 Copper Oxide

Note Wall and ceiling luminaire. Matt white diffuser.

Apparecchio illuminante da parete e soffitto. Diffusore bianco opaco.



AURORA

28W

110-240V - 50/60Hz

3000K - 2700lm

CRI >80

Driver integrated

DALI - PUSH - 1-10V

CE IP20

Matt White - 3000K - DALI - PUSH - 1-10V

1A4010300.30.07

Matt Black - 3000K - DALI - PUSH - 1-10V

1A4010400.30.07

Copper Oxide - 3000K - DALI - PUSH - 1-10V

1A4013200.30.07

DOT PL 51

Omar Carraglia - Davide Groppi / 2015



A tool to light.

A luminaire designed for use with state-of-the-art LED bulbs
to offer superior performance and a wide range of light beams.

Elemento di luce.

Un apparecchio illuminante progettato per utilizzare lampadine a LED
in grado di fornire prestazioni superiori ed un'ampia gamma di fasci luminosi.

DOT PL 51

Omar Carraglia - Davide Groppi / 2015

Ceiling / Direct / Indoor

Material Metal
Finish .03 Matt White

Note Ceiling luminaire.

Apparecchio illuminante da soffitto.



DOT PL 51

Max 10W - GU10
 100-240V - 50/60Hz
 ON/OFF
 Bulb not included
 CE IP20

Matt White - ON/OFF

1A3800300.00.00

DOT PL 51

Omar Carraglia - Davide Groppi / 2015

Optional accessories / Accessori opzionali

Bulbs / Lampadine



LED - GU10 - PAR16

220-240V - 5,5W - 25°
 3000K - 375lm - CRI >97
 Energy Efficiency G - Dimmable

1Y0330500

Not included



LED SORAA - GU10 - MR16

230V - 7,5W - 10°
 2700K - 390lm - CRI >95
 Energy Efficiency G - Dimmable

1Y1580210

Not included




LED SORAA - GU10 - MR16

230V - 7,5W - 10°
 3000K - 410lm - CRI >95
 Energy Efficiency G - Dimmable

1Y1580010

Not included

Other accessories / Altri accessori




Darklight

LED SORAA - GU10 - MR16

1Y1580040

Not included




25° beam filter / Filtro fascio 25°

LED SORAA - GU10 - MR16

1Y1580020

Not included



36° beam filter / Filtro fascio 36°

LED SORAA - GU10 - MR16

1Y1580030

Not included

HAKO PL

Alberto Zattin / 2000



A tool to light.

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

HAKO PL


Alberto Zattin / 2000

Ceiling / Diffuse / Indoor

Material Glass - Metal - Methacrylate
Finish .03 Matt White

Note Ceiling luminaire. Sanded glass diffuser.

Apparecchio illuminante da soffitto. Diffusore in vetro sabbato.




HAKO PL

Max 60W - R7s
 100-240V - 50/60Hz
 ON/OFF
 Bulb not included
 C E IP20 \varnothing 0,5 m

Matt White - ON/OFF

| 1A3460300.00.00 |



HAKO PL LED

12,5W
 220-230V - 50/60Hz
 2700K - 593lm / 3000K - 638lm
 CRI >90
 TRIAC/IGBT
 C E IP20

Matt White - 2700K - TRIAC/IGBT
 Matt White - 3000K - TRIAC/IGBT

| 1A3160300.27.02 |
 | 1A3160300.30.02 |

Optional accessories / Accessori opzionali

Bulbs / Lampadine




LED - R7s COB - 78 mm

Not included

220-240V - 4W - 330°
 3000K - 450lm - CRI >80
 Energy Efficiency E

1Y0000138






**The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.**

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

Ceiling / Direct / Indoor

Material Metal
Finish .03 Matt White .34 Matt White/Black Bicolor

Note Ceiling luminaire. Adjustable in all directions. *Apparecchio illuminante da soffitto. Orientabile in tutte le direzioni.*



MINI PL 51

Max 10W - GU10
 100-240V - 50/60Hz
 ON/OFF
 Bulb not included
 CE IP20

Matt White - ON/OFF
 Matt White/Black Bicolor - ON/OFF

1A3450300.00.00
 1A3453400.00.00

Optional accessories / Accessori opzionali

Bulbs / Lampadine



LED - GU10 - PAR16	Not included
220-240V - 5,5W - 25° 3000K - 375lm - CRI >97 Energy Efficiency G - Dimmable	1Y0330500




LED SORAA - GU10 - MR16	Not included
230V - 7,5W - 10° 2700K - 390lm - CRI >95 Energy Efficiency G - Dimmable	1Y1580210




LED SORAA - GU10 - MR16	Not included
230V - 7,5W - 10° 3000K - 410lm - CRI >95 Energy Efficiency G - Dimmable	1Y1580010


Other accessories / Altri accessori



Darklight	Not included
LED SORAA - GU10 - MR16	1Y1580040



25° beam filter / Filtro fascio 25°	Not included
LED SORAA - GU10 - MR16	1Y1580020



36° beam filter / Filtro fascio 36°	Not included
LED SORAA - GU10 - MR16	1Y1580030

NULLA PL

Daide Groppi / 2014



The marvellous Nulla project, also available in a surface mounted version.

Il meraviglioso progetto Nulla utilizzabile anche in versione non incassata.

NULLA PL


Davide Groppi / 2014

Ceiling / Direct / Indoor

Material Metal
Finish .03 Matt White

Note Ceiling luminaire. Visible 18 mm diameter hole.

Apparecchio illuminante da soffitto. Foro visibile con diametro da 18 mm.



NULLA PL

8,5W
100-240V - 50/60Hz
2700K - 460lm / 3000K - 495lm
CRI >90
Driver integrated
ON/OFF
CE IP20

Matt White - 2700K - ON/OFF
Matt White - 3000K - ON/OFF

1A2500300.27.00
1A2500300.30.00





A tool to light.

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.


Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

Ceiling / Direct / Indoor

Material Metal
Finish .03 Matt White .34 Matt White/Black Bicolor

Note Ceiling luminaire. Adjustable in all directions. *Apparecchio illuminante da soffitto. Orientabile in tutte le direzioni.*



PUNTO PL


Max 21W
 100-240V - 50/60Hz
 CRI >90
 Driver integrated
 PUSH
 LED module not included
 CE IP20

Matt White - PUSH
 Matt White/Black Bicolor - PUSH


1A1110300.00.04
 1A1113400.00.04

Compulsory accessories / Accessori obbligatori


LED modules / Moduli LED



DG111 LED module / Modulo LED DG111		Not included
16,7W - 15° - 500mA DC		1A4700000.27.20
2700K - 1648lm - CRI >90		
Energy Efficiency F - Dimmable		
16,7W - 15° - 500mA DC		1A4700000.30.20
3000K - 1682lm - CRI >90		
Energy Efficiency F - Dimmable		




DG111 LED module / Modulo LED DG111		Not included
16,7W - 22° - 500mA DC		1A3890000.27.20
2700K - 1859lm - CRI >90		
Energy Efficiency F - Dimmable		
16,7W - 22° - 500mA DC		1A3890000.30.20
3000K - 1945lm - CRI >90		
Energy Efficiency F - Dimmable		




DG111 LED module / Modulo LED DG111		Not included
16,7W - 36° - 500mA DC		1A3900000.27.20
2700K - 1808lm - CRI >90		
Energy Efficiency F - Dimmable		
16,7W - 36° - 500mA DC		1A3900000.30.20
3000K - 1890lm - CRI >90		
Energy Efficiency F - Dimmable		

Optional accessories / Accessori opzionali


Other accessories / Altri accessori




Accessory holder + Soft filter + Honeycomb louvre / Porta accessori + Filtro soft + Frangiluce nido d'ape		Not included
Matt Black		1X0070400.04.00




Accessory holder + Elliptical filter / Porta accessori + Filtro ellittico		Not included
Matt Black		1X0070400.05.00



Blue filter / Filtro blu		Not included
Standard	Compulsory with 1X0070400.04.00 / 1X0070400.05.00	1X0070000.06.00



Red filter / Filtro rosso		Not included
Standard	Compulsory with 1X0070400.04.00 / 1X0070400.05.00	1X0070000.07.00



Yellow filter / Filtro giallo		Not included
Standard	Compulsory with 1X0070400.04.00 / 1X0070400.05.00	1X0070000.08.00



A tool to light.

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.


Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

Ceiling / Direct / Indoor

Material Metal
Finish .03 Matt White .34 Matt White/Black Bicolor

Note Ceiling luminaire. Adjustable in all directions. *Apparecchio illuminante da soffitto. Orientabile in tutte le direzioni.*




PUNTO 2 PL
 Max 2x21W
 100-240V - 50/60Hz
 CRI >90
 Driver integrated
 PUSH
 LED modules not included
 CE IP20


Matt White - PUSH 1A1120300.00.04
 Matt White/Black Bicolor - PUSH 1A1123400.00.04

Compulsory accessories / Accessori obbligatori


LED modules / Moduli LED



DG111 LED module / Modulo LED DG111		Not included
16,7W - 15° - 500mA DC		1A4700000.27.20
2700K - 1648lm - CRI >90		
Energy Efficiency F - Dimmable		
16,7W - 15° - 500mA DC		1A4700000.30.20
3000K - 1682lm - CRI >90		
Energy Efficiency F - Dimmable		




DG111 LED module / Modulo LED DG111		Not included
16,7W - 22° - 500mA DC		1A3890000.27.20
2700K - 1859lm - CRI >90		
Energy Efficiency F - Dimmable		
16,7W - 22° - 500mA DC		1A3890000.30.20
3000K - 1945lm - CRI >90		
Energy Efficiency F - Dimmable		




DG111 LED module / Modulo LED DG111		Not included
16,7W - 36° - 500mA DC		1A3900000.27.20
2700K - 1808lm - CRI >90		
Energy Efficiency F - Dimmable		
16,7W - 36° - 500mA DC		1A3900000.30.20
3000K - 1890lm - CRI >90		
Energy Efficiency F - Dimmable		

Optional accessories / Accessori opzionali


Other accessories / Altri accessori




Accessory holder + Soft filter + Honeycomb louvre / Porta accessori + Filtro soft + Frangiluce nido d'ape		Not included
Matt Black		1X0070400.04.00




Accessory holder + Elliptical filter / Porta accessori + Filtro ellittico		Not included
Matt Black		1X0070400.05.00



Blue filter / Filtro blu		Not included
Standard	Compulsory with 1X0070400.04.00 / 1X0070400.05.00	1X0070000.06.00




Red filter / Filtro rosso		Not included
Standard	Compulsory with 1X0070400.04.00 / 1X0070400.05.00	1X0070000.07.00



Yellow filter / Filtro giallo		Not included
Standard	Compulsory with 1X0070400.04.00 / 1X0070400.05.00	1X0070000.08.00

SANMARTINO

Omar Carraglia - Davide Groppi / 2014



**Where did the chandelier go?
A work about absence. About something missing.
As if by removing the chandelier, its memory stays,
but with a modern and sensual light.**

Dov'è finito il lampadario?
Un progetto sull'assenza, su qualcosa che manca.
Come se togliendo il lampadario, rimanga la sua memoria,
ma con una luce moderna e sensuale.

SANMARTINO

Omar Carraglia - Davide Groppi / 2014

Ceiling / Direct / Indoor

Material Metal
Finish .03 Matt White .15 Natural Brass

Note Ceiling luminaire. Visible 18 mm diameter hole. *Apparecchio illuminante da soffitto. Foro visibile con diametro da 18 mm.*



SANMARTINO

8,5W
100-240V - 50/60Hz
3000K - 375lm
CRI >90
Driver integrated
ON/OFF
CE IP20

Matt White - 3000K - ON/OFF
Natural Brass - 3000K - ON/OFF

1A3420300.30.00
1A3421500.30.00





A tool to light.

**The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.**

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

SPY PL


/ 2022

Ceiling / Direct / Indoor

Material Metal - Polycarbonate
Finish .03 Matt White

Note Ceiling luminaire.

Apparecchio illuminante da soffitto.




SPY PL

39W
110-240V - 50/60Hz
3000K - 4292lm
CRI >80
UGR <19
Driver integrated
DALI
CE IP20

Matt White - 3000K - DALI

| 1A2930300.30.01 |






**A simple, graphic solution.
Bringing accent lighting with an external wiring system.**

Una soluzione semplice e grafica.
Per portare luce d'accento con un sistema fuori traccia.

Wall-Ceiling / Direct / Indoor

Material	Metal
Finish	.03 Matt White .04 Matt Black

Note Ceiling luminaire. Adjustable in all directions. White cable (2 m) for the matt white finish. Black cable (2 m) for the matt black finish. Connects max 20 lamps. *Apparecchio illuminante da soffitto. Orientabile in tutte le direzioni. Cavo bianco (2 m) per la finitura bianco opaco. Cavo nero (2 m) per la finitura nero opaco. Collegabili max 20 apparecchi.*



TRICK TRACK

Max 10W - GU10
100-240V - 50/60Hz
ON/OFF
Bulb not included
CE IP20

Matt White - ON/OFF
Matt Black - ON/OFF

1A3430300.00.00
1A3430400.00.00

Optional accessories / Accessori opzionali

Installation kits / Kit d'installazione



Wall and ceiling rose / Rosone da parete e soffitto	Not included
Matt White	1A3440300.00.00
Matt Black	1A3440400.00.00

Bulbs / Lampadine



LED - GU10 - PAR16	Not included
220-240V - 5,5W - 25° 3000K - 375lm - CRI >97 Energy Efficiency G - Dimmable	1Y0330500




LED SORAA - GU10 - MR16	Not included
230V - 7,5W - 10° 2700K - 390lm - CRI >95 Energy Efficiency G - Dimmable	1Y1580210




LED SORAA - GU10 - MR16	Not included
230V - 7,5W - 10° 3000K - 410lm - CRI >95 Energy Efficiency G - Dimmable	1Y1580010


Other accessories / Altri accessori



Darklight	Not included
LED SORAA - GU10 - MR16	1Y1580040



25° beam filter / Filtro fascio 25°	Not included
LED SORAA - GU10 - MR16	1Y1580020



36° beam filter / Filtro fascio 36°	Not included
LED SORAA - GU10 - MR16	1Y1580030

RECESSED / INCASSO



A tool to light.

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

BUCO 58

/ 2021

Recessed / Direct / Indoor

Material Glass - Metal
Finish .03 Matt White .04 Matt Black

Note Recessed luminaire. Plasterboard hole: Ø 50 mm. Minimum space for recessed installation: 150 mm. *Apparecchio illuminante da incasso. Foro del cartongesso: Ø 50 mm. Spazio minimo per incasso: 150 mm.*



BUCO 58

7W
 24V DC
 2700K - 495lm / 3000K - 546lm
 CRI >90
 Beam 40°
 Driver not included


CE IP67

Matt White - 2700K
 Matt White - 3000K
 Matt Black - 2700K
 Matt Black - 3000K

1A1490300.27.20
 1A1490300.30.20
 1A1490400.27.20
 1A1490400.30.20

Compulsory accessories / Accessori obbligatori

Drivers / Alimentatori



Driver / Alimentatore		Not included
110-240V	24V/25W/IP67/ON/OFF	1Z1120620

Optional accessories / Accessori opzionali


Installation kits / Kit d'installazione



Installation box / Cassaforma		Not included
Standard	Cut-out Ø 53 mm Minimum space for mounting 150 mm	1A1500000.00.00



Driver connector IP68 / Connettore driver IP68		Not included
	1 Piece	1A1660000.00.00





A tool to light.

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

BUCO R

/ 2006

Recessed / Direct / Indoor

Material Metal
Finish .03 Matt White

Note Recessed luminaire. Adjustable in all directions. Plasterboard hole: Ø 90 mm. *Apparecchio illuminante da incasso. Orientabile in tutte le direzioni. Foro del cartongesso: Ø 90 mm. Spazio minimo per incasso: 85 mm.*



BUCO R

Max 35W - GU5,3 - 12V

12V

Driver not included

ON/OFF

Bulb not included


CE IP20 1.0 m

Matt White - ON/OFF

| 1A3720300.00.00 |

Compulsory accessories / Accessori obbligatori

Drivers / Alimentatori



Driver / Alimentatore

230-240V

12V/50W/IP20/TRIAC/IGBT

1Z0240440

Not included

Optional accessories / Accessori opzionali

Bulbs / Lampadine



LED - GU5,3 - MR16

12V - 6,7W - 36°


3000K - 440lm - CRI >97

Energy Efficiency G - Dimmable

1Y0330530

Not included





DOT R

Omar Carraglia - Davide Groppi / 2015



A tool to light.

A luminaire designed for use with state-of-the-art LED modules to offer superior performance and a wide range of light beams.


Elemento di luce.

Un apparecchio illuminante progettato per utilizzare moduli a LED in grado di fornire prestazioni superiori ed un'ampia gamma di fasci luminosi.

Recessed / Direct / Indoor

Material Metal
Finish .03 Matt White .04 Matt Black

Note Recessed luminaire. Adjustable in all directions. Plasterboard hole: 40x40 mm. Minimum space for recessed installation: 85 mm. *Apparecchio illuminante da incasso. Orientabile in tutte le direzioni. Foro del cartongesso: 40x40 mm. Spazio minimo per incasso: 85 mm.*




DOT R

13W
 Max 350mA DC
 2700K / 3000K
 CRI >97
 Driver not included



Matt White - 2700K
 Matt White - 3000K
 Matt Black - 2700K
 Matt Black - 3000K

1A4770300.27.20
 1A4770300.30.20
 1A4770400.27.20
 1A4770400.30.20



DOT R 51

Max 10W - GU10
 100-240V - 50/60Hz
 ON/OFF
 Bulb not included




Matt White - ON/OFF
 Matt Black - ON/OFF


1A3700300.00.00
 1A3700400.00.00

Compulsory accessories / Accessori obbligatori


Drivers / Alimentatori



Driver / Alimentatore				Not included
220-240V(100-127V)	350mA/17W(15W)/IP20/DALI	DOT R	1Z0241180.350	



Driver / Alimentatore				Not included
220-240V(100-127V)	350mA/18W(15W)/IP20/PUSH - 1-10V	DOT R	1Z0240870.350	



Driver / Alimentatore				Not included
220-240V	350mA/17W/IP20/TRIAC/IGBT	DOT R	1Z0240850.350	

Other accessories / Altri accessori




Lens / Lente Not included


Beam - 14°	2700K - CRI >97 - 983lm	DOT R	1A3090000.00.00
	3000K - CRI >97 - 1038lm		
Beam - 24°	2700K - CRI >97 - 943lm	DOT R	1A3100000.00.00
	3000K - CRI >97 - 996lm		
Beam - 36°	2700K - CRI >97 - 955lm	DOT R	1A3110000.00.00
	3000K - CRI >97 - 1005lm		
Beam - 50°	2700K - CRI >97 - 965lm	DOT R	1A3120000.00.00
	3000K - CRI >97 - 1016lm		

Optional accessories / Accessori opzionali


Other accessories / Altri accessori




Accessory holder + Honeycomb louvre / Porta accessori + Frangiluce nido d'ape		Not included	
	DOT R	1X0080400.01.00	




Elliptical filter / Filtro ellittico		Not included	
Standard	Compulsory with 1X0080400.01.00	DOT R	1X0080000.02.00



Blue filter / Filtro blu		Not included	
Standard	Compulsory with 1X0080400.01.00	DOT R	1X0080000.03.00



Red filter / Filtro rosso		Not included	
Standard	Compulsory with 1X0080400.01.00	DOT R	1X0080000.04.00



Yellow filter / Filtro giallo		Not included	
Standard	Compulsory with 1X0080400.01.00	DOT R	1X0080000.05.00

Optional accessories / Accessori opzionali

Bulbs / Lampadine



LED - GU10 - PAR16		Not included	
	220-240V - 5,5W - 25° 3000K - 375lm - CRI >97 Energy Efficiency G - Dimmable	DOT R 51	1Y0330500




LED SORAA - GU10 - MR16		Not included	
	230V - 7,5W - 10° 2700K - 390lm - CRI >95 Energy Efficiency G - Dimmable	DOT R 51	1Y1580210




LED SORAA - GU10 - MR16		Not included	
	230V - 7,5W - 10° 3000K - 410lm - CRI >95 Energy Efficiency G - Dimmable	DOT R 51	1Y1580010


Other accessories / Altri accessori



Darklight		Not included	
	LED SORAA - GU10 - MR16	DOT R 51	1Y1580040



25° beam filter / Filtro fascio 25°		Not included	
	LED SORAA - GU10 - MR16	DOT R 51	1Y1580020



36° beam filter / Filtro fascio 36°		Not included	
	LED SORAA - GU10 - MR16	DOT R 51	1Y1580030



A tool to light.

**The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.**

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

Recessed / Direct / Indoor

Material Metal
Finish .03 Matt White .04 Matt Black

Note Recessed luminaire. Adjustable in all directions. Plasterboard hole: 104x104 mm. Minimum space for recessed installation: 130 mm. *Apparecchio illuminante da incasso. Orientabile in tutte le direzioni. Foro del cartongesso: 104x104 mm. Spazio minimo per incasso: 130 mm.*



MINI 51

Max 10W - GU10
 100-240V - 50/60Hz
 ON/OFF

Bulb not included



Matt White - ON/OFF
 Matt Black - ON/OFF

1A0660300.00.00
 1A0660400.00.00

Compulsory accessories / Accessori obbligatori

Installation kits / Kit d'installazione



Plasterboard frame 12,5 mm / Cornice per cartongesso 12,5 mm			Not included
Matt White	Cut-out 104x104 mm Minimum space for mounting 130 mm	1A3500300.00.00	
Matt Black	Cut-out 104x104 mm Minimum space for mounting 130 mm	1A3500400.00.00	

Optional accessories / Accessori opzionali

Bulbs / Lampadine



LED - GU10 - PAR16	Not included
220-240V - 5,5W - 25° 3000K - 375lm - CRI >97 Energy Efficiency G - Dimmable	1Y0330500




LED SORAA - GU10 - MR16	Not included
230V - 7,5W - 10° 2700K - 390lm - CRI >95 Energy Efficiency G - Dimmable	1Y1580210




LED SORAA - GU10 - MR16	Not included
230V - 7,5W - 10° 3000K - 410lm - CRI >95 Energy Efficiency G - Dimmable	1Y1580010


Other accessories / Altri accessori



Darklight	Not included
LED SORAA - GU10 - MR16	1Y1580040



25° beam filter / Filtro fascio 25°	Not included
LED SORAA - GU10 - MR16	1Y1580020



36° beam filter / Filtro fascio 36°	Not included
LED SORAA - GU10 - MR16	1Y1580030



A tool to light.

**The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.**

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

MINI BIT 51

/ 2016

Recessed / Direct / Indoor

Material Metal
Finish .03 Matt White .34 Matt White/Black Bicolor

Note Recessed luminaire. Adjustable in all directions. Plasterboard hole: 104x104 mm. Minimum space for recessed installation: 130 mm. *Apparecchio illuminante da incasso. Orientabile in tutte le direzioni. Foro del cartongesso: 104x104 mm. Spazio minimo per incasso: 130 mm.*



MINI BIT 51

Max 10W - GU10
 100-240V - 50/60Hz
 ON/OFF

Bulb not included



Matt White - ON/OFF

Matt White/Black Bicolor - ON/OFF

1A0670300.00.00

1A0673400.00.00

MINI BIT 51

/ 2016

Optional accessories / Accessori opzionali

Bulbs / Lampadine



LED - GU10 - PAR16

220-240V - 5,5W - 25°
 3000K - 375lm - CRI >97
 Energy Efficiency G - Dimmable

1Y0330500

Not included



LED SORAA - GU10 - MR16

230V - 7,5W - 10°
 2700K - 390lm - CRI >95
 Energy Efficiency G - Dimmable

1Y1580210

Not included




LED SORAA - GU10 - MR16

230V - 7,5W - 10°
 3000K - 410lm - CRI >95
 Energy Efficiency G - Dimmable

1Y1580010

Not included

Other accessories / Altri accessori




Darklight / Darklight

LED SORAA - GU10 - MR16

1Y1580040

Not included




25° beam filter / Filtro fascio 25°

LED SORAA - GU10 - MR16

1Y1580020

Not included



36° beam filter / Filtro fascio 36°


LED SORAA - GU10 - MR16

1Y1580030

Not included

MIRA R

Omar Carraglia / 2015



A tool to light.

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.


MIRA R

Omar Carraglia / 2015

Recessed / Direct / Indoor

Material Metal
Finish .03 Matt White .04 Matt Black

Note Recessed luminaire. Adjustable in all directions. Plasterboard hole: *Apparecchio illuminante da incasso. Orientabile in tutte le direzioni.*
 40x40 mm. Minimum space for recessed installation: 85 mm. *Foro del cartongesso: 40x40 mm. Spazio minimo per incasso: 85 mm.*



MIRA R


5,6W
 Max 500mA DC
 2700K - 327lm / 3000K - 352lm
 CRI >90
 Driver not included
 CE IP20

Matt White - 2700K
 Matt White - 3000K
 Matt Black - 2700K
 Matt Black - 3000K


1A3690300.27.20
 1A3690300.30.20
 1A3690400.27.20
 1A3690400.30.20

Compulsory accessories / Accessori obbligatori


Drivers / Alimentatori



Driver / Alimentatore	Not included
220-240V(100-127V) 500mA/20W(15W)/IP20/DALI	1Z0241180.500



Driver / Alimentatore	Not included
220-240V(100-127V) 500mA/20W(15W)/IP20/PUSH - 1-10V	1Z0240870.500



Driver / Alimentatore	Not included
220-240V 500mA/20W/IP20/TRIAC/IGBT	1Z0240850.500





An extreme expression of subtraction, uniting optics and electronics as an answer to the ultimate challenge: the absence of structural support and the essence of light.

Nulla is a project that represents both the beginning and end of our work on light.

It's the beginning, in the sense that we have always been looking for absolute light, one coming from a distance, almost without a source. It's the end in that every time we

look at Nulla, we feel as though we can't get it better than that.

Nulla generates light and propagates mystery. Nulla is the most generous of our lamps.

Its sole objective is to hide and give all the attention to whatever it is lighting.

What we see is only a tiny black hole, as if it were drawn on the ceiling.

A circle in the ceiling hiding a very bright LED and lens to project the light.

XXIII Compasso d'Oro ADI Award, 2014

Un lavoro estremo di sottrazione, che unisce elettronica e l'ottica verso la sfida finale:

l'assenza del supporto e l'essenza della luce.

Nulla è un progetto che rappresenta l'inizio e la fine del nostro lavoro sulla luce.

L'inizio perché da sempre cerchiamo la luce assoluta, quella che arriva da lontano,

quasi senza fonte. La fine perché ogni volta che guardiamo Nulla

ci sembra di non potere andare più avanti di così.

Nulla genera luce e diffonde mistero. È la più generosa delle nostre lampade,

quella che si nasconde al solo scopo di regalare la scena al soggetto illuminato.

Ciò che appare è solo un minuscolo buco nero, quasi disegnato.

Un foro nel soffitto, un LED potentissimo e una lente che generano la luce.


Premio XXIII Premio Compasso d'Oro ADI, 2014



Recessed / Direct / Indoor

Material Metal
Finish .00 Standard

Note Recessed luminaire. Visible 18 / 25 mm diameter hole. NULLA 18 and NULLA 25: lamp extractable for maintenance. *Apparecchio illuminante da incasso. Foro visibile con diametro da 18 / 25 mm. NULLA 18 e NULLA 25: apparecchio estraibile per manutenzione.*




NULLA - 23°

14W
 24V DC
 2700K - 425lm / 3000K - 458lm
 CRI >90
 Beam 23°
 UGR <19
 Driver not included
 CE IP20/IP65

Standard - 2700K
 Standard - 3000K

1A4100000.27.20
 1A4100000.30.20



NULLA - 32°

14W
 24V DC
 2700K - 538lm / 3000K - 579lm
 CRI >90
 Beam 32°
 UGR <19
 Driver not included
 CE IP20/IP65

Standard - 2700K
 Standard - 3000K

1A2110000.27.20
 1A2110000.30.20



NULLA 18 - 20°

4,5W
 24V DC
 2700K - 174lm / 3000K - 186lm
 CRI >90
 Beam 20°
 UGR <19
 Driver not included
 CE IP20

Standard - 2700K
 Standard - 3000K

1A2010000.27.20
 1A2010000.30.20



NULLA 25 - 23°

9W
 24V DC
 2700K - 304lm / 3000K - 327lm
 CRI >90
 Beam 23°
 UGR <19
 Driver not included
 CE IP20/IP65

Standard - 2700K
 Standard - 3000K

1A4080000.27.20
 1A4080000.30.20



NULLA 25 - 32°

9W
 24V DC
 2700K - 384lm / 3000K - 413lm
 CRI >90
 Beam 32°
 UGR <19
 Driver not included
 CE IP20/IP65

Standard - 2700K
 Standard - 3000K


1A2020000.27.20
 1A2020000.30.20

Compulsory accessories / Accessori obbligatori


Installation kits / Kit d'installazione



Plasterboard flange 12,5 mm / Flangia per cartongesso 12,5 mm				Not included
Matt Black	Cut-out Ø 21 mm Minimum space for mounting 100 mm IP65	NULLA	1A2200400.00.00	



Plasterboard flange 12,5 mm / Flangia per cartongesso 12,5 mm				Not included
Matt Black	Cut-out Ø 22 mm Minimum space for mounting 190 mm	NULLA 18	1A2210400.00.00	



Plasterboard flange 12,5 mm / Flangia per cartongesso 12,5 mm				Not included
Matt Black	Cut-out Ø 35 mm Minimum space for mounting 190 mm	NULLA 25	1A2170400.00.00	




Plasterboard flange 12,5 mm / Flangia per cartongesso 12,5 mm				Not included
Matt Black	Cut-out Ø 35 mm Minimum space for mounting 145 mm IP65	NULLA 25	1A3980400.00.00	




Plasterboard flange (bottom) ≠ 12,5 mm / Flangia (da sotto) per cartongesso ≠ 12,5 mm				Not included
Matt Black	Cut-out Ø 35 mm Minimum space for mounting 145 mm IP65	NULLA 25	1A4960400.00.00	


Drivers / Alimentatori



Driver / Alimentatore			Not included
220-240V(100-127V)	24V/16W(15W)/IP20/DALI		1Z0241180.24



Driver / Alimentatore			Not included
220-240V(100-127V)	24V/20W(15W)/IP20/PUSH		1Z0240870.24




Driver / Alimentatore			Not included
220-240V	24V/20W/IP20/TRIAC/IGBT		1Z0240850.24

Optional accessories / Accessori opzionali


Installation kits / Kit d'installazione




Trapdoor for plasterboard 12,5 mm / Botola per cartongesso 12,5 mm				Not included
Standard	Cut-out 205x205 mm	NULLA	1A3780000.00.00	




Trapdoor for plasterboard 12,5 mm / Botola per cartongesso 12,5 mm				Not included
Standard	Cut-out 415x415 mm	NULLA	1A3790000.00.00	




Masonry Box / Cassaforma per laterizio				Not included
Standard		NULLA 18	1A2390000.00.00	




Concrete box / Cassaforma per cemento				Not included
Standard		NULLA 18	1A2240000.00.00	




Masonry Box / Cassaforma per laterizio				Not included
Standard		NULLA 25	1A2380000.00.00	




Concrete box / Cassaforma per cemento				Not included
Standard		NULLA 25	1A2230000.00.00	



NULLA installation conditions



NULLA 18 installation conditions



NULLA 25 installation conditions





A tool to light.

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

Recessed / Direct / Indoor

Material Metal
Finish .03 Matt White .04 Matt Black

Note Recessed luminaire. Adjustable in all directions. Plasterboard hole: 133x148 mm. Minimum space for recessed installation: 180 mm. *Apparecchio illuminante da incasso. Orientabile in tutte le direzioni. Foro del cartongesso: 133x148 mm. Spazio minimo per incasso: 180 mm.*



PUNTO

Max 21W
 Max 500mA DC
 CRI >90
 Driver not included
 LED module not included



Matt White
 Matt Black

1A1100300.00.20
 1A1100400.00.20

Compulsory accessories / Accessori obbligatori

Installation kits / Kit d'installazione



Plasterboard frame 12,5 mm / Cornice per cartongesso 12,5 mm Not included		
Matt White	Cut-out 133x148 mm Minimum space for mounting 180 mm	1A3510300.00.00
Matt Black	Cut-out 133x148 mm Minimum space for mounting 180 mm	1A3510400.00.00

LED modules / Moduli LED



DG111 LED module / Modulo LED DG111 Not included		
	16,7W - 15° - 500mA DC 2700K - 1648lm - CRI >90 Energy Efficiency F - Dimmable	1A4700000.27.20
	16,7W - 15° - 500mA DC 3000K - 1682lm - CRI >90 Energy Efficiency F - Dimmable	1A4700000.30.20




DG111 LED module / Modulo LED DG111 Not included		
	16,7W - 22° - 500mA DC 2700K - 1859lm - CRI >90 Energy Efficiency F - Dimmable	1A3890000.27.20
	16,7W - 22° - 500mA DC 3000K - 1945lm - CRI >90 Energy Efficiency F - Dimmable	1A3890000.30.20




DG111 LED module / Modulo LED DG111 Not included		
	16,7W - 36° - 500mA DC 2700K - 1808lm - CRI >90 Energy Efficiency F - Dimmable	1A3900000.27.20
	16,7W - 36° - 500mA DC 3000K - 1890lm - CRI >90 Energy Efficiency F - Dimmable	1A3900000.30.20


Drivers / Alimentatori



Driver / Alimentatore Not included		
220-240V(100-127V)	500mA/20W(15W)/IP20/DALI	1Z0241180.500



Driver / Alimentatore Not included		
220-240V(100-127V)	500mA/20W(15W)/IP20/PUSH	1Z0240840.500



Driver / Alimentatore Not included		
220-240V	500mA/20W/IP20/TRIAC/IGBT	1Z0240850.500

Optional accessories / Accessori opzionali

Other accessories / Altri accessori



Accessory holder + Soft filter + Honeycomb louvre / Porta accessori + Filtro soft + Frangilucente nido d'ape Not included
 Matt Black 1X0070400.04.00



Accessory holder + Elliptical filter / Porta accessori + Filtro ellittico Not included
 Matt Black 1X0070400.05.00




Blue filter / Filtro blu Not included
 Standard Compulsory with 1X0070000.06.00
 1X0070400.04.00 / 1X0070400.05.00




Red filter / Filtro rosso Not included
 Standard Compulsory with 1X0070000.07.00
 1X0070400.04.00 / 1X0070400.05.00



Yellow filter / Filtro giallo Not included
 Standard Compulsory with 1X0070000.08.00
 1X0070400.04.00 / 1X0070400.05.00





A tool to light.

**The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.**


Elemento di luce.

**Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.**

Recessed / Diffuse / Indoor

Material Metal
 Finish .03 Matt White

Note Recessed luminaire. Plasterboard hole: 161x138 mm. Minimum space for recessed installation: 80 mm. *Apparecchio illuminante da incasso. Foro del cartongesso: 161x138 mm. Spazio minimo per incasso: 80 mm.*



PURA


6W
 110-240V - 50/60Hz
 3000K - 445lm
 CRI >80
 Driver integrated
 ON/OFF
 CE IP20

Matt White - 3000K - ON/OFF

| 1A3520300.30.00 |

Compulsory accessories / Accessori obbligatori

Installation kits / Kit d'installazione



Installation box / Cassaforma

Not included

Standard	Plasterboard cut-out 161x138 mm Minimum space for mounting 80 mm	1A3530000.00.00
----------	---	-----------------





A tool to light.

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

QUAD

/ 2021

Recessed / Diffuse / Indoor

Material Metal
Finish .03 Matt White

Note Recessed luminaire. Plasterboard hole: 40x60 mm. Minimum space for recessed installation: 80 mm. *Apparecchio illuminante da incasso. Foro del cartongesso: 40x60 mm. Spazio minimo per incasso: 80 mm.*



QUAD

2W

Max 500mA DC

2700K - 128lm / 3000K - 133lm

CRI >90

Driver not included

CE IP44

Matt White - 2700K


Matt White - 3000K

1A1510300.27.20

1A1510300.30.20

Compulsory accessories / Accessori obbligatori

Drivers / Alimentatori



Driver / Alimentatore


220-240V(110-127V) 500mA/24W(15W)/IP68/ON/OFF

1Z0241170

Not included

Optional accessories / Accessori opzionali

Installation kits / Kit d'installazione



Installation box / Cassaforma

Standard Plasterboard cut-out 40x60 mm
Minimum space for mounting 80 mm

1A1520000.00.00

Not included



SYSTEMS / SISTEMI




Absolute freedom, absolute spatiality, absolute creativity.
An adhesive tape that conducts electricity can be placed anywhere
on walls and ceilings to power our lighting projects.
Endless is the system created and patented by our Team in order to transport
electric energy in a digital and graphic manner.
It's the idea of considering walls and ceilings like electronic circuits,
where luminaires can be done fixed freely and easily.
This system comes with various accessories
to provide and manage the flow of electricity.

Libertà assoluta, spazialità assoluta, creatività assoluta.
Un nastro conduttore e adesivo che può essere disposto a piacimento
su pareti e soffitti per alimentare i nostri modelli.
Endless è il sistema ideato e brevettato dal nostro Team per portare
"differenza di potenziale" dove si desidera in modo grafico e digitale.
È l'idea di considerare le pareti e i soffitti come circuiti elettronici
per posizionare gli apparecchi illuminanti con la massima libertà.
Il sistema è dotato di vari accessori di alimentazione e derivazione.



2018/11 39900010 device_grouppl + MAX.48V DC MAX.4A MAX.150W 2018/11 39900010 device_grouppl + MAX.48V DC MAX.4A MAX.150W 2018/11 39900010

POWER SUPPLY MAX.4A DRY LOCATION ONLY - FOR NORTH AMERICA USE ONLY CLASS 2 POWER SUPPLY MAX.4A DRY LOCATION ONLY - FOR NORTH AMERICA USE ONLY CLASS 2 POWER SUPPLY MAX.4A DRY LOCATION ONLY - FOR NORTH AMERICA USE ONLY CLASS 2 POWER SUPPLY MAX.4A DRY LOCATION ONLY





ENDLESS


ENDLESS ON/OFF
(Max 48V DC -
Max 150W - Max 4A)




ENDLESS dimmable
(Max 48V DC -
Max 150W - Max 4A)



ENDLESS CASAMBI
(Max 48V DC -
Max 150W - Max 4A)



ENDLESS conductive tape
used with voltage/current
other than 48V DC




Davide Groppi / 2018

Systems / Direct-Indirect-Diffuse / Indoor

Material Metal
Finish .00 Standard

Note System consisting of a conductive adhesive tape to apply to surfaces. *Sistema costituito da un nastro conduttivo adesivo applicabile alle superfici.*
 Possibility to connect several lamps (Max 48V DC - Max 150W - Max 4A). *Possibilità di collegare più apparecchi (Max 48V DC - Max 150W - Max 4A).*



Compulsory accessories / Accessori obbligatori

Installation kits / Kit d'installazione



Strip Endless - 5 m / Strip Endless - 5 m		Not included
Matt White	Output 48V - Max 150W - Max 4A	1A3470300.00.00
Matt Black	Output 48V - Max 150W - Max 4A	1A3470400.00.00




Strip Endless - 10 m / Strip Endless - 10 m		Not included
Matt White	Output 48V - Max 150W - Max 4A	1A0050300.00.00
Matt Black	Output 48V - Max 150W - Max 4A	1A0050400.00.00



Fixing rough walls kit / Kit di fissaggio per pareti ruvide		Not included
Length 2,5 m		1A0370000.00.00



Terminal box / Scatola di collegamento		Not included
Matt White	2 Terminals included	1A3480300.00.00
Matt Black	2 Terminals included	1A3480400.00.00




Power base / Base di alimentazione		Not included
Matt White		1A0030300.00.00
Matt Black		1A0030400.00.00




Terminals / Morsetti		Not included
2 Pieces		1A3490000.00.00

Compulsory accessories / Accessori obbligatori


Drivers for ENDLESS ON/OFF system and CASAMBI / Alimentatori per ENDLESS ON/OFF e CASAMBI




Driver with plug / Alimentatore con spina		Not included
Matt White	Input 100-240V - 50/60Hz Output 48V - 60W - Max 1,25A IP20 - ON/OFF	1A1330300.00.00
Matt Black	Input 100-240V - 50/60Hz Output 48V - 60W - Max 1,25A IP20 - ON/OFF	1A1330400.00.00



Wall/ceiling/remote driver / Alimentatore parete/soffitto/remoto		Not included
Matt White	Input 100-240V - 50/60Hz Output 48V - 60W - Max 1,25A IP20 - ON/OFF	1A2450300.00.00
Matt Black	Input 100-240V - 50/60Hz Output 48V - 60W - Max 1,25A IP20 - ON/OFF	1A2450400.00.00




Driver with plug / Alimentatore con spina		Not included
Matt White	Input 100-240V - 50/60Hz Output 48V - 150W - Max 3,125A IP20 - ON/OFF	1A0260300.00.00
Matt Black	Input 100-240V - 50/60Hz Output 48V - 150W - Max 3,125A IP20 - ON/OFF	1A0260400.00.00




Wall/ceiling/remote driver / Alimentatore parete/soffitto/remoto		Not included
Matt White	Input 100-240V - 50/60Hz Output 48V - 150W - Max 3,125A IP20 - ON/OFF	1A1020300.00.00
Matt Black	Input 100-240V - 50/60Hz Output 48V - 150W - Max 3,125A IP20 - ON/OFF	1A1020400.00.00

Compulsory accessories / Accessori obbligatori


Drivers for ENDLESS dimmable system / Alimentatori per ENDLESS dimmerabile




Driver with plug / Alimentatore con spina		Not included
Matt White	Input 100-240V - 50/60Hz Output 48V - 60W - Max 1,25A IP20 - Dimmer on board	1A1340300.00.06
Matt Black	Input 100-240V - 50/60Hz Output 48V - 60W - Max 1,25A IP20 - Dimmer on board	1A1340400.00.06



Wall/ceiling driver / Alimentatore parete/soffitto		Not included
Matt White	Input 100-240V - 50/60Hz Output 48V - 60W - Max 1,25A IP20 - DALI - PUSH - 1-10V	1A4090300.00.07
Matt Black	Input 100-240V - 50/60Hz Output 48V - 60W - Max 1,25A IP20 - DALI - PUSH - 1-10V	1A4090400.00.07



Driver with plug / Alimentatore con spina		Not included
Matt White	Input 100-240V - 50/60Hz Output 48V - 150W - Max 3,125A IP20 - Dimmer on board	1A1800300.00.06
Matt Black	Input 100-240V - 50/60Hz Output 48V - 150W - Max 3,125A IP20 - Dimmer on board	1A1800400.00.06




Wall/ceiling driver / Alimentatore parete/soffitto		Not included
Matt White	Input 100-240V - 50/60Hz Output 48V - 150W - Max 3,125A IP20 - DALI - PUSH - 1-10V	1A1810300.00.07
Matt Black	Input 100-240V - 50/60Hz Output 48V - 150W - Max 3,125A IP20 - DALI - PUSH - 1-10V	1A1810400.00.07




Compulsory accessories / Accessori obbligatori


Remote drivers for ENDLESS / Alimentatori remoti per ENDLESS




Driver / Alimentatore		Not included
100-240V	48V/60W/IP67/ON/OFF	1Z1120640




Driver / Alimentatore		Not included
100-240V	48V/150W/IP67/1-10V	1Z1120250




Controller / Controller		Not included
DALI - PUSH - 0/1-10V - TRIAC - IP20		1Z2170010




Examples of installation with the three different power supply modes




Example of combined installation between various devices with remote driver




Example of combined installation between various devices with driver with plug



Example of combined installation between various devices with wall/ceiling driver




CATHODE: example of installation




MISS: example of installation







REFLEX: example of installation with remote driver




REFLEX: example of installation with wall/ceiling driver




REFLEX: example of installation with driver with plug






FLASH and INFINITO: example of installation with remote driver




FLASH and INFINITO: example of installation with wall/ceiling driver



FLASH and INFINITO: example of installation with driver with plug







COLIBRI: example of installation




1A4170000.20.00
COLIBRI ENDLESS connector



OHM: example of installation



OHM: example of installation



UTOPIA: example of installation

1X001XX00.02.00 - 1X001XX00.04.00
Ceiling suspension kit





FLASH

Davide Groppi / 2017

It is our Infinito model turned around, with the light flowing downwards.
The 9 mm wide stainless steel strip can run perfectly up to 36 metres in length
(standard versions at 6 / 12 / 18 metres in length).

The ideal solution for direct illumination of spaces with very high ceilings.
Its name pays homage to the famous comic book superhero,
who can run seven times the speed of light.

Luminaire designed also to be powered by ENDLESS system.

È la declinazione del nostro modello Infinito, ma con la luce diretta verso il basso.
Il nastro in acciaio inossidabile, largo 9 millimetri, può essere teso perfettamente
fino a 36 metri di lunghezza (lampada standard 6 / 12 / 18 metri).


La soluzione ideale per l'illuminazione diretta di spazi di grande altezza.

Il nome è un omaggio al leggendario supereroe dei fumetti.


Famoso perché corre sette volte più veloce della luce...

Apparecchio illuminante alimentabile anche con il sistema ENDLESS.

How to order - FLASH 6



How to order - FLASH 12



How to order - FLASH 18



Wall-Systems / Direct / Indoor

Material Metal
 Finish .03 Matt White .04 Matt Black

Note Special stainless steel tape (9 mm) running from wall to wall. Available in 6 / 12 / 18 m with a single power unit and uniform lighting. Available in Dual emission (DE) and Tunable White (TW – 5 / 10 m) versions. LED strip that can be divided every 96,6 mm. DE versions are available with dual on/off (two drivers required). FLASH 6 and FLASH 12: possibility for the luminaires to be powered by ENDLESS system (Max 48V DC - Max 150W - Max 4A) and to be used, on the same circuit, with the ENDLESS models. See page: ENDLESS.

Speciale nastro (9 mm) in acciaio inox teso da parete a parete. Disponibile da 6/12/18m con un'unica alimentazione e illuminamento uniforme. Disponibile in versione a Doppia Emissione (DE) e in versione Tunable White (TW – 5 / 10 m). Strip LED sezionabile ogni 96,6 mm. Le versioni DE sono realizzabili con doppia accensione (necessari due driver). FLASH 6 e FLASH 12: apparecchi illuminanti alimentabili anche con il sistema ENDLESS (Max 48V DC - Max 150W - Max 4A) ed utilizzabili, sullo stesso circuito, con i modelli ENDLESS. Vedi pagina ENDLESS.

FLASH 6
 57W - 1,48A
 48V DC
 2700K - 6576lm / 3000K - 6708lm
 CRI >90
 Driver not included
 CE IP20 E

Matt White - 2700K	1A2130300.27.20
Matt White - 3000K	1A2130300.30.20
Matt Black - 2700K	1A2130400.27.20
Matt Black - 3000K	1A2130400.30.20


FLASH 12
 114W - 2,61A
 48V DC
 2700K - 13152lm / 3000K - 13416lm
 CRI >90
 Driver not included
 CE IP20 E

Matt White - 2700K	1A2150300.27.20
Matt White - 3000K	1A2150300.30.20
Matt Black - 2700K	1A2150400.27.20
Matt Black - 3000K	1A2150400.30.20


FLASH 18
 171W
 48V DC
 2700K - 19728lm / 3000K - 20124lm
 CRI >90
 Driver not included
 CE IP20 E

Matt White - 2700K	1A2900300.27.20
Matt White - 3000K	1A2900300.30.20
Matt Black - 2700K	1A2900400.27.20
Matt Black - 3000K	1A2900400.30.20



How to order -
FLASH 6 DE



How to order -
FLASH 12 DE



How to order -
FLASH 18 DE




FLASH 6 DE

Dual emission
114W
48V DC
2700K - Up 6576lm - Down 6576lm /
3000K - Up 6708lm - Down 6708lm
CRI >90
Driver not included
CE IP20

Matt White - 2700K
Matt White - 3000K
Matt Black - 2700K
Matt Black - 3000K

1A1290300.27.20
1A1290300.30.20
1A1290400.27.20
1A1290400.30.20




FLASH 12 DE

Dual emission
228W
48V DC
2700K - Up 13152lm - Down 13152lm /
3000K - Up 13416lm - Down 13416lm
CRI >90
Driver not included
CE IP20

Matt White - 2700K
Matt White - 3000K
Matt Black - 2700K
Matt Black - 3000K

1A1300300.27.20
1A1300300.30.20
1A1300400.27.20
1A1300400.30.20




FLASH 18 DE

Dual emission
342W
48V DC
2700K - Up 19728lm - Down 19728lm /
3000K - Up 20124lm - Down 20124lm
CRI >90
Driver not included
CE IP20


Matt White - 2700K
Matt White - 3000K
Matt Black - 2700K
Matt Black - 3000K

1A1310300.27.20
1A1310300.30.20
1A1310400.27.20
1A1310400.30.20


How to order -
FLASH 5 TW



How to order -
FLASH 10 TW




Note Tunable White describes the variable colour temperature controls from warm white to cool white light. *Tunable White è la regolazione variabile della temperatura di colore della luce dalla tonalità calda a quella fredda.*



FLASH 5 TW
Tunable White
50W
24V DC
2700K / 6500K - 7650lm
CRI >90
Driver not included
CE IP20

Matt White - 2700K / 6500K
Matt Black - 2700K / 6500K

1A4820300.96.20
1A4820400.96.20




FLASH 10 TW
Tunable White
100W
24V DC
2700K / 6500K - 15300lm
CRI >90
Driver not included
CE IP20

Matt White - 2700K / 6500K
Matt Black - 2700K / 6500K

1A4830300.96.20
1A4830400.96.20

How to order -
FLASH 5 DE TW



FLASH 5 DE TW
1A4840300.96.20
1A4840400.96.20

+



2 x

REMOTE DRIVER
1Z1120400

+



2 x

CONTROLLER
1Z0830880

How to order -
FLASH 10 DE TW



FLASH 10 DE TW
1A4850300.96.20
1A4850400.96.20

+



4 x

REMOTE DRIVER
1Z1120400


+



4 x

CONTROLLER
1Z0830880


Note Tunable White describes the variable colour temperature controls from warm white to cool white light. *Tunable White è la regolazione variabile della temperatura di colore della luce dalla tonalità calda a quella fredda.*



FLASH 5 DE TW
Dual emission - Tunable White
100W
24V DC
2700K / 6500K - 15300lm
CRI >90
Driver not included
CE IP20

Matt White - 2700K / 6500K
Matt Black - 2700K / 6500K

1A4840300.96.20
1A4840400.96.20




FLASH 10 DE TW
Dual emission - Tunable White
200W
24V DC
2700K / 6500K - 30600lm
CRI >90
Driver not included
CE IP20

Matt White - 2700K / 6500K
Matt Black - 2700K / 6500K


1A4850300.96.20
1A4850400.96.20

Compulsory accessories / Accessori obbligatori


Drivers / Alimentatori




Driver with plug / Alimentatore con spina				Not included
Matt White	Input 100-240V - 50/60Hz Output 48V - Max 57W - IP20 Dimmer on board	FLASH 6	1X0060300.01.06	
Matt Black	Input 100-240V - 50/60Hz Output 48V - Max 57W - IP20 Dimmer on board	FLASH 6	1X0060400.01.06	




Driver with plug / Alimentatore con spina				Not included
Matt White	Input 100-240V - 50/60Hz Output 48V - Max 114W - IP20 Dimmer on board	FLASH 12	1X0060300.02.06	
Matt Black	Input 100-240V - 50/60Hz Output 48V - Max 114W - IP20 Dimmer on board	FLASH 12	1X0060400.02.06	




Driver / Alimentatore				Not included
100-240V	48V/80W/IP67/1-10V	FLASH 6 / FLASH 6 DE / FLASH 5 TW / FLASH 5 DE TW	1Z1120400	




Driver / Alimentatore				Not included
100-240V	48V/150W/IP67/1-10V	FLASH 12 / FLASH 12 DE / FLASH 10 TW / FLASH 10 DE TW	1Z1120250	



Driver / Alimentatore				Not included
100-240V	48V/240W/IP67/1-10V	FLASH 18 / FLASH 18 DE	1Z1120390	



Controller				Not included
	DALI - PUSH - 0/1-10V - TRIAC - IP20	FLASH 6 / FLASH 12 / FLASH 18 / FLASH 6 DE / FLASH 12 DE / FLASH 18 DE	1Z2170010	




Controller Casambi - Tunable white				Not included
		FLASH 5 TW / FLASH 10 TW / FLASH 5 DE TW / FLASH 10 DE TW	1Z0830880	

Optional accessories / Accessori opzionali


Installation kits / Kit d'installazione




Spacer / Distanziale				Not included
Matt White	For driver kit with plug	FLASH 6 / FLASH 12	1A4930300.00.00	
Matt Black	For driver kit with plug	FLASH 6 / FLASH 12	1A4930400.00.00	




Ceiling installation kit / Kit d'installazione da soffitto				Not included
Matt Black			1A0080400.00.00	



Kit wall connection vertical sloped 45° / Kit attacco da parete per inclinazione verticale 45°				Not included
Matt Black			1A0120400.00.00	




Kit wall connection sloped right 75° / Kit attacco da parete per inclinazione 75° destro				Not included
Matt Black			1A0340400.00.00	




Kit wall connection sloped left 75° / Kit attacco da parete per inclinazione 75° sinistro				Not included
Matt Black			1A0350400.00.00	




Swallows / Rondini				Not included
Matt Black			1A0800400.00.00	




Example of installation with remote driver




Example of installation with driver with plug







Example of installation with max rotation 30°



1A0340400.00.00 - 1A0350400.00.00 - Example of installation with kit wall connection sloped 75°



1A0120400.00.00 - Example of installation with kit wall connection vertical sloped 45°



1A0080400.00.00 - Example of installation with ceiling installation kit



INFINITO

Davide Groppi / 2016


A spatial concept, it is continuous light. An ultra-thin strip of special stainless steel just 18 mm wide "cuts" the space to produce indirect light. Infinito can be adapted to various situations, stretched from wall to wall or ceiling to floor. It comes in strips up to 36 metres in length (standard versions at 6 / 12 / 18 metres in length). Infinito breaks down the luminaire, turning it into something else, leaving only a trace, a line and then not even that, just light. This project pays homage to the art of Lucio Fontana and his spatial concepts. The graphic force of this system is surprising. It can be integrated into space, but at the same time it becomes part of that space. Infinito: essence and absence. Luminaire designed also to be powered by ENDLESS system.

Archiproducts Design Award 2017
People's Choice AZ Award 2017


È un concetto spaziale, è luce continua. Un nastro sottilissimo, in un particolare acciaio inossidabile e di soli 18 millimetri di larghezza, taglia lo spazio e produce luce indiretta. È possibile adattare, tendere e orientare Infinito da parete a parete, da soffitto a pavimento, fino a 36 metri di lunghezza (lampada standard 6 / 12 / 18 metri). Infinito smaterializza l'oggetto lampada, trasformandolo in qualcos'altro, lasciandone solo una traccia, una riga e poi nemmeno più quella, solo la luce. È un omaggio all'arte di Lucio Fontana e ai suoi concetti spaziali. La forza grafica di questo sistema è sorprendente, per la sua capacità di essere integrato e nello stesso tempo presente nello spazio. Infinito, essenza e assenza. Apparecchio illuminante alimentabile anche con il sistema ENDLESS.

Archiproducts Design Award 2017
People's Choice AZ Award 2017

How to order - INFINITO 6



How to order - INFINITO 12



How to order - INFINITO 18



Wall-Systems / Indirect / Indoor

Material Metal
Finish .03 Matt White .04 Matt Black

Note Special stainless steel tape (18 mm) stretched from wall to wall. Available in 6 / 12 / 18 m with a single power unit and uniform lighting. Available in Tunable White (TW - 5 / 10 m) version. LED strip that can be divided every 96,6 mm. INFINITO 6 and INFINITO 12: possibility for the luminaires to be powered by ENDLESS system (Max 48V DC - Max 150W - Max 4A) and to be used, on the same circuit, with the ENDLESS models. See page: ENDLESS.

Speciale nastro (18 mm) in acciaio inox teso da parete a parete. Disponibile da 6/12/18m con un'unica alimentazione e illuminamento uniforme. Disponibile in versione Tunable White (TW - 5 / 10 m). Strip LED sezionabile ogni 96,6 mm. INFINITO 6 e INFINITO 12: apparecchi illuminanti alimentabili anche con il sistema ENDLESS (Max 48V DC - Max 150W - Max 4A) ed utilizzabili, sullo stesso circuito, con i modelli ENDLESS. Vedi pagina ENDLESS.

INFINITO 6
57W - 1,48A
48V DC
2700K - 6576lm / 3000K - 6708lm
CRI >90
Driver not included
CE IP20 E

Matt White - 2700K	1A2250300.27.20
Matt White - 3000K	1A2250300.30.20
Matt Black - 2700K	1A2250400.27.20
Matt Black - 3000K	1A2250400.30.20


INFINITO 12
114W - 2,61A
48V DC
2700K - 13152lm / 3000K - 13416lm
CRI >90
Driver not included
CE IP20 E

Matt White - 2700K	1A2260300.27.20
Matt White - 3000K	1A2260300.30.20
Matt Black - 2700K	1A2260400.27.20
Matt Black - 3000K	1A2260400.30.20


INFINITO 18
171W
48V DC
2700K - 19728lm / 3000K - 20124lm
CRI >90
Driver not included
CE IP20

Matt White - 2700K	1A2270300.27.20
Matt White - 3000K	1A2270300.30.20
Matt Black - 2700K	1A2270400.27.20
Matt Black - 3000K	1A2270400.30.20


How to order -
INFINITO 5 TW



How to order -
INFINITO 10 TW




Note Tunable White describes the variable colour temperature controls from warm white to cool white light. *Tunable White è la regolazione variabile della temperatura di colore della luce dalla tonalità calda a quella fredda.*



INFINITO 5 TW
Tunable White
50W
24V DC
2700K / 6500K - 7650lm
CRI >90
Driver not included
CE IP20

Matt White - 2700K / 6500K
Matt Black - 2700K / 6500K

1A4860300.96.20
1A4860400.96.20




INFINITO 10 TW
Tunable White
100W
24V DC
2700K / 6500K - 15300lm
CRI >90
Driver not included
CE IP20

Matt White - 2700K / 6500K
Matt Black - 2700K / 6500K


1A4870300.96.20
1A4870400.96.20

Compulsory accessories / Accessori obbligatori


Drivers / Alimentatori




Driver with plug / Alimentatore con spina				Not included
Matt White	Input 100-240V - 50/60Hz Output 48V - Max 57W - IP20 Dimmer on board	INFINITO 6	1X0060300.01.06	
Matt Black	Input 100-240V - 50/60Hz Output 48V - Max 57W - IP20 Dimmer on board	INFINITO 6	1X0060400.01.06	




Driver with plug / Alimentatore con spina				Not included
Matt White	Input 100-240V - 50/60Hz Output 48V - Max 114W - IP20 Dimmer on board	INFINITO 12	1X0060300.02.06	
Matt Black	Input 100-240V - 50/60Hz Output 48V - Max 114W - IP20 Dimmer on board	INFINITO 12	1X0060400.02.06	




Driver / Alimentatore				Not included
100-240V	48V/80W/IP67/1-10V	INFINITO 6 / INFINITO 5 TW	1Z1120400	




Driver / Alimentatore				Not included
100-240V	48V/150W/IP67/1-10V	INFINITO 12 / INFINITO 10 TW	1Z1120250	



Driver / Alimentatore				Not included
100-240V	48V/240W/IP67/1-10V	INFINITO 18	1Z1120390	



Controller				Not included
	DALI - PUSH - 0/1-10V - TRIAC - IP20	INFINITO 6 / INFINITO 12 / INFINITO 18	1Z2170010	




Controller Casambi - Tunable white				Not included
		INFINITO 5 TW / INFINITO 10 TW	1Z0830880	

Optional accessories / Accessori opzionali


Installation kits / Kit d'installazione




Spacer / Distanziale				Not included
Matt White	For driver kit with plug	INFINITO 6 / INFINITO 12	1A4930300.00.00	
Matt Black	For driver kit with plug	INFINITO 6 / INFINITO 12	1A4930400.00.00	




Ceiling installation kit / Kit d'installazione da soffitto				Not included
Matt Black			1A0080400.00.00	



Kit wall connection vertical sloped 45° / Kit attacco da parete per inclinazione verticale 45°				Not included
Matt Black			1A0120400.00.00	




Kit wall connection sloped right 75° / Kit attacco da parete per inclinazione 75° destro				Not included
Matt Black			1A0340400.00.00	




Kit wall connection sloped left 75° / Kit attacco da parete per inclinazione 75° sinistro				Not included
Matt Black			1A0350400.00.00	



Swallows / Rondini				Not included
Matt Black			1A0290400.00.00	




Example of installation with remote driver




Example of installation with driver with plug







Example of installation with max rotation 30°




1A0340400.00.00 - 1A0350400.00.00 - Example of installation with kit wall connection sloped 75°



1A0120400.00.00 - Example of installation with kit wall connection vertical sloped 45°



1A0080400.00.00 - Example of installation with ceiling installation kit



Light runs on a wire. An almost imperceptible wire, suspended in space. Like a tightrope walker on a thin rope, the light reaches everywhere, weightless and wonderful. Ohm is an electro mechanic project that takes maximum advantage of the characteristics of luminous diodes. Its secret is a special unipolar wire stretched from wall to wall. Where the light comes from is discreetly hidden, giving all the attention to what it is illuminating.

It is possible to replace the light source even with the luminaire assembled.

Luminaire designed also to be powered by ENDLESS conductive tape.

Selection for ADI Design Index 2020

La luce corre sul filo. Un filo quasi impercettibile, sospeso nello spazio. Come un funambolo su una corda sottilissima, la luce arriva ovunque, con leggerezza ed emozione.



Ohm è un progetto elettromeccanico, che sfrutta al massimo le caratteristiche dei diodi luminosi. Il segreto è uno speciale cavo unipolare tirato da parete a parete. La fonte quasi si nasconde, impalpabile e discreta, regalando la scena al soggetto illuminato.

È possibile sostituire l'ottica anche ad apparecchio montato.



Apparecchio illuminante alimentabile anche con il tape conduttivo ENDLESS.

Selezione per ADI Design Index 2020

Remote driver version



Wall/ceiling driver version




Systems / Direct / Indoor

Material Metal - PA
Finish .04 Matt Black

Note Special unipolar wire stretched from wall to wall. Max 4 Spots. Possibility for the luminaire to be powered by ENDLESS conductive tape and by dedicated voltage/current (Max 48V DC - Max 150W - Max 4A). See page: ENDLESS.

Speciale cavo unipolare teso da parete a parete. Max 4 Spot. Alimentabile anche con il tape conduttivo ENDLESS e tensione/corrente dedicata (Max 48V DC - Max 150W - Max 4A). Vedi pagina ENDLESS.




OHM SPOT
 3,2W
 Max 350mA DC
 2700K / 3000K
 CRI >95
 Driver not included
 CE IP20

Matt Black - 2700K
 Matt Black - 3000K

1A3000400.27.20
 1A3000400.30.20

Compulsory accessories / Accessori obbligatori

Installation kits / Kit d'installazione



Tie rods / Tiranti		Not included
Matt White	2 Pieces	1A3020300.00.00




Unipolar wire - 12 m / Cavo unipolare - 12 m		Not included
	Max 60V DC	1A3060000.00.00


Unipolar wire - 24 m / Cavo unipolare - 24 m		Not included
	Max 60V DC	1A3070000.00.00

Unipolar wire - 48 m / Cavo unipolare - 48 m		Not included
	Max 60V DC	1A3080000.00.00

Drivers / Alimentatori




Driver / Alimentatore		Not included
220-240V(100-127V)	350mA/18W(18W)/IP20/DALI - PUSH - 1-10V	1Z0240530.350



Wall/ceiling driver / Alimentatore da parete/soffitto		Not included
Matt White	Input 100-240V - 50/60Hz Output 350mA - 18,5W - IP20 DALI - PUSH - 1-10V	1A3010300.00.07


Other accessories / Altri accessori




Lens / Lente		Not included
Beam - 14°	2700K - CRI >95 - 272lm	OHM SPOT 1A3090000.00.00
	3000K - CRI >95 - 288lm	
Beam - 24°	2700K - CRI >95 - 271lm	OHM SPOT 1A3100000.00.00
	3000K - CRI >95 - 286lm	
Beam - 36°	2700K - CRI >95 - 257lm	OHM SPOT 1A3110000.00.00
	3000K - CRI >95 - 273lm	
Beam - 50°	2700K - CRI >95 - 254lm	OHM SPOT 1A3120000.00.00
	3000K - CRI >95 - 270lm	

Optional accessories / Accessori opzionali


Installation kits / Kit d'installazione




Wall adapter plate / Piastra parete		Not included
Matt White	For mounting on brick masonry walls	1A3030300.00.00




Wire guide / Guidacavo		Not included
Matt Black	1 Piece	1A3040400.00.00




Weight kit for suspension version / Kit pesi per versione a sospensione		Not included
	4 Pieces	1A3050000.00.00




Power base for Endless / Base di alimentazione per Endless		Not included
Matt White		1A3940300.00.00
Matt Black		1A3940400.00.00






Remote driver version



Wall/ceiling driver version



Suspension version



Utopia is a project on the limit state of light,
the research for the minimum dimension necessary for pure and essential lighting.

It represents full flexibility, in both its design and its light control.

The light strip reaches into space, bending,
breaking and drawing abstract, mysterious patterns.
Luminaire designed also to be powered by ENDLESS conductive tape.

Utopia è un progetto sullo stato limite della luce,
alla ricerca della dimensione minima necessaria
per illuminare in modo puro ed essenziale.


Rappresenta la massima flessibilità, sia nel disegno della linea
che nella gestione della luce. Il nastro luminoso si tende nello spazio,
piegandosi, interrompendosi, disegnando grafi astratti e misteriosi.
Apparecchio illuminante alimentabile anche con il tape conduttivo ENDLESS.

Systems / Indirect / Indoor

Material Metal - PVC
Finish .00 Standard

Note Special stainless steel and rubber profile stretched from wall to wall. Available in 6 / 12 m with a single power unit and uniform lighting. Possibility for the luminaire to be powered by ENDLESS conductive tape and by dedicated voltage/current (Max 48V DC - Max 150W - Max 4A). See page: ENDLESS.

Speciale profilo in gomma e acciaio inox teso da parete a parete. Disponibile da 6 / 12 m con un'unica alimentazione e illuminamento uniforme. Possibilità di piegare il profilo nello spazio. Alimentabile anche con il tape conduttivo ENDLESS e tensione/corrente dedicata (Max 48V DC - Max 150W - Max 4A). Vedi pagina ENDLESS.




UTOPIA 6

79W
 24V DC
 2700K - 6079lm / 3000K - 6322lm
 CRI >90
 Driver not included



Standard - 2700K
 Standard - 3000K

1A4250000.27.20
 1A4250000.30.20



UTOPIA 12

125W
 24V DC
 2700K - 10133lm / 3000K - 10538lm
 CRI >90
 Driver not included




Standard - 2700K
 Standard - 3000K


1A4600000.27.20
 1A4600000.30.20

Compulsory accessories / Accessori obbligatori


Drivers / Alimentatori



Driver / Alimentatore				Not included
100-240V	24V/96W/IP67/1-10V	UTOPIA 6	1Z1120540	



Driver / Alimentatore				Not included
100-240V	24V/150W/IP67/1-10V	UTOPIA 12	1Z1120500	




Controller			Not included
	DALI - PUSH - 0/1-10V - TRIAC - IP20		1Z2170010

Optional accessories / Accessori opzionali


Installation kits / Kit d'installazione




Accessory 1 / Accessorio 1			Not included
	Polished Chrome		1A4480100.00.00



Accessory 2 / Accessorio 2			Not included
	Polished Chrome		1A4490100.00.00



1A4480100.00.00 - Example of installation with accessory 1



1A4490100.00.00 - Example of installation with accessory 2



TRACKS - PROFILES / BINARI - PROFILI

BINARIO TRIFASE


/ 2007




Pure line in space.
Our track holds the models Dot, Mira and Spot.

Linea pura nello spazio.
Il nostro binario accoglie i modelli Dot, Mira e Spot.

Power right connector and power left connector installation



Power intermediate connector installation



Systems / Direct / Indoor

Material Metal - Polycarbonate

Finish .03 Matt White


.04 Matt Black

Note Ceiling and wall track system.

Sistema a binario da soffitto e parete.

Compulsory accessories / Accessori obbligatori

Installation kits / Kit d'installazione



Track 1 m / Binario 1 m		Not included
Matt White	1A2800300.01.00	
Matt Black	1A2800400.01.00	

Track 2 m / Binario 2 m		Not included
Matt White	1A2800300.02.00	
Matt Black	1A2800400.02.00	

Track 3 m / Binario 3 m		Not included
Matt White	1A2800300.03.00	
Matt Black	1A2800400.03.00	



End cap / Tappo di chiusura		Not included
Matt White	1A2800300.07.00	
Matt Black	1A2800400.07.00	

Connectors / Connettori



Power right connector / Elemento di alimentazione destro		Not included
Matt White	1A2800300.13.00	
Matt Black	1A2800400.13.00	



Power left connector / Elemento di alimentazione sinistro		Not included
Matt White	1A2800300.12.00	
Matt Black	1A2800400.12.00	



Power intermediate connector / Elemento di alimentazione intermedio		Not included
Matt White	1A2800300.16.00	
Matt Black	1A2800400.16.00	

Optional accessories / Accessori opzionali

Installation kits / Kit d'installazione



Linear connector / Connettore lineare		Not included
Matt White	1A2800300.11.00	
Matt Black	1A2800400.11.00	



Internal L connector / Connettore L interno		Not included
Matt Black	1A2800400.09.00	
Matt White	1A2800300.09.00	



External L connector / Connettore L esterno		Not included
Matt White	1A2800300.08.00	
Matt Black	1A2800400.08.00	



Right T connector / Connettore T destro		Not included
Matt White	1A2800300.14.00	
Matt Black	1A2800400.14.00	



Left T connector / Connettore T sinistro		Not included
Matt White	1A2800300.10.00	
Matt Black	1A2800400.10.00	



X connector / Connettore X		Not included
Matt White	1A2800300.15.00	
Matt Black	1A2800400.15.00	



Adjustable suspension cable / Cavo di sospensione regolabile		Not included
Length 1500 mm	1A2800000.04.00	

Adjustable suspension cable / Cavo di sospensione regolabile		Not included
Length 3000 mm	1A2800000.05.00	

Adjustable suspension cable / Cavo di sospensione regolabile		Not included
Length 5000 mm	1A2800000.06.00	




Cutting tool / Tronchese per taglio		Not included
	1A2800300.17.00	



Compulsory accessories / Accessori obbligatori

Luminaires / Corpi illuminanti




DOT BINARIO

13W
220-240V - 50/60Hz
2700K / 3000K
CRI >97
Driver integrated
DALI

CE IP20

Matt White - 2700K - DALI
Matt White - 3000K - DALI
Matt Black - 2700K - DALI
Matt Black - 3000K - DALI

1A2290300.27.01
1A2290300.30.01
1A2290400.27.01
1A2290400.30.01




DOT BINARIO 51

Max 10W
100-240V - 50/60Hz
ON/OFF
Bulb not included

CE IP20

Matt White - ON/OFF
Matt Black - ON/OFF

1A3710300.00.00
1A3710400.00.00




MIRA BINARIO

8W
220-240V - 50/60Hz
2700K - 327lm / 3000K - 352lm
CRI >90
Driver integrated
DALI

CE IP20

Matt White - 2700K - DALI
Matt White - 3000K - DALI
Matt Black - 2700K - DALI
Matt Black - 3000K - DALI

1A0490300.27.01
1A0490300.30.01
1A0490400.27.01
1A0490400.30.01



SPOT BINARIO

21W
220-240V - 50/60Hz
CRI >90
Driver integrated
DALI
LED Module not included

CE IP20

Matt White - DALI
Matt Black - DALI

1A0280300.00.01
1A0280400.00.01


Compulsory accessories / Accessori obbligatori

Other accessories / Altri accessori




Lens / Lente	Not included		
Beam - 14°	2700K - CRI >97 - 983lm	DOT BINARIO	1A3090000.00.00
	3000K - CRI >97 - 1038lm		
Beam - 24°	2700K - CRI >97 - 943lm	DOT BINARIO	1A3100000.00.00
	3000K - CRI >97 - 996lm		
Beam - 36°	2700K - CRI >97 - 955lm	DOT BINARIO	1A3110000.00.00
	3000K - CRI >97 - 1005lm		
Beam - 50°	2700K - CRI >97 - 965lm	DOT BINARIO	1A3120000.00.00
	3000K - CRI >97 - 1016lm		


LED modules / Moduli LED



DG111 LED module / Modulo LED DG111	Not included		
16,7W - 15° - 500mA DC	SPOT BINARIO	1A4700000.27.20	
2700K - 1648lm - CRI >90			
Energy Efficiency F - Dimmable			
16,7W - 15° - 500mA DC		1A4700000.30.20	
3000K - 1682lm - CRI >90			
Energy Efficiency F - Dimmable			




DG111 LED module / Modulo LED DG111	Not included		
16,7W - 22° - 500mA DC	SPOT BINARIO	1A3890000.27.20	
2700K - 1859lm - CRI >90			
Energy Efficiency F - Dimmable			
16,7W - 22° - 500mA DC		1A3890000.30.20	
3000K - 1945lm - CRI >90			
Energy Efficiency F - Dimmable			




DG111 LED module / Modulo LED DG111	Not included		
16,7W - 36° - 500mA DC	SPOT BINARIO	1A3900000.27.20	
2700K - 1808lm - CRI >90			
Energy Efficiency F - Dimmable			
16,7W - 36° - 500mA DC		1A3900000.30.20	
3000K - 1890lm - CRI >90			
Energy Efficiency F - Dimmable			

Optional accessories / Accessori opzionali


Other accessories / Altri accessori




Accessory holder + Honeycomb louvre / Porta accessori + Frangiluce nido d'ape	Not included		
	DOT BINARIO	1X0080400.01.00	




Elliptical filter / Filtro ellittico	Not included		
Standard	Compulsory with 1X0080400.01.00	DOT BINARIO	1X0080000.02.00



Blue filter / Filtro blu	Not included		
Standard	Compulsory with 1X0080400.01.00	DOT BINARIO	1X0080000.03.00






Red filter / Filtro rosso	Not included		
Standard	Compulsory with 1X0080400.01.00	DOT BINARIO	1X0080000.04.00






Yellow filter / Filtro giallo	Not included		
Standard	Compulsory with 1X0080400.01.00	DOT BINARIO	1X0080000.05.00

Optional accessories / Accessori opzionali

Bulbs / Lampadine









	LED - GU10 - PAR16			Not included
	220-240V - 5,5W - 25° 3000K - 375lm - CRI >97 Energy Efficiency G - Dimmable	DOT BINARIO 51	1Y0330500	
	LED SORAA - GU10 - MR16			Not included
	230V - 7,5W - 10° 2700K - 390lm - CRI >95 Energy Efficiency G - Dimmable	DOT BINARIO 51	1Y1580210	
	LED SORAA - GU10 - MR16			Not included
	230V - 7,5W - 10° 3000K - 410lm - CRI >95 Energy Efficiency G - Dimmable	DOT BINARIO 51	1Y1580010	

Other accessories / Altri accessori


	Darklight			Not included
	LED SORAA - GU10 - MR16	DOT BINARIO 51	1Y1580040	
	25° beam filter / Filtro fascio 25°			Not included
	LED SORAA - GU10 - MR16	DOT BINARIO 51	1Y1580020	
	36° beam filter / Filtro fascio 36°			Not included
	LED SORAA - GU10 - MR16	DOT BINARIO 51	1Y1580030	

Optional accessories / Accessori opzionali

Other accessories / Altri accessori



	Accessory holder + Soft filter + Honeycomb louvre / Porta accessori + Filtro soft + Frangiluce nido d'ape			Not included
	Matt Black	SPOT BINARIO	1X0070400.04.00	
	Accessory holder + Elliptical filter / Porta accessori + Filtro ellittico			Not included
	Matt Black	SPOT BINARIO	1X0070400.05.00	
	Blue filter / Filtro blu			Not included
	Standard	Compulsory with 1X0070400.04.00 / 1X0070400.05.00	SPOT BINARIO	1X0070000.06.00
	Red filter / Filtro rosso			Not included
	Standard	Compulsory with 1X0070400.04.00 / 1X0070400.05.00	SPOT BINARIO	1X0070000.07.00
	Yellow filter / Filtro giallo			Not included
	Standard	Compulsory with 1X0070400.04.00 / 1X0070400.05.00	SPOT BINARIO	1X0070000.08.00
	Horizontal directional fins / Alette direzionali			Not included
	Matt Black	SPOT BINARIO	1X0070400.01.00	
	Cylindrical screen / Schermo cilindrico			Not included
	Matt Black	SPOT BINARIO	1X0070400.02.00	
	Cone 45° / Cono 45°			Not included
	Matt Black	SPOT BINARIO	1X0070400.03.00	





A minimal track system with tiny lights, small hummingbirds that perch where needed.
Luminaire designed also to be powered by ENDLESS system.

Un sistema a binario ridotto al minimo, con minuscoli corpi luminosi,
piccoli Colibri che si posano dove necessario.
Apparecchio illuminante alimentabile anche con il sistema ENDLESS.

Layout example of
wall and ceiling versionLayout example of
recessed version

Systems / Direct / Indoor

Material

Finish .04 Matt Black


Note

Ceiling and wall track system operating at 48V DC. Possibility for the luminaire to be powered by ENDLESS system (Max 48V DC - Max 150W - Max 4A) and to be used, on the same circuit, with the ENDLESS models. See page: ENDLESS.

Sistema a binario da soffitto e parete funzionante a 48V DC. Alimentabile anche con il sistema ENDLESS (Max 48V DC - Max 150W - Max 4A) ed utilizzabile, sullo stesso circuito, con i modelli ENDLESS. Vedi pagina ENDLESS.

Compulsory accessories / Accessori obbligatori


Installation kits for wall and ceiling track / Kit d'installazione per binario da parete e soffitto



Wall and ceiling track - 1 m / Binario da parete e soffitto - 1 m		Not included
Matt White	1A4170300.01.00	
Matt Black	1A4170400.01.00	

Wall and ceiling track - 2 m / Binario da parete e soffitto - 2 m		Not included
Matt White	1A4170300.02.00	
Matt Black	1A4170400.02.00	

Wall and ceiling track - 3 m / Binario da parete e soffitto - 3 m		Not included
Matt White	1A4170300.03.00	
Matt Black	1A4170400.03.00	




Power connector / Elemento di alimentazione		Not included
Matt White	1A4170300.04.00	
Matt Black	1A4170400.04.00	



End cap / Tappo di chiusura		Not included
Matt White	1A4170300.07.00	
Matt Black	1A4170400.07.00	

Compulsory accessories / Accessori obbligatori

Installation kits for recessed track / Kit d'installazione per binario da incasso



Recessed wall and ceiling track - 1 m / Binario da parete e soffitto da incasso - 1 m		Not included
Matt Black		1A4180400.01.00

Recessed wall and ceiling track - 2 m / Binario da parete e soffitto da incasso - 2 m		Not included
Matt Black		1A4180400.02.00

Recessed wall and ceiling track - 3 m / Binario da parete e soffitto da incasso - 3 m		Not included
Matt Black		1A4180400.03.00




Power connector / Elemento di alimentazione		Not included
Matt Black	For recessed track	1A4180400.04.00




End cap / Tappo di chiusura		Not included
Matt Black	For recessed track	1A4180400.05.00

Drivers / Alimentatori



Driver / Alimentatore		Not included
	Input 100-240V - 50/60Hz Output 48V - 60W - IP20 - DALI	1A4170000.19.00







Driver / Alimentatore		Not included
	Input 100-240V - 50/60Hz Output 48V - 150W - IP20 - DALI	1A2810000.11.00





Optional accessories / Accessori opzionali

Installation kits for wall and ceiling track / Kit d'installazione per binario da parete e soffitto






	Corner joint cover H / Coprigiunto angolare H		Not included
	Matt White	For wall and ceiling track	1A4170300.05.00
	Matt Black	For wall and ceiling track	1A4170400.05.00
	Corner joint cover V / Coprigiunto angolare V		Not included
	Matt White	For wall and ceiling track	1A4170300.06.00
	Matt Black	For wall and ceiling track	1A4170400.06.00
	Cover - 3 m / Copertura - 3 m		Not included
	Matt White	For wall and ceiling track	1A4170300.08.00
	Matt Black	For wall and ceiling track	1A4170400.08.00
	Endless connector / Connettore Endless		Not included
	Standard	For wall and ceiling track	1A4170000.20.00

Installation kits for recessed track / Kit d'installazione per binario da incasso

	Cover - 3 m / Copertura - 3 m		Not included
	Matt White	For recessed track	1A4180300.08.00
	Matt Black	For recessed track	1A4180400.08.00
	Template / Dima		Not included
	Standard	For recessed track	1A4180000.09.00


Optional accessories / Accessori opzionali

Installation kits / Kit d'installazione

	L connector / Connettore a L		Not included
	Matt Black		1A4170400.13.00
	Ceiling wall connector / Connettore soffitto-parete		Not included
	Matt Black		1A4170400.14.00
	Flexible joint / Giunto flessibile		Not included
	Matt Black		1A4170400.15.00
	Linear connector / Connettore lineare		Not included
	Matt Black		1A4170400.16.00
	Locking tool / Strumento per bloccaggio		Not included
	Standard		1A4170000.17.00

Compulsory accessories / Accessori obbligatori

Luminaires / Corpi illuminanti


**COLIBRÌ 18 - 15°**

2W - 0,07A
48V DC
2700K - 81lm / 3000K - 84lm
CRI >90
Beam 15°
Driver integrated
DALI

CE IP20

Matt Black - 2700K - DALI
Matt Black - 3000K - DALI

1A4260400.27.01
1A4260400.30.01


**COLIBRÌ 18 - 25°**

2W - 0,07A
48V DC
2700K - 79lm / 3000K - 81lm
CRI >90
Beam 25°
Driver integrated
DALI

CE IP20

Matt Black - 2700K - DALI
Matt Black - 3000K - DALI

1A4270400.27.01
1A4270400.30.01


**COLIBRÌ 28 - BEAM 15°**

4W - 0,14A
48V DC
2700K - 147lm / 3000K - 151lm
CRI >90
Beam 15°
Driver integrated
DALI

CE IP20

Matt Black - 2700K - DALI
Matt Black - 3000K - DALI

1A4280400.27.01
1A4280400.30.01

**COLIBRÌ 28 - BEAM 25°**

5W - 0,14A
48V DC
2700K - 250lm / 3000K - 258lm
CRI >90
Beam 25°
Driver integrated
DALI

CE IP20

Matt Black - 2700K - DALI
Matt Black - 3000K - DALI


1A4290400.27.01
1A4290400.30.01



Plasterboard track for recessed installation.
It is designed for use with state-of-the-art LED modules
to create a wide range of light beams.

Binario per installazione da incasso per cartongesso.
Ideato per utilizzare moduli a LED di ultima generazione
ed avere un'ampia disponibilità di fasci luminosi.

Layout example



Systems / Direct / Indoor

Material Metal - Polycarbonate


Finish .03 Matt White .04 Matt Black

Note Recessed track system operating at 48V DC.

Sistema a binario da incasso funzionante a 48V DC.

Compulsory accessories / Accessori obbligatori

Installation kits / Kit d'installazione



Plasterboard track 12,5 mm / Binario per cartongesso 12,5 mm		Not included
Matt Black	48V DC - Max 15A Length 2000 mm Cut-out 2000x26 mm	1A2810400.01.00



Power connector / Elemento di alimentazione		Not included
Matt Black	Output 48V - Max 15A	1A2810400.02.00







End cap for power connector / Tappo di chiusura per alimentazione		Not included
Matt Black		1A2810400.03.00



End cap / Tappo di chiusura		Not included
Matt Black		1A2810400.04.00







Compulsory accessories / Accessori obbligatori

Drivers / Alimentatori

	Driver / Alimentatore 100-240V 48V/150W/IP67/1-10V	Not included 1Z1120250
	Driver / Alimentatore 100-240V 48V/320W/IP67/1-10V	Not included 1Z1120380
	Driver / Alimentatore Input 100-240V - 50/60Hz Output 48V - 150W - IP20 - DALI	Not included 1A2810000.11.00
	Driver / Alimentatore Input 100-240V - 50/60Hz Output 48V - 320W - IP20 - DALI	Not included 1A2810000.12.00


Optional accessories / Accessori opzionali

Installation kits / Kit d'installazione

	Linear connector / Connettore lineare Matt Black Output 48V - Max 15A	Not included 1A2810400.05.00
	Reinforcing bracket / Staffa di rinforzo Matt Black	Not included 1A2810400.06.00
	Clamp with M6 grippe / Morsetto con pinza M6	Not included 1A2810000.07.00
	Suspension set / Set sospensione	Not included 1A2810000.08.00
	Plaster installation guard / Protezione per installazione cartongesso Length 2000 mm	Not included 1A2810000.09.00
	Cutting tool / Tronchese per taglio	Not included 1A2810000.10.00

Compulsory accessories / Accessori obbligatori

Luminaires / Corpi illuminanti



DOT FRAMELESS

13W
48V DC
2700K / 3000K
CRI >97
Driver integrated
DALI



Matt White - 2700K - DALI
Matt White - 3000K - DALI
Matt Black - 2700K - DALI
Matt Black - 3000K - DALI

1A0090300.27.01
1A0090300.30.01
1A0090400.27.01
1A0090400.30.01


Other accessories / Altri accessori



Lens / Lente		Not included	
Beam - 14°	2700K - CRI >97 - 983lm	DOT FRAMELESS	1A3090000.00.00
	3000K - CRI >97 - 1038lm		
Beam - 24°	2700K - CRI >97 - 943lm	DOT FRAMELESS	1A3100000.00.00
	3000K - CRI >97 - 996lm		
Beam - 36°	2700K - CRI >97 - 955lm	DOT FRAMELESS	1A3110000.00.00
	3000K - CRI >97 - 1005lm		
Beam - 50°	2700K - CRI >97 - 965lm	DOT FRAMELESS	1A3120000.00.00
	3000K - CRI >97 - 1016lm		

Optional accessories / Accessori opzionali

Other accessories / Altri accessori



Accessory holder + Honeycomb louvre / Porta accessori + Frangiluce nido d'ape		Not included	
	DOT FRAMELESS		1X0080400.01.00




Elliptical filter / Filtro ellittico		Not included	
Standard	Compulsory with 1X0080400.01.00	DOT FRAMELESS	1X0080000.02.00




Blue filter / Filtro blu		Not included	
Standard	Compulsory with 1X0080400.01.00	DOT FRAMELESS	1X0080000.03.00



Red filter / Filtro rosso		Not included	
Standard	Compulsory with 1X0080400.01.00	DOT FRAMELESS	1X0080000.04.00



Yellow filter / Filtro giallo		Not included	
Standard	Compulsory with 1X0080400.01.00	DOT FRAMELESS	1X0080000.05.00



Profiles designed to create projects with continuous light.

Profili pensati per realizzare progetti di luce continua.


Systems / Direct / Indoor

Material Metal
Finish .00 Standard

Note Recessed profile with continuous light. *Profilo da incasso a luce continua.*

Compulsory accessories / Accessori obbligatori

Installation kits / Kit d'installazione



Aluminium profile 2 m / Profilo in alluminio 2 m		Not included
Standard	With opal cover	1A4970000.01.00



Cap / Tappo		Not included
Standard		1A4970000.02.00



Fixing spring / Molla di fissaggio		Not included
Standard		1A4970000.03.00


Compulsory accessories / Accessori obbligatori

LED modules / Moduli LED




Strip LED - 5 m - IP20		Not included
	Input 24V DC - 63W - IP20 2700K - 6200lm - CRI >94	1A5010000.27.20
	Input 24V DC - 63W - IP20 3000K - 6900lm - CRI >94	1A5010000.30.20


Drivers / Alimentatori




Driver / Alimentatore		Not included
100-240V	24V/80W/IP20/ON/OFF	1Z1120440



Driver / Alimentatore		Not included
100-240V	24V/96W/IP67/1-10V	1Z1120540



Driver / Alimentatore		Not included
100-240V	24V/150W/IP67/1-10V	1Z1120500



Controller		Not included
	DALI - PUSH - 0/1-10V - TRIAC - IP20	1Z2170010




Systems / Direct / Indoor

Material Metal
 Finish .00 Standard

Note Profile with continuous light. *Profilo a luce continua.*

Compulsory accessories / Accessori obbligatori

Installation kits / Kit d'installazione



Aluminium profile 2 m / Profilo in alluminio 2 m		Not included
Standard	With opal cover	1A4970000.04.00



Cap / Tappo		Not included
Standard		1A4970000.05.00



Fixing spring / Molla di fissaggio		Not included
Standard		1A4970000.06.00


Compulsory accessories / Accessori obbligatori

LED modules / Moduli LED




Strip LED - 5 m - IP20		Not included
	Input 24V DC - 63W - IP20 2700K - 6200lm - CRI >94	1A5010000.27.20
	Input 24V DC - 63W - IP20 3000K - 6900lm - CRI >94	1A5010000.30.20


Drivers / Alimentatori




Driver / Alimentatore		Not included
100-240V	24V/80W/IP20/ON/OFF	1Z1120440



Driver / Alimentatore		Not included
100-240V	24V/96W/IP67/1-10V	1Z1120540



Driver / Alimentatore		Not included
100-240V	24V/150W/IP67/1-10V	1Z1120500



Controller		Not included
	DALI - PUSH - 0/1-10V - TRIAC - IP20	1Z2170010



Systems / Direct / Indoor


Material Metal
Finish .00 Standard

Note Recessed profile with continuous light.


Profilo da incasso a luce continua.

Compulsory accessories / Accessori obbligatori

Installation kits / Kit d'installazione




Aluminium profile 2 m / Profilo in alluminio 2 m Not included
Standard 1A4970000.07.00



Opal cover 2 m / Diffusore opale 2 m Not included
Standard 1A4970000.08.00




Transparent cover 2 m / Diffusore trasparente 2 m Not included
Standard 1A4970000.09.00




Satin cover 2 m / Diffusore satinato 2 m Not included
Standard 1A4970000.10.00



Cap / Tappo Not included
Standard 1A4970000.11.00



Adhesive 1 m / Adesivo 1 m Not included
Standard 1A4970000.12.00



Adhesive magnet 1 m / Calamita adesiva 1 m Not included
Standard 1A4970000.13.00

Compulsory accessories / Accessori obbligatori

LED modules / Moduli LED



Strip LED - 5 m - IP20 Not included
Input 24V DC - 63W - IP20 1A5010000.27.20
2700K - 6200lm - CRI >94
Input 24V DC - 63W - IP20 1A5010000.30.20
3000K - 6900lm - CRI >94



Strip LED - 5 m - IP20 Not included
Input 24V DC - 72W - IP20 1A4980000.27.20
2700K - 7100lm - CRI >80
Input 24V DC - 72W - IP20 1A4980000.30.20
3000K - 7875lm - CRI >80




Strip LED - 5 m - IP20 Not included
Input 24V DC - 96W - IP20 1A4990000.27.20
2700K - 10500lm - CRI >80
Input 24V DC - 96W - IP20 1A4990000.30.20
3000K - 11700lm - CRI >80




Strip LED - 5 m - IP65 Not included
Input 24V DC - 72W - IP65 1A5000000.27.20
2700K - 7100lm - CRI >82
Input 24V DC - 72W - IP65 1A5000000.30.20
3000K - 7875lm - CRI >82


Drivers / Alimentatori




Driver / Alimentatore Not included
100-240V 24V/80W/IP20/ON/OFF 1Z1120440



Driver / Alimentatore Not included
100-240V 24V/96W/IP67/1-10V 1Z1120540



Driver / Alimentatore Not included
100-240V 24V/150W/IP67/1-10V 1Z1120500



Controller Not included
DALI - PUSH - 0/1-10V - TRIAC - IP20 1Z2170010




Systems / Direct / Indoor

Material Metal
Finish .00 Standard


Note Recessed profile with continuous light. *Profilo da incasso a luce continua.*

Compulsory accessories / Accessori obbligatori


Installation kits / Kit d'installazione




Aluminium profile 2 m / Profilo in alluminio 2 m Not included
Standard 1A4970000.14.00



Opal cover 2 m / Diffusore opale 2 m Not included
Standard 1A4970000.08.00



Transparent cover 2 m / Diffusore trasparente 2 m Not included
Standard 1A4970000.09.00




Satin cover 2 m / Diffusore satinato 2 m Not included
Standard 1A4970000.10.00



Cap / Tappo Not included
Standard 1A4970000.15.00



Fixing spring / Molla di fissaggio Not included
Standard 1A4970000.16.00



Formwork kit 2 m / Kit cassaforma 2 m Not included
Standard 1A4970000.17.00

Compulsory accessories / Accessori obbligatori

LED modules / Moduli LED



Strip LED - 5 m - IP20 Not included
Input 24V DC - 63W - IP20 1A5010000.27.20
2700K - 6200lm - CRI >94
Input 24V DC - 63W - IP20 1A5010000.30.20
3000K - 6900lm - CRI >94



Strip LED - 5 m - IP20 Not included
Input 24V DC - 72W - IP20 1A4980000.27.20
2700K - 7100lm - CRI >80
Input 24V DC - 72W - IP20 1A4980000.30.20
3000K - 7875lm - CRI >80




Strip LED - 5 m - IP20 Not included
Input 24V DC - 96W - IP20 1A4990000.27.20
2700K - 10500lm - CRI >80
Input 24V DC - 96W - IP20 1A4990000.30.20
3000K - 11700lm - CRI >80




Strip LED - 5 m - IP65 Not included
Input 24V DC - 72W - IP65 1A5000000.27.20
2700K - 7100lm - CRI >82
Input 24V DC - 72W - IP65 1A5000000.30.20
3000K - 7875lm - CRI >82


Drivers / Alimentatori




Driver / Alimentatore Not included
100-240V 24V/80W/IP20/ON/OFF 1Z1120440



Driver / Alimentatore Not included
100-240V 24V/96W/IP67/1-10V 1Z1120540



Driver / Alimentatore Not included
100-240V 24V/150W/IP67/1-10V 1Z1120500



Controller Not included
DALI - PUSH - 0/1-10V - TRIAC - IP20 1Z2170010



Systems / Direct / Indoor


Material Metal
Finish .00 Standard

Note Recessed profile with continuous light.

Profilo da incasso a luce continua.

Compulsory accessories / Accessori obbligatori

Installation kits / Kit d'installazione



Aluminium profile 2 m / Profilo in alluminio 2 m	Not included
Standard	1A4970000.18.00



Opal cover 2 m / Diffusore opale 2 m	Not included
Standard	1A4970000.19.00

Compulsory accessories / Accessori obbligatori

LED modules / Moduli LED



Strip LED - 5 m - IP20	Not included
Input 24V DC - 63W - IP20 2700K - 6200lm - CRI >94	1A5010000.27.20
Input 24V DC - 63W - IP20 3000K - 6900lm - CRI >94	1A5010000.30.20



Strip LED - 5 m - IP20	Not included
Input 24V DC - 72W - IP20 2700K - 7100lm - CRI >80	1A4980000.27.20
Input 24V DC - 72W - IP20 3000K - 7875lm - CRI >80	1A4980000.30.20




Strip LED - 5 m - IP20	Not included
Input 24V DC - 96W - IP20 2700K - 10500lm - CRI >80	1A4990000.27.20
Input 24V DC - 96W - IP20 3000K - 11700lm - CRI >80	1A4990000.30.20




Strip LED - 5 m - IP65	Not included
Input 24V DC - 72W - IP65 2700K - 7100lm - CRI >82	1A5000000.27.20
Input 24V DC - 72W - IP65 3000K - 7875lm - CRI >82	1A5000000.30.20


Drivers / Alimentatori




Driver / Alimentatore	Not included
100-240V 24V/80W/IP20/ON/OFF	1Z1120440




Driver / Alimentatore	Not included
100-240V 24V/96W/IP67/1-10V	1Z1120540



Driver / Alimentatore	Not included
100-240V 24V/150W/IP67/1-10V	1Z1120500



Controller	Not included
DALI - PUSH - 0/1-10V - TRIAC - IP20	1Z2170010



OUTDOOR / ESTERNO



BELLADINOTTE

Maurizio Mancini / 2012

The magic of the mirror brought into the garden.
A study of camouflage. The reflective surface is used as a tool
to camouflage and hide the machine to create light.
The reflection of the environment makes the luminaire invisible.

La magia dello specchio portata in giardino.
Un lavoro sulla mimetica. La superficie riflettente utilizzata come strumento
per mimetizzare e nascondere la macchina per fare luce.
La riflessione del contesto ambientale rende invisibile il corpo illuminante.


BELLADINOTTE

Maurizio Mancini / 2012

Floor / Indirect / Outdoor

Material Metal
Finish .00 Standard

Note Outdoor lamp with spike. Adjustable along the vertical axis. Plane with mirror finish. Matt green mirror finish rear plane. Black cable (5 m). *Apparecchio illuminante da esterno a picchetto. Orientabile lungo l'asse verticale. Piano con finitura a specchio. Retro del piano a specchio verde opaco. Cavo nero (5 m).*



BELLADINOTTE


2x4,2W
 24V DC
 2700K - 262lm / 3000K - 282lm
 CRI >90
 Driver not included
 CE IP67

Standard - 2700K
 Standard - 3000K

1A3560000.27.20
 1A3560000.30.20

Compulsory accessories / Accessori obbligatori

Drivers / Alimentatori



Driver / Alimentatore		Not included
110-240V	24V/25W/IP67/ON/OFF	1Z1120620

Optional accessories / Accessori opzionali

Installation kits / Kit d'installazione



Driver connector IP68 / Connettore driver IP68		Included
	1 Piece	1A1660000.00.00





BUBKA

Daniele Sprega / 2014

A perfect tool to make outdoor light.
The light as a tool for guiding people along a path.


Un perfetto utensile per fare la luce fuori.
La luce come strumento per condurre le persone lungo i percorsi.

Floor / Direct / Outdoor

Material AISI 316L Stainless Steel - Metal

Finish .00 Standard

Note Outdoor floor luminaire. Adjustable along the vertical axis. AISI 316L *Apparecchio illuminante da esterno da terra. Orientabile lungo l'asse verticale. Stelo in inox AISI 316L. Cavo nero (7 m).*



BUBKA

8,4W

Max 700mA DC

2700K - 639lm / 3000K - 639lm

CRI >90

Driver not included

CE IP65

Standard - 2700K


Standard - 3000K

1A3600000.27.20

1A3600000.30.20

Compulsory accessories / Accessori obbligatori

Drivers / Alimentatori



Driver / Alimentatore

220-240V(100-127V) 700mA/30W(15W)/IP68/ON/OFF

1Z0241110

Not included

Optional accessories / Accessori opzionali

Installation kits / Kit d'installazione




Driver connector IP68 / Connettore driver IP68

Included

1 Piece

1A1660000.00.00



Anchoring bolt / Tirafondo


Not included

Cut-out Ø 250 mm

Minimum space for mounting 350 mm

1A3620000.00.00

Lighting modules / Corpi illuminanti



Additional LED head / Testa LED supplementare

Not included

Matt Black

Max 700mA DC - 8,4W

2700K - 639lm - CRI >90

1A3610400.27.20

Max 700mA DC - 8,4W

3000K - 639lm - CRI >90

1A3610400.30.20



BUBKA BOLLARD

Daniele Sprega / 2021

A perfect tool to make outdoor light.
The light as a tool for guiding people along a path.

Un perfetto utensile per fare la luce fuori.
La luce come strumento per condurre le persone lungo i percorsi.


BUBKA BOLLARD

Daniele Sprega / 2021

Floor / Direct / Outdoor

Material AISI 316L Stainless Steel - Metal
Finish .00 Standard

Note Outdoor floor luminaire. Adjustable along the vertical axis. *Apparecchio illuminante da esterno da terra. Orientabile lungo l'asse verticale. Stelo in inox AISI 316L. Cavo nero (9 m).*



BUBKA BOLLARD


8,4W
 Max 700mA DC
 2700K - 350lm / 3000K - 350lm
 CRI >90
 Driver not included
 CE IP65

Standard - 2700K
 Standard - 3000K

1A1440000.27.20
 1A1440000.30.20

Compulsory accessories / Accessori obbligatori

Drivers / Alimentatori



Driver / Alimentatore

220-240V(100-127V) 350mA/17W(15W)/IP68/ON/OFF

1Z0240880

Not included

Daniele Sprega / 2021

BUBKA BOLLARD

Optional accessories / Accessori opzionali

Installation kits / Kit d'installazione




Driver connector IP68 / Connettore driver IP68

1 Piece

1A1660000.00.00

Included




Anchoring bolt / Tirafondo

Cut-out Ø 250 mm
 Minimum space for mounting 350 mm

1A3620000.00.00

Not included

Lighting modules / Corpi illuminanti



Additional LED head / Testa LED supplementare

Matt Black

Max 700mA DC - 8,4W
 2700K - 639lm - CRI >90

1A3610400.27.20

Not included

Max 700mA DC - 8,4W
 3000K - 639lm - CRI >90

1A3610400.30.20



A small black dot reveals its function only when necessary.
For us the secret of light lies not in its shape, or in some technical virtuosity,
but in the choice and assumption of a method,
the method of amazement and memory.

Un piccolo punto nero svela la sua funzione solo quando necessario.
Per noi il segreto della luce non è nella forma, o in alcuni virtuosismi produttivi,
ma nella scelta e nell'assunzione di un metodo,
il metodo dello stupore e della memoria.

BUIO - TRIMLESS


Maurici Ginés / 2023

Recessed / Direct / Outdoor

Material

Finish .04 Matt Black

Note Outdoor luminaire. Available with transparent or black glass. Black cable (1 m). *Apparecchio illuminante da esterno. Disponibile con vetro trasparente o nero. Cavo nero (1 m).*




BUIO TRIMLESS - 13°

Black filter
6,2W
24V DC
2700K - 120lm / 3000K - 123lm
CRI >90
Beam 13°
UGR <19
Driver not included
CE IP67

Matt Black - 2700K
Matt Black - 3000K

1A5200400.27.20
1A5200400.30.20



BUIO TRIMLESS - 25°


Black filter
6,2W
24V DC
2700K - 150lm / 3000K - 155lm
CRI >90
Beam 25°
UGR <19
Driver not included
CE IP67

Matt Black - 2700K
Matt Black - 3000K

1A5220400.27.20
1A5220400.30.20

Maurici Ginés / 2023

BUIO - TRIMLESS




BUIO TRIMLESS - 32°

Black filter
6,2W
24V DC
2700K - 140lm / 3000K - 144lm
CRI >90
Beam 32°
UGR <19
Driver not included
CE IP67

Matt Black - 2700K
Matt Black - 3000K

1A5210400.27.20
1A5210400.30.20




BUIO TRIMLESS ELLIPTICAL

Black filter
6,2W
24V DC
2700K - 132lm / 3000K - 136lm
CRI >90
UGR <19
Driver not included
CE IP67

Matt Black - 2700K
Matt Black - 3000K

1A5230400.27.20
1A5230400.30.20




BUIO TRIMLESS - 13°

Transparent filter
 6,2W
 24V DC
 2700K - 239lm / 3000K - 246lm
 CRI >90
 Beam 13°
 UGR <19
 Driver not included



Matt Black - 2700K
 Matt Black - 3000K

1A5240400.27.20
 1A5240400.30.20




BUIO TRIMLESS - 25°

Transparent filter
 6,2W
 24V DC
 2700K - 300lm / 3000K - 309lm
 CRI >90
 Beam 25°
 UGR <19
 Driver not included



Matt Black - 2700K
 Matt Black - 3000K

1A5260400.27.20
 1A5260400.30.20




BUIO TRIMLESS - 32°

Transparent filter
 6,2W
 24V DC
 2700K - 279lm / 3000K - 288lm
 CRI >90
 Beam 32°
 UGR <19
 Driver not included



Matt Black - 2700K
 Matt Black - 3000K

1A5250400.27.20
 1A5250400.30.20



BUIO TRIMLESS ELLIPTICAL

Transparent filter
 6,2W
 24V DC
 2700K - 263lm / 3000K - 271lm
 CRI >90
 UGR <19
 Driver not included




Matt Black - 2700K
 Matt Black - 3000K

1A5270400.27.20
 1A5270400.30.20


Compulsory accessories / Accessori obbligatori

Installation kits / Kit d'installazione



Installation box / Cassaforma	Not included
Standard	1A5280000.00.00

Drivers / Alimentatori



Driver / Alimentatore	Not included
110-240V 24V/25W/IP67/ON/OFF	1Z1120620

BUIO - TRIM


Maurici Ginés / 2023

Recessed / Direct / Outdoor

Material

Finish .04 Matt Black

Note Outdoor luminaire. Available with transparent or black glass. Black cable (1 m). *Apparecchio illuminante da esterno. Disponibile con vetro trasparente o nero. Cavo nero (1 m).*




BUIO TRIM - 13°

Black filter
6,2W
24V DC
2700K - 120lm / 3000K - 123lm
CRI >90
Beam 13°
UGR <19
Driver not included
CE IP67

Matt Black - 2700K
Matt Black - 3000K

1A5120400.27.20
1A5120400.30.20



BUIO TRIM - 25°


Black filter
6,2W
24V DC
2700K - 300lm / 3000K - 155lm
CRI >90
Beam 25°
UGR <19
Driver not included
CE IP67

Matt Black - 2700K
Matt Black - 3000K

1A5140400.27.20
1A5140400.30.20

Maurici Ginés / 2023

BUIO - TRIM




BUIO TRIM - 32°

Black filter
6,2W
24V DC
2700K - 140lm / 3000K - 144lm
CRI >90
Beam 32°
UGR <19
Driver not included
CE IP67

Matt Black - 2700K
Matt Black - 3000K

1A5130400.27.20
1A5130400.30.20




BUIO TRIM ELLIPTICAL

Black filter
6,2W
24V DC
2700K - 132lm / 3000K - 136lm
CRI >90
UGR <19
Driver not included
CE IP67

Matt Black - 2700K
Matt Black - 3000K

1A5150400.27.20
1A5150400.30.20




BUJO TRIM - 13°

Transparent filter
 6,2W
 24V DC
 2700K - 239lm / 3000K - 246lm
 CRI >90
 Beam 13°
 UGR <19
 Driver not included



Matt Black - 2700K
 Matt Black - 3000K

1A5160400.27.20
 1A5160400.30.20




BUJO TRIM - 25°

Transparent filter
 6,2W
 24V DC
 2700K - 300lm / 3000K - 309lm
 CRI >90
 Beam 25°
 UGR <19
 Driver not included



Matt Black - 2700K
 Matt Black - 3000K

1A5180400.27.20
 1A5180400.30.20




BUJO TRIM - 32°

Transparent filter
 6,2W
 24V DC
 2700K - 279lm / 3000K - 288lm
 CRI >90
 Beam 32°
 UGR <19
 Driver not included



Matt Black - 2700K
 Matt Black - 3000K

1A5170400.27.20
 1A5170400.30.20



BUJO TRIM ELLIPTICAL

Transparent filter
 6,2W
 24V DC
 2700K - 263lm / 3000K - 271lm
 CRI >90
 UGR <19
 Driver not included



Matt Black - 2700K
 Matt Black - 3000K

1A5190400.27.20
 1A5190400.30.20

Compulsory accessories / Accessori obbligatori

Installation kits / Kit d'installazione




Installation box / Cassaforma

Standard Not included

1A5280000.00.00

Drivers / Alimentatori



Driver / Alimentatore

110-240V Not included

24V/25W/IP67/ON/OFF

1Z1120620

BUIO - SPOT


Maurici Ginés / 2023

Floor-Wall-Ceiling / Direct / Outdoor

Material

Finish .04 Matt Black

Note Outdoor luminaire. Adjustable spike and wall versions. Available with transparent or black glass. AISI 316L stainless steel accessories for the spike and wall versions. Black cable (1 m). *Apparecchio illuminante da esterno. Orientabile nella versione a picchetto e da parete. Disponibile con vetro trasparente o nero. Accessori per la versione a picchetto e da parete in inox AISI 316L. Cavo nero (1 m).*




BUIO - 13°

Black filter
6,2W
24V DC
2700K - 120lm / 3000K - 123lm
CRI >90
Beam 13°
UGR <19
Driver not included
CE IP67

Matt Black - 2700K
Matt Black - 3000K

1A5040400.27.20
1A5040400.30.20



BUIO - 25°


Black filter
6,2W
24V DC
2700K - 150lm / 3000K - 155lm
CRI >90
Beam 25°
UGR <19
Driver not included
CE IP67

Matt Black - 2700K
Matt Black - 3000K

1A5060400.27.20
1A5060400.30.20

Maurici Ginés / 2023

BUIO - SPOT




BUIO - 32°

Black filter
6,2W
24V DC
2700K - 140lm / 3000K - 144lm
CRI >90
Beam 32°
UGR <19
Driver not included
CE IP67

Matt Black - 2700K
Matt Black - 3000K

1A5050400.27.20
1A5050400.30.20




BUIO ELLIPTICAL

Black filter
6,2W
24V DC
2700K - 132lm / 3000K - 136lm
CRI >90
UGR <19
Driver not included
CE IP67

Matt Black - 2700K
Matt Black - 3000K

1A5070400.27.20
1A5070400.30.20




BUIO - 13°

Transparent filter
 6,2W
 24V DC
 2700K - 239lm / 3000K - 246lm
 CRI >90
 Beam 13°
 UGR <19
 Driver not included



Matt Black - 2700K
 Matt Black - 3000K

1A5080400.27.20
 1A5080400.30.20




BUIO - 25°

Transparent filter
 6,2W
 24V DC
 2700K - 300lm / 3000K - 309lm
 CRI >90
 Beam 25°
 UGR <19
 Driver not included



Matt Black - 2700K
 Matt Black - 3000K

1A5100400.27.20
 1A5100400.30.20




BUIO - 32°

Transparent filter
 6,2W
 24V DC
 2700K - 279lm / 3000K - 288lm
 CRI >90
 Beam 32°
 UGR <19
 Driver not included



Matt Black - 2700K
 Matt Black - 3000K

1A5090400.27.20
 1A5090400.30.20



BUIO ELLIPTICAL

Transparent filter
 6,2W
 24V DC
 2700K - 263lm / 3000K - 271lm
 CRI >90
 UGR <19
 Driver not included




Matt Black - 2700K
 Matt Black - 3000K

1A5110400.27.20
 1A5110400.30.20


Compulsory accessories / Accessori obbligatori

Installation kits / Kit d'installazione


Wall bracket / Staffa da parete		Not included
Stainless Steel	Brushed INOX	1A4431000.00.00




Ceiling rose / Rosone		Not included
Matt Black	Brushed INOX	1A4441000.00.00



Earth spike / Picchetto		Not included
Stainless Steel	Brushed INOX	1A4451000.00.00





Tree strap / Cinghia per albero		Not included
Standard	Length 1 m	1A4590000.00.00




Drivers / Alimentatori

Driver / Alimentatore		Not included
110-240V	24V/25W/IP67/ON/OFF	1Z1120620







A tool to light.

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.


CHILLOUT

/ 2011

Wall / Direct / Outdoor

Material Glass - Metal
Finish .03 Matt White

Note Outdoor wall luminaire. Adjustable along the vertical axis. *Apparecchio illuminante da esterno da parete. Orientabile lungo l'asse verticale.*



CHILLOUT

Max 12W - E27
100-240V - 50/60Hz
ON/OFF
Bulb not included
C E IP65

Matt White - ON/OFF

1A3660300.00.00

Optional accessories / Accessori opzionali

Installation kits / Kit d'installazione



Driver connector IP68 / Connettore driver IP68	Included
1 Piece	1A1660000.00.00

Bulbs / Lampadine



LED - E27 - PAR30s	Not included
220-240V - 9,5W - 25° 3000K - 760lm - CRI >80 Energy Efficiency F - Dimmable	1Y0330730





GRILLO

Daniele Sprega / 2012

A small luminous elf that you can install in your garden or inside a vase.
A thin stem stuck into the ground and a little adjustable LED projector.
For illuminating a flower, a plant or simply to accompany us along a path.
Lamp with spike.

Un piccolo elfo luminoso da installare in giardino o all'interno di un vaso.
Uno stelo sottile incastrato nel terreno e un piccolo proiettore a LED orientabile.
Per illuminare un fiore, una pianta o semplicemente per accompagnare un percorso.
Lampada con picchetto.


GRILLO

Daniele Sprega / 2012

Floor / Direct / Outdoor

Material AISI 316L Stainless Steel - Metal
Finish .04 Matt Black

Note Outdoor lamp with spike. Adjustable in all directions. AISI 316L stainless steel stem. Black cable (5 m). *Apparecchio illuminante da esterno a picchetto. Orientabile in tutte le direzioni. Stelo in inox AISI 316L. Cavo nero (5 m).*



GRILLO

4,2W
 24V DC
 2700K - 262lm / 3000K - 282lm
 CRI >90
 Driver not included


CE IP67

Matt Black - 2700K
 Matt Black - 3000K

1A3570400.27.20
 1A3570400.30.20

Compulsory accessories / Accessori obbligatori

Drivers / Alimentatori



Driver / Alimentatore		Not included
110-240V	24V/25W/IP67/ON/OFF	1Z1120620

Daniele Sprega / 2012

GRILLO

Optional accessories / Accessori opzionali

Installation kits / Kit d'installazione




Driver connector IP68 / Connettore driver IP68		Included
1 Piece		1A1660000.00.00



Additional stem 1 m / Stelo supplementare 1 m		Not included
Standard	AISI 316L stainless steel	1A3590000.00.00

Lighting modules / Corpi illuminanti



Additional LED head / Testa LED supplementare		Not included
Matt Black	24V DC - 4,2W 2700K - 262lm - CRI >90	1A3580400.27.20
	24V DC - 4,2W 3000K - 282lm - CRI >90	1A3580400.30.20



HAZARD

Davide Groppi / 2023

We have always been thrilled by bare, abandoned lamps.
On the walls of mountain huts, in the countryside of our plain.
Unfinished works, lamps still to be decided, ephemeral thoughts that become poetry.
Wall lamp with direct light for outdoor environments
with steel nail subject to natural oxidation over time.

Ci hanno sempre emozionato le lampadine abbandonate, nude.
Sui muri delle case di montagna, nelle campagne della nostra pianura.
Lavori non ancora finiti, lampade ancora da decidere,
pensieri effimeri che diventano poesia.
Lampada da parete a luce diretta per ambienti esterni
con chiodo in acciaio soggetto ad ossidazione naturale nel tempo.


HAZARD

Davide Groppi / 2023


Wall / Direct / Outdoor

Material Metal - Thermoplastic resin
Finish .00 Standard

Note Outdoor wall luminaire. Adjustable in all directions. One red and one black cable (1,5 m). *Apparecchio illuminante da esterno da parete. Orientabile in tutte le direzioni. Un cavo rosso e un cavo nero (1,5 m).*



HAZARD


0,6W - E27
36V DC
2200K - 50lm
CRI 80
Driver not included
Bulb included
CE  IP65

Standard - 2200K

| 1A4210000.22.20 |

Compulsory accessories / Accessori obbligatori

Drivers / Alimentatori



Driver / Alimentatore		Not included
110-240V	36V/36W/IP67/ON/OFF	1Z1120590








Light has found a home.
A lamp designed to welcome, illuminating the entrance.

La luce ha trovato casa.
Una lampada pensata per dare il benvenuto, per illuminare la soglia.

Wall / Direct / Outdoor

Material Metal
 Finish .00 Standard

Note Outdoor wall luminaire. Matt black body and matt red top cover. *Apparecchio illuminante da esterno da parete. Corpo nero opaco e tetto rosso opaco. Luce del foro rossa.*




IMU
 5,5W
 Max 350mA DC
 3000K - 306lm
 CRI >80
 Driver not included
 CE IP65

Standard - 3000K

1A3550000.30.20

Compulsory accessories / Accessori obbligatori

Drivers / Alimentatori



Driver / Alimentatore	Not included
220-240V(100-127V) 350mA/17W(15W)/IP68/ON/OFF	1Z0240880

Optional accessories / Accessori opzionali

Installation kits / Kit d'installazione



Driver connector IP68 / Connettore driver IP68	Included
1 Piece	1A1660000.00.00





Light, waiting for Romeo.
An outdoor light, for walls or to illuminate the entrance.

La luce, aspettando Romeo.
Una luce per esterno, sulle pareti o per illuminare le soglie.

JULIET


/ 2014

Wall / Diffuse / Outdoor

Material Glass - Metal
Finish .03 Matt White

Note Outdoor wall luminaire.

Apparecchio illuminante da esterno da parete.



JULIET

18W

220-240V - 50/60Hz

2700K - 827lm / 3000K - 865lm

CRI >80

TRIAC/IGBT

CE IP65

Matt White - 2700K - TRIAC/IGBT

1A3670300.27.02

Matt White - 3000K - TRIAC/IGBT

1A3670300.30.02

Optional accessories / Accessori opzionali

Installation kits / Kit d'installazione



Driver connector IP68 / Connettore driver IP68

Included

1 Piece

1A1660000.00.00






A lantern. Soft and diffuse light.
A Slow-Light project for outdoors.

Una lanterna, luce morbida e diffusa.
Un progetto di slow-light per l'outdoor.

Floor / Diffuse / Outdoor

Material Metal - Methacrylate - Polycarbonate
Finish .03 Matt White

Note Outdoor floor luminaire. Matt white diffuser. Black cable (5 m). *Apparecchio illuminante da esterno da terra. Diffusore bianco opaco. Cavo nero (5 m).*



LENTA

Max 18W - E27
 100-240V - 50/60Hz
 ON/OFF
 Bulb not included
 C E IP65

Matt White - ON/OFF

| 1A3630300.00.00 |

Optional accessories / Accessori opzionali

Installation kits / Kit d'installazione




Driver connector IP68 / Connettore driver IP68 Included
 1 Piece 1A1660000.00.00

Bulbs / Lampadine



LED - E27 - A60 Not included
 220-240V - 11,2W - 360°
 2700K - 1521lm - CRI >90
 Energy Efficiency D - Dimmable 1Y0330790

Other accessories / Altri accessori



IP65 Schuko adapter / Adattatore Schuko IP65 Not included
 IP65 1A2950000.00.00





NEURO OUTDOOR

Davide Groppi - Beppe Merlano / 2022

The idea is to bring light wherever you like.
A simple project: a cable and a LED.
Indoor version also available.

È l'idea di portare la luce dove si desidera.
Un progetto semplice: un cavo e un modulo LED.
Disponibile anche nella versione indoor.


NEURO OUTDOOR

Davide Groppi - Beppe Merlano / 2022

Suspension / Direct / Outdoor

Material AISI 316L Stainless Steel - Metal
Finish .04 Matt Black .32 Copper Oxide

Note Outdoor suspension luminaire. Black cable (10 m). *Apparecchio illuminante da esterno a sospensione. Cavo nero (10 m).*



NEURO OUTDOOR


4,2W
 24V DC
 2700K - 262lm / 3000K - 282lm
 CRI >90
 Driver not included
 CE IP67

Matt Black - 2700K
 Matt Black - 3000K
 Copper Oxide - 2700K
 Copper Oxide - 3000K

1A4030400.27.20
 1A4030400.30.20
 1A4033200.27.20
 1A4033200.30.20

Compulsory accessories / Accessori obbligatori

Drivers / Alimentatori



Driver / Alimentatore		Not included
110-240V	24V/25W/IP67/ON/OFF	1Z1120620

Optional accessories / Accessori opzionali

Installation kits / Kit d'installazione



Driver connector IP68 / Connettore driver IP68		Included
	1 Piece	1A1660000.00.00





NUIT


Maurici Ginés / 2023

Night has always been a source of inspiration.
We walk, and we are not alone.
Nuit is a small travel companion that draws our night-time journeys.

La notte è sempre fonte di ispirazione.
Camminiamo e non siamo soli.
Nuit è una piccola compagna di viaggio che disegna i nostri transiti notturni.

Recessed / Diffuse / Indoor-Outdoor

Material	Metal		
Finish	.03 Matt White	.27 Gravity Black	.38 Blasted Inox
Note	Outdoor recessed luminaire. Minimum space for recessed installation: 55 mm. <i>Apparecchio illuminante da esterno da incasso. Spazio minimo per incasso: 55 mm.</i>		




NUIT

1W
24V DC
2700K - 45lm / 3000K - 50lm
CRI >90
Driver not included
CE IP65

Matt White - 2700K	1A1320300.27.20
Matt White - 3000K	1A1320300.30.20
Gravity Black - 2700K	1A1322700.27.20
Gravity Black - 3000K	1A1322700.30.20
Blasted Inox - 2700K	1A1323800.27.20
Blasted Inox - 3000K	1A1323800.30.20


Compulsory accessories / Accessori obbligatori

Installation kits / Kit d'installazione



Concrete box / Cassaforma per cemento	Not included
Standard	1A4460000.00.00

Drivers / Alimentatori



Driver / Alimentatore	Not included	
110-240V	24V/25W/IP67/ON/OFF	1Z1120620

Optional accessories / Accessori opzionali

Installation kits / Kit d'installazione



Plasterboard frame 12,5 mm / Cornice per cartongesso 12,5 mm	Not included
Matt White	Cut-out 100x100 mm Minimum space for mounting 120 mm 1A4470000.00.00



Adapter plasterboard 25 mm / Adattatore per cartongesso 25 mm	Not included
Standard	1A5030000.00.00



ORIGINE OUTDOOR

Davide Groppi - Giorgio Rava / 2020

From the Latin "origo", start, birth, source.
It appears like a bud emerging from the ground and soaring upwards towards the sky,
a stem that becomes increasingly thinner. Mysterious, enigmatic but comfortable,
it combines the fascination of the unknown with the pleasure
of a sophisticated and elegant ambient light.

Origine sculpts and enhances every environment with its indirect light,
which is intentionally non-invasive, graphic and fascinating.

Indoor version also available.

**AZ Award 2021 and People's Choice
Archiproducts Design Award 2020**

Dal latino "origo", inizio, nascita, fonte.

Evoca un germoglio che emerge dalla terra e si slancia verso il cielo,
lo stelo che diventa sempre più sottile. Misteriosa, enigmatica ma confortevole,
unisce il fascino dell'incognito al piacere di una luce d'ambiente sofisticata ed elegante.

Origine scolpisce e valorizza ogni ambiente con la sua luce indiretta,
volutamente non invasiva, grafica e affascinante.

Disponibile anche nella versione indoor.

**AZ Award 2021 e People's Choice
Archiproducts Design Award 2020**

ORIGINE OUTDOOR


Davide Groppi - Giorgio Rava / 2020

Outdoor / Indirect / Outdoor

Material Glass fiber - Metal
Finish .04 Matt Black

Note Outdoor floor luminaire. Black cable (5 m).

Apparecchio illuminante da esterno da terra. Cavo nero (5 m).



ORIGINE OUTDOOR


35W
24V DC
2700K - 2872lm / 3000K - 2930lm
CRI >80
Driver not included
CE IP65

Matt Black - 2700K
Matt Black - 3000K

1A2480400.27.20
1A2480400.30.20

Compulsory accessories / Accessori obbligatori

Drivers / Alimentatori



Driver / Alimentatore		Not included
100-240V	24V/60W/IP67/1-10V	1Z1120260

Optional accessories / Accessori opzionali

Installation kits / Kit d'installazione



Driver connector IP68 / Connettore driver IP68		Included
	1 Piece	1A1660000.00.00





A tool to light.

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

OUT 44

/ 2021

Wall / Direct / Outdoor

Material Metal
Finish .04 Matt Black

Note Outdoor wall and ceiling luminaire. Adjustable along the vertical axis. *Apparecchio illuminante da esterno da parete e soffitto. Orientabile lungo l'asse verticale. Cavo nero.*



OUT 44 - 14°
 2W
 Max 500mA DC
 3000K - 133lm
 CRI >90
 Beam 14°
 Driver not included

Matt Black - 3000K

| 1A1600400.30.20 |

CE IP65



OUT 44 - 23°
 2W
 Max 500mA DC
 3000K - 133lm
 CRI >90
 Beam 23°
 Driver not included

Matt Black - 3000K

| 1A1610400.30.20 |


CE IP65

OUT 44

/ 2021

Compulsory accessories / Accessori obbligatori


Drivers / Alimentatori



Driver / Alimentatore		Not included
220-240V(110-127V)	500mA/24W(15W)/IP68/ON/OFF	1Z0241170

Optional accessories / Accessori opzionali

Installation kits / Kit d'installazione



Earth spike / Picchetto		Not included
Standard		1A1620000.00.00




Wall adapter plate / Piastra di adattamento da parete		Not included
Matt White		1A1630300.00.00
Matt Black		1A1630400.00.00



Driver connector IP68 / Connettore driver IP68		Not included
1 Piece		1A1660000.00.00





A tool to light.

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

OUT 58

/ 2021

Recessed / Direct / Outdoor

Material Glass - Metal
Finish .10 Stainless Steel

Note Outdoor recessed luminaire. AISI 316L stainless steel body. *Apparecchio illuminante da esterno da incasso. Corpo in inox AISI 316L.*



OUT 58

7W
 24V DC
 3000K - 546lm
 CRI >90
 Driver not included
 CE IP67

Stainless Steel - 3000K

1A1551000.30.20

Compulsory accessories / Accessori obbligatori

Installation kits / Kit d'installazione




Installation box / Cassaforma

Not included

Standard	Cut-out 55 mm Minimum space for mounting 110 mm	1A1560000.00.00
----------	--	-----------------

Drivers / Alimentatori



Driver / Alimentatore

Not included

110-240V	24V/25W/IP67/ON/OFF	1Z1120620
----------	---------------------	-----------

Optional accessories / Accessori opzionali

Installation kits / Kit d'installazione




Driver connector IP68 / Connettore driver IP68

Included

1 Piece	1A1660000.00.00
---------	-----------------





A tool to light.

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

Recessed / Direct / Outdoor

Material Glass - Metal
Finish .10 Stainless Steel

Note Outdoor recessed luminaire. AISI 316L stainless steel body. *Apparecchio illuminante da esterno da incasso. Corpo in inox AISI 316L.*



OUT 100 - 15°
 20W
 Max 500mA DC
 3000K - 2058lm
 CRI >90
 Beam 15°
 Driver not included
 CE IP67

Stainless Steel - 3000K

| 1A1571000.30.20 |



OUT 100 - 23°
 20W
 Max 500mA DC
 3000K - 2058lm
 CRI >90
 Beam 23°
 Driver not included
 CE IP67

Stainless Steel - 3000K

| 1A1581000.30.20 |


Compulsory accessories / Accessori obbligatori

Installation kits / Kit d'installazione



Installation box / Cassaforma		Not included
Standard	Cut-out 94 mm Minimum space for mounting 160 mm	1A1590000.00.00

Drivers / Alimentatori



Driver / Alimentatore		Not included
220-240V(110-127V)	500mA/24W(15W)/IP68/ON/OFF	1Z0241170

Optional accessories / Accessori opzionali

Installation kits / Kit d'installazione



Driver connector IP68 / Connettore driver IP68		Not included
	1 Piece	1A1660000.00.00




A piece of architecture to be used in space.
A concrete cube that allows you to understand volumes and architecture
in an unusual and sometimes unprecedented way.
Indoor version also available.

Un pezzo di architettura da utilizzare nello spazio.
Un cubo realizzato in cemento che permette di interpretare i volumi e le architetture
in modo inconsueto e talvolta inedito.
Disponibile anche nella versione indoor.

Floor / Direct / Outdoor

Material Cement - Metal
 Finish .00 Standard

Note Outdoor floor luminaire. Concrete body. Black cable (2,5 m). *Apparecchio illuminante da esterno da terra. Corpo in cemento. Cavo nero (2,5 m).*




Q²
 20W
 Max 500mA DC
 3000K - 2058lm
 CRI >90
 Driver not included
 CE IP67

Standard - 3000K

| 1A1150000.30.20 |

Compulsory accessories / Accessori obbligatori

Drivers / Alimentatori



Driver / Alimentatore	Not included
220-240V(110-127V) 500mA/24W(15W)/IP68/ON/OFF	1Z0241170

Optional accessories / Accessori opzionali

Installation kits / Kit d'installazione



Driver connector IP68 / Connettore driver IP68	Included
1 Piece	1A1660000.00.00



SAMPEI 440 OUTDOOR

Enzo Calabrese - Davide Groppi / 2011



A special project, an authentic ready-made.
Obtained from a fishing flexible rod, it is a delicate and elegant sign,
which brings to mind the subtle branches of a willow tree
or bamboo canes floating on a light breeze.

Sampei is an unexpected gift, it is the magic of looking up,
using light as a hook, and being amazed by so much weightlessness.
Indoor version also available.

Un progetto speciale, un autentico ready-made.
Ricavata da una canna da pesca flessibile, è un segno delicato ed elegante,
che fa pensare a effimeri rami di salice, a canne di bambù mosse da un debole vento.
Sampei è un regalo inaspettato, è la magia di guardare in alto,
usando la luce come amo, e stupirsi di tanta leggerezza.
Disponibile anche nella versione indoor.

Compasso d'Oro ADI
Award 2014




SAMPEI 440 OUTDOOR

Enzo Calabrese - Davide Groppi / 2011

Floor / Direct / Outdoor

Material Glass fiber - Metal
Finish .03 Matt White .04 Matt Black

Note Outdoor floor luminaire. Adjustable in all directions. Black cable (5 m). *Apparecchio illuminante da esterno da terra. Orientabile in tutte le direzioni. Cavo nero (5 m).*



SAMPEI 440 OUTDOOR

8,4W
 Max 700mA DC
 2700K - 639lm / 3000K - 639lm
 CRI >90
 Driver not included


CE IP65

Matt White - 2700K
 Matt White - 3000K
 Matt Black - 2700K
 Matt Black - 3000K

1A3770300.27.20
 1A3770300.30.20
 1A3770400.27.20
 1A3770400.30.20

Compulsory accessories / Accessori obbligatori

Drivers / Alimentatori



Driver / Alimentatore	Not included
220-240V(100-127V) 700mA/30W(15W)/IP68/ON/OFF	1Z0241110

Optional accessories / Accessori opzionali

Installation kits / Kit d'installazione



Driver connector IP68 / Connettore driver IP68	Included
1 Piece	1A1660000.00.00



SHOJI OUTDOOR

Davide Groppi - Paola Lenti / 2013



A nylon lampshade, strictly hand-stitched and hand-made.
Indoor version also available.

Un paralume in nylon rigorosamente cucito e confezionato a mano.
Disponibile anche nella versione indoor.


SHOJI OUTDOOR

Davide Groppi - Paola Lenti / 2013

Floor / Diffuse / Outdoor

Material Metal - PBT - Polycarbonate
Finish .00 Standard

Note Outdoor floor luminaire. Hand-stitched shade. Matt black stems. Black cable (5 m). *Apparecchio illuminante da esterno da terra. Paralume cucito a mano. Steli nero opaco. Cavo nero (5 m).*



SHOJI

Max 18W - E27
100-240V - 50/60Hz
ON/OFF
Bulb not included
C E IP65

Standard - ON/OFF

| 1A3640000.00.00 |

Optional accessories / Accessori opzionali

Installation kits / Kit d'installazione




Driver connector IP68 / Connettore driver IP68	Included
1 Piece	1A1660000.00.00

Bulbs / Lampadine



LED - E27 - A60	Not included
220-240V - 11,2W - 360° 2700K - 1521lm - CRI >90 Energy Efficiency D - Dimmable	1Y0330790

Other accessories / Altri accessori



IP65 Schuko adapter / Adattatore Schuko IP65	Not included
IP65	1A2950000.00.00



A tool to light.

**The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.**

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.


SPOT OUTDOOR

/ 2018

Wall / Direct / Outdoor

Material Metal
Finish .03 Matt White .04 Matt Black

Note Outdoor wall and ceiling luminaire. Adjustable in all directions. *Apparecchio illuminante da esterno da parete e soffitto. Orientabile in tutte le direzioni.*



SPOT OUTDOOR

8,4W
 Max 700mA DC
 2700K - 639lm / 3000K - 639lm
 CRI >90
 Driver not included


CE IP65

Matt White - 2700K
 Matt White - 3000K
 Matt Black - 2700K
 Matt Black - 3000K

1A3650300.27.20
 1A3650300.30.20
 1A3650400.27.20
 1A3650400.30.20

Compulsory accessories / Accessori obbligatori

Drivers / Alimentatori



Driver / Alimentatore	Not included
220-240V(100-127V) 700mA/30W(15W)/IP68/ON/OFF	1Z0241110














Optional accessories / Accessori opzionali

Installation kits / Kit d'installazione





Driver connector IP68 / Connettore driver IP68	Included
1 Piece	1A1660000.00.00












BULBS / LAMPADINE

	Socket	Voltage	Power	Beam Angle	CCT	Lumens	CRI	Energy Efficiency	Dimmable	Code
	E14	220-240V	4,5W		2700K	470lm	>80	F	X	1Y0041410
	E27	220-240V	7W	360°	2700K	806lm	>80	E	X	1Y2080010
	E27	220-240V	11,2W	360°	2700K	1521lm	>90	D	X	1Y0330790
	E27	220-240V	20W	200°	2700K	2452lm	>80	E	X	1Y2160020
	E27	220-240V	9,5W	25°	3000K	760lm	>80	F	X	1Y0330730
	GU4	12V	4W	24°	2700K	200lm	>80	G	-	1Y0330450
	GU5,3	12V	6,7W	36°	3000K	440lm	>97	G	X	1Y0330530
	GU10	220-240V	4,9W	120°	3000K	550lm	>80	E	-	1Y0330740
	GU10	220-240V	5,5W	25°	3000K	375lm	>97	G	X	1Y0330500
	GU10	230V	7,5W	10°	2700K	390lm	>95	G	X	1Y1580210
	GU10	230V	7,5W	10°	3000K	410lm	>95	G	X	1Y1580010
	R7s	220-240V	4W	330°	3000K	450lm	>80	E	-	1Y0000138
	R7s	220-240V	8W	330°	3000K	1000lm	>80	E	-	1Y0000139







DG111 LED MODULES / MODULI LED DG111

	Current	Power	Beam Angle	CCT	Lumens	CRI	Energy Efficiency	Dimmable	Code
	350mA DC	11,7W	15°	2700K	1336lm	>90	F	X	1A4700000.27.20
	350mA DC	11,7W	15°	3000K	1364lm	>90	F	X	1A4700000.30.20
	350mA DC	11,7W	22°	2700K	1266lm	>90	F	X	1A3890000.27.20
	350mA DC	11,7W	22°	3000K	1323lm	>90	F	X	1A3890000.30.20
	350mA DC	11,7W	36°	2700K	1508lm	>90	F	X	1A3900000.27.20
	350mA DC	11,7W	36°	3000K	1578lm	>90	F	X	1A3900000.30.20
	500mA DC	16,7W	15°	2700K	1648lm	>90	F	X	1A4700000.27.20
	500mA DC	16,7W	15°	3000K	1682lm	>90	F	X	1A4700000.30.20
	500mA DC	16,7W	22°	2700K	1859lm	>90	F	X	1A3890000.27.20
	500mA DC	16,7W	22°	3000K	1945lm	>90	F	X	1A3890000.30.20
	500mA DC	16,7W	36°	2700K	1808lm	>90	F	X	1A3900000.27.20
	500mA DC	16,7W	36°	3000K	1890lm	>90	F	X	1A3900000.30.20










DRIVERS / ALIMENTATORI

	Power	Input	Output	Dimming	Protection	Code
	60W(40W)	220-240V(100-127V)	1000mA	DALI	IP20	1Z0241140.1000
	50W	230-240V	12V	TRIAC/IGBT	IP20	1Z0240440
	50W	100-240V	24V	ON/OFF	IP20	1Z1120490
	80W	100-240V	24V	ON/OFF	IP20	1Z1120440
	20W	220-240V	24V	TRIAC/IGBT	IP20	1Z0240850.24
	16W(15W)	220-240V(100-127V)	24V	DALI	IP20	1Z0241180.24
	20W(15W)	220-240V(100-127V)	24V	PUSH	IP20	1Z0240870.24
	12,5W	220-240V	250mA	TRIAC/IGBT	IP20	1Z0241280
	4,2W	220-240V	250mA	TRIAC/IGBT	IP20	1Z2320010
	13,5W(13,5W)	220-240V(110-127V)	250mA	DALI - PUSH - 1-10V	IP20	1Z0241270.250
	17W	220-240V	350mA	TRIAC/IGBT	IP20	1Z0240850.350




DRIVERS / ALIMENTATORI

	Power	Input	Output	Dimming	Protection	Code
	17W(15W)	220-240V(100-127V)	350mA	DALI	IP20	1Z0241180.350
	18W(15W)	220-240V(100-127V)	350mA	PUSH - 1-10V	IP20	1Z0240870.350
	18W(18W)	220-240V(100-127V)	350mA	DALI - PUSH - 1-10V	IP20	1Z0240530.350
	60W	220-240V	48V	DALI	IP20	1Z0830820
	20W	220-240V	500mA	TRIAC/IGBT	IP20	1Z0240850.500
	20W(15W)	220-240V(100-127V)	500mA	DALI	IP20	1Z0241180.500
	20W(15W)	220-240V(100-127V)	500mA	PUSH	IP20	1Z0240840.500
	20W(15W)	220-240V(100-127V)	500mA	PUSH - 1-10V	IP20	1Z0240870.500
	25W(13,5W)	220-240V(110-127V)	500mA	DALI - PUSH - 1-10V	IP20	1Z0241270.500
	17,5W	100-240V	5V	ON/OFF	IP20	1Z1120180


DRIVERS / ALIMENTATORI

	Power	Input	Output	Dimming	Protection	Code
	150W	100-240V	24V	1-10V	IP67	1Z1120500
	60W	100-240V	24V	1-10V	IP67	1Z1120260
	96W	100-240V	24V	1-10V	IP67	1Z1120540
	25W	110-240V	24V	ON/OFF	IP67	1Z1120620
	36W	110-240V	36V	ON/OFF	IP67	1Z1120590
	150W	100-240V	48V	1-10V	IP67	1Z1120250
	240W	100-240V	48V	1-10V	IP67	1Z1120390
	320W	100-240V	48V	1-10V	IP67	1Z1120380
	60W	100-240V	48V	ON/OFF	IP67	1Z1120640
	80W	100-240V	48V	1-10V	IP67	1Z1120400




DRIVERS / ALIMENTATORI

	Power	Input	Output	Dimming	Protection	Code
	17W(15W)	220-240V(100-127V)	350mA	ON/OFF	IP68	1Z0240880
	24W(15W)	220-240V(110-127V)	500mA	ON/OFF	IP68	1Z0241170
	30W(15W)	220-240V(100-127V)	700mA	ON/OFF	IP68	1Z0241110

COMMON ACCESSORIES / ACCESSORI COMUNI


Power	Input	Output	Dimming	Protection	Code
Controller Casambi - Radio signal 2.4 - 2.486 GHz					
	220-240V - 50Hz		DALI	IP20	1Z0400740
	220-240V - 50Hz		1-10 V	IP20	1Z0400660
(75W) 150W	(110V) 240V - 50/60Hz		TRIAC	IP20	1Z0400670

COMMON ACCESSORIES / ACCESSORI COMUNI

Size	Cut-out	Finish	Code
Plasterboard trapdoors / Botole in cartongesso			
 200x200 mm	205x205 mm	Standard	1A3780000.00.00
 400x400 mm	415x415 mm	Standard	1A3790000.00.00
Clamp / Bloccacavo			
 Ø 50x20 mm		Matt White	1A3270300.00.00
		Matt Black	1A3270400.00.00
Driver connector IP68 / Connettore driver IP68			
		Standard	1A1660000.00.00

SUSPENSION KITS / KIT DI SOSPENSIONE

Recessed suspension kit / Kit di sospensione da incasso



Suspension kit for 12,5 mm plasterboard
Plasterboard cut-out Ø 44 mm
Minimum space for mounting 70 mm

Kit di sospensione per cartongesso 12,5 mm
Dimensioni taglio cartongesso Ø 44 mm
Spazio minimo per incasso 70 mm


Magnetic fixing
Fissaggio magnetico



Version	Use	Product reference	Finish	Code		
Recessed suspension kit.01	For suspension cables	REFLEX S 1	Matt White	1X0000300.01.00		
		REFLEX S 2				
		SHANGHAI 1				
		SHANGHAI 2				
		SOTTILE 1				
Recessed suspension kit.02	For electrical cables	SOTTILE 1 DE	Matt Black	1X0000400.01.00		
		SOTTILE 2				
		SOTTILE 2 DE				
		MAGIA			Matt White	1X0000300.02.00
		MAGIA			Matt Black	1X0000400.02.00
Recessed suspension kit.03	For suspension cables	MASAI 1	Matt White	1X0000300.03.00		
		MASAI 2				
		SPY DE			Matt Black	1X0000400.03.00
Recessed suspension kit.04	For electrical cables	ASINTOTO	Matt White	1X0000300.04.00		
		REFLEX S 2				
		SHANGHAI 2			Matt Black	1X0000400.04.00
Recessed suspension kit.05	For electrical cables	SOTTILE 2	Matt White	1X0000300.05.00		
		SOTTILE 2 DE			Matt Black	1X0000400.05.00

SUSPENSION KITS / KIT DI SOSPENSIONE

Ceiling suspension kit / Kit di sospensione da soffitto



Back plate for masonry ceilings
Back plate per soffitti in muratura

Magnetic fixing
Fissaggio magnetico



Version	Use	Product reference	Finish	Code		
Ceiling suspension kit.01	For suspension cables	REFLEX S 1	Matt White	1X0010300.01.00		
		REFLEX S 2				
		SHANGHAI 1				
		SHANGHAI 2				
		SOTTILE 1				
Ceiling suspension kit.02	For electrical cables	SOTTILE 1 DE	Matt Black	1X0010400.01.00		
		SOTTILE 2				
		SOTTILE 2 DE				
		MAGIA			Matt White	1X0010300.02.00
		MAGIA			Matt Black	1X0010400.02.00
Ceiling suspension kit.03	For suspension cables	MASAI 1	Matt White	1X0010300.03.00		
		MASAI 2				
		SPY DE			Matt Black	1X0010400.03.00
Ceiling suspension kit.04	For electrical cables	ASINTOTO	Matt White	1X0010300.04.00		
		REFLEX S 2				
		SHANGHAI 2			Matt Black	1X0010400.04.00
Back plate	For masonry ceilings	SOTTILE 2	Matt White	1X0050300.01.00		
		SOTTILE 2 DE				

COMMERCIAL TERMS / CONDIZIONI COMMERCIALI

General terms.

This document replaces any other previous one.

Davide Groppi srl reserves the right to change its products without notice. In this case, the descriptions printed here are not binding.

The sizes are expressed in millimeters.

Shipment.

Returned merchandise must be authorized in writing by Davide Groppi srl.

Any claim must be made in writing to Davide Groppi srl within 7 days of the delivery date. If not, will not be accepted.

Warranty.

All products are guaranteed for 24 months from the date of delivery.

The warranty is not valid for damage caused by third parties.

Any damage resulting from improper installation or changes to products cannot be considered the responsibility of Davide Groppi srl.

Rights.

No part of this document may be reproduced or transmitted in any form or by any means: electronic, mechanical or otherwise, without the written permission of Davide Groppi srl.

Jurisdiction.

For any dispute, Piacenza, Italy, will be the court of jurisdiction.

Privacy.

Davide Groppi srl protects the confidentiality of personal data as provided to articles 12, 13 and 14 of the European Regulation n. 679/2016 (GDPR).

Condizioni generali.

Il presente documento annulla e sostituisce ogni edizione precedente.

Davide Groppi srl si riserva la facoltà di modificare i propri prodotti senza preavviso pertanto le descrizioni riportate in questo documento non sono vincolanti.

Le dimensioni sono espresse in millimetri.

Spedizioni.

Resi di materiale sono accettati previa autorizzazione scritta dell'azienda.

Eventuali reclami sono considerati solo se comunicati per iscritto entro 7 giorni dalla data di consegna della merce.

Garanzia.

I prodotti di Davide Groppi srl sono garantiti per 24 mesi dalla data di consegna.

La garanzia non ha valore per danni causati da terzi.

Eventuali danni derivanti da errata installazione o da modifiche apportate ai prodotti non possono essere considerati responsabilità di Davide Groppi srl.

Diritti.

Nessuna parte di questo documento può essere riprodotta o trasmessa in qualsiasi forma o con qualsiasi mezzo elettronico, meccanico o altro senza l'autorizzazione scritta di Davide Groppi srl.

Foro Competente.

Per eventuali controversie è competente il Foro di Piacenza.

Privacy.

La Davide Groppi srl tutela la riservatezza dei dati personali come previsto degli art. 12, 13 e 14 del Regolamento Europeo n. 679/2016 (GDPR).

davidegroppi.com

Davide Groppi s.r.l.
Via Belizzi 20 / 22
29122 Piacenza - Italia
+39.0523.571590
info@davidegroppi.com

Davide Groppi s.r.l. © 2024
Company with sole shareholder under the direction and coordination of Dexelance