



16100303	MATT WHITE	120 V - 60 Hz - 5,5 W LED - 3000K - 420 lm
16100403	MATT BLACK	WHITE CABLE - WHITE CEILING ROSE - NOT DIMMABLE
16100803	BRUSHED BRASS	120 V - 60 Hz - 5,5 W LED - 3000K - 420 lm
		BLACK CABLE - BLACK CEILING ROSE - NOT DIMMABLE



16110303	MATT WHITE	350 mA DC - 4 W LED - 3000K - 420 lm WHITE CABLE - WHITE CEILING ROSE
16110403	MATT BLACK	350 mA DC - 4 W LED - 3000K - 420 lm BLACK CABLE - BLACK CEILING ROSE
		INSTALLATION ON PLASTERBOARD WITH FLAT ROSE AND MAGNETIC FIXING
		COMPULSORY INSTALLATION KIT INCLUDED
		PLASTERBOARD CUT-OUT 85 x 97 mm
		MINIMUM SPACE FOR MOUNTING 120 mm
		NOT DIMMABLE
		INCLUDES LED DRIVER INPUT 100 / 240 V - 50 / 60 Hz - OUTPUT 350 mA DC
16110803	BRUSHED BRASS	350 mA DC - 4 W LED - 3000K - 420 lm BLACK CABLE - BLACK CEILING ROSE
		INSTALLATION ON PLASTERBOARD WITH FLAT ROSE AND MAGNETIC FIXING
		COMPULSORY INSTALLATION KIT INCLUDED
		PLASTERBOARD CUT-OUT 85 x 97 mm
		MINIMUM SPACE FOR MOUNTING 120 mm
		NOT DIMMABLE
		INCLUDES LED DRIVER INPUT 100 / 240 V - 50 / 60 Hz - OUTPUT 350 mA DC